MSDS Page 1 of 8

PDF Copy





View (M)SDS Section: 1 2 6 7 8 9 10 11 12 13 14 15 16 3 5

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product Name: **BEHR Interior/Exterior Alkyd Satin Enamel -**

White Base

7900 Product Code: 7900 SDS Manufacturer

Number:

Manufacturer Name: BEHR Process Corporation Address: 3400 W. Segerstrom Avenue

Santa Ana, CA 92704

General Phone

Number:

(714) 545-7101

General Fax

(714) 241-1002

Number:

Customer Service Phone Number:

(800) 854-0133 ext. 2

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

SDS Creation Date: September 23, 2016 October 20, 2017 SDS Revision Date:

(M)SDS Format: In accordance with 2012 OSHA Hazardous

Communication Standard

SECTION 2: HAZARD(S) IDENTIFICATION

GHS Pictograms:



Signal Word: Warning.

GHS Class: Eye Irritant, Category 2B.

Skin Irritant, Category 2.

Hazard Statements:

MSDS Page 2 of 8

Causes eye irritation. Causes skin irritation.

Precautionary Statements:

Wear protective clothing, gloves, eye, and face protection. Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Dispose of unused contents, container, and other contaminated wastes in accordance with local, state, federal, and provincial regulations. **If in eyes**: Rinse cautiously with water for several minutes and remove contacts if present and easy to do. Continue rinsing and get

medical attention if eye irritation persists.

If on skin: Wash with plenty of soap and water.

If swallowed: Rinse mouth and get medical attention if you feel

unwell.

Emergency Overview: Irritant.

Route of Exposure: Eyes. Skin. Inhalation. Ingestion.

Potential Health Effects:

Eye: Causes eye irritation.

Skin: Causes skin irritation.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract

irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation.

Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Conditions: None generally recognized.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS# | Ingredient Percent | EC Num. |
|---|-----------------|-----------------------|------------|
| Titanium dioxide | 13463- | 10 - 30 by | 236- |
| | 67-7 | weight | 675-5 |
| Nepheline Syenite | 37244- 96-5 | 5 - 10 by weight | |
| Silica, amorphous, precipitated and gel | 112926- 00-8 | 1 - 5 by weight | |
| Aluminum hydroxide | 21645- | 1 - 5 by | 244- |
| | 51-2 | weight | 492-7 |
| Xylene | 1330- | 0.1 - 1 by | 215- |
| | 20-7 | weight | 535-7 |

MSDS Page 3 of 8

Oxirane,[[(2-Ethylhexyl)Oxy]Methyl]-, Reaction Products W/Polyethylene Glycol Ether W/2,4,7,9-TetraMethyl-5-Decyne-4-,7-Diol(2:1)

58-1

857892-

0.1 - 1 by

weight

SECTION 4: FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20

minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of

overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial

respiration or give oxygen by trained personnel. Seek immediate

medical attention.

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison

control center immediately. Never give anything by mouth to an

unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Flash Point: None.

Lower Not applicable.

Flammable/Explosive

Limit:

Upper Not applicable.

Flammable/Explosive

Limit

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog

or spray when fighting fires involving this material.

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA),

MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Ratings:

NFPA Health: 1
NFPA Flammability: 1
NFPA Reactivity: 0

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Evacuate area and keep unnecessary and unprotected personnel from

entering the spill area. Use proper personal protective equipment as

listed in Section 8.

MSDS Page 4 of 8

Environmental Precautions:

Avoid runoff into storm sewers, ditches, and waterways.

Methods for containment:

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide

ventilation.

Methods for cleanup:

Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water to

remove trace residue.

SECTION 7: HANDLING and STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with

eyes, skin and clothing.

Storage: Store in a cool, dry, well ventilated area away from sources of heat,

combustible materials, and incompatible substances. Keep container

tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin.

Avoid inhaling vapor or mist.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

Engineering Controls: Use appropriate engineering control such as process enclosures, local

exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and

maintenance of the personal protective equipment.

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by

29 CFR 1910.133, OSHA eye and face protection regulation, or the

European standard EN 166.

Skin Protection Description:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with

eyes, skin or clothing.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor

cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide

adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an

eyewash facility and a safety shower.

PPE Pictograms:

MSDS Page 5 of 8





EXPOSURE GUIDELINES

Titanium dioxide:

Guideline ACGIH: TLV-TWA: 10 mg/m3

Silica, amorphous, precipitated and gel:
Guideline OSHA: PEL-TWA: 20 mppcf

Xylene:

Guideline ACGIH: TLV-STEL: 150 ppm

TLV-TWA: 100 ppm

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

Physical State: Liquid.
Color: White
Odor: Slight.

Odor Threshold:

Boiling Point:

Not applicable.

>99°F (>37°C)

Melting Point:

Not applicable.

Density:

10.88 Lbs/gal

Solubility:

Not applicable.

Vapor Density:

Not applicable.

Vapor Pressure:

Not applicable.

pH: 7 - 10 Viscosity: 50-140

Coefficient of Water/Oil

Evaporation Rate:

Distribution:

Not applicable.

Not applicable.

Flammability: Not applicable.

Flash Point: None.

VOC Content: Material VOC: 16 gm/L(Includes Water)

Coating VOC.:38 gm/L(Excludes Water)

SECTION 10: STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Not reported.

Polymerization:

MSDS Page 6 of 8

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures

below 32 deg. F.

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

Eye: No relevant toxicological data for classification were found.

Skin: No relevant toxicological data for classification were found.

Inhalation: No relevant toxicological data for classification were found.

Ingestion: No relevant toxicological data for classification were found.

Xylene:

Eye: Administration into the eye - Rabbit Standard Draize test: 87 mg [Mild]

Administration into the eye - Rabbit Standard Draize test: 5 mg/24H

[Severe] (RTECS)

Skin: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent

kill: >1700 mg/kg [Details of toxic effects not reported other than

lethal dose value] (RTECS)

Inhalation: Inhalation - Rat LC50 - Lethal concentration, 50 percent kill: 5000

ppm/4H [Details of toxic effects not reported other than lethal dose

value] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 4300 mg/kg [Liver -

Other changes Kidney/Ureter/Bladder - Other changes] (RTECS)

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the

classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the

EPA and/or state and local guidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

MSDS Page 7 of 8

IATA Shipping Name: Not restricted as a dangerous good. IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Not restricted as a dangerous good.

Name:

Canadian UN Number: Not restricted as a dangerous good. IMDG UN Number: Not restricted as a dangerous good. IMDG Shipping Name: Not restricted as a dangerous good. ADR UN Number: Not restricted as a dangerous good. ADR Shipping Name: Not restricted as a dangerous good.

SECTION 15: REGULATORY INFORMATION

<u>Titanium dioxide</u>:

TSCA Inventory Status: Listed Canada DSL: Listed

EC Number: 236-675-5

Nepheline Syenite:

Canada DSL: Listed

Silica, amorphous, precipitated and gel:

Canada DSL: Listed

Aluminum hydroxide:

TSCA Inventory Status: Listed Canada DSL: Listed

EC Number: 244-492-7

Xylene:

TSCA Inventory Status: Listed

Section 313: EPCRA - 40 CFR Part 372 - (SARA Title III) Section 313 Listed

Chemical.

Canada DSL: Listed

EC Number: 215-535-7

Oxirane,[[(2-Ethylhexyl)Oxy]Methyl]-, Reaction Products W/Polyethylene Glycol Ether W/2,4,7,9-TetraMethyl-5-Decyne-4-,7-Diol(2:1):

Canada DSL: Listed

SECTION 16: ADDITIONAL INFORMATION

MSDS Page 8 of 8

HMIS Ratings:

HMIS Health Hazard: 1
HMIS Fire Hazard: 1
HMIS Reactivity: 0
HMIS Other: x

SDS Creation Date: September 23, 2016 SDS Revision Date: October 20, 2017

SDS Format: In accordance with 2012 OSHA Hazardous Communication

Standard

SDS Author: Actio Corporation

Disclaimer: This Health and Safety Information is correct to the best of our

knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose

address is at the top of this data sheet.

Trademark: The trademarks, service marks, graphics and logos used on this MSDS

are registered or unregistered trademarks of BEHR Process

Corporation. All Rights Reserved.

Copyright© 1996-2018 Enviance. All Rights Reserved.