

SAFETY DATA SHEET

Version 8.6 Revision Date 07/02/2024 Print Date 07/03/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifiers

Product name : Hydrofluoric Acid 47-51% OmniTrace(R)

Product Number : HX0627
Brand : Millipore
CAS-No. : 7664-39-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis

Uses advised against : The product is being supplied under the TSCA R&D Exemption

(40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by

MilliporeSigma.

1.3 Details of the supplier of the safety data sheet

Company : Sigma-Aldrich Inc.

3050 SPRUCE ST ST. LOUIS MO 63103 UNITED STATES

Telephone : +1 314 771-5765 Fax : +1 800 325-5052

1.4 Emergency telephone

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-

527-3887 CHEMTREC (International) 24

Hours/day; 7 Days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Acute toxicity, Oral (Category 2), H300 Acute toxicity, Inhalation (Category 2), H330 Acute toxicity, Dermal (Category 1), H310 Skin corrosion (Category 1A), H314 Serious eye damage (Category 1), H318

Millipore - HX0627



Page 1 of 13

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram Signal Word Danger Hazard Statements H300 + H310 + H330 Fatal if swallowed, in contact with skin or if inhaled. H314 Causes severe skin burns and eye damage. **Precautionary Statements** P260 Do not breathe mist or vapors. P262 Do not get in eyes, on skin, or on clothing. Wash skin thoroughly after handling. P264 P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 Wear respiratory protection. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P301 + P310 + P330 Rinse mouth. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P302 + P350 + P310 IF ON SKIN: Gently wash with plenty of soap and water. Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF INHALED: Remove person to fresh air and keep comfortable P304 + P340 + P310 for breathing. Immediately call a POISON CENTER/ doctor. P305 + P351 + P338 + IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue P310 rinsing. Immediately call a POISON CENTER/ doctor. Take off contaminated clothing and wash before reuse. P362 P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

plant.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

P501

| Component | | Classification | Concentration |
|-------------------|--------------|--------------------------|---------------|
| Hydrofluoric acid | | | |
| CAS-No. | 7664-39-3 | Acute Tox. 2; Acute Tox. | >= 50 - < 70 |
| EC-No. | 231-634-8 | 1; Skin Corr. 1A; Eye | % |
| Index-No. | 009-002-00-6 | Dam. 1; H300, H330, | |
| | | H310, H314, H318 | |

Dispose of contents/ container to an approved waste disposal

Millipore - HX0627 Page 2 of 13



| Concentration limits: >= 7 %: Skin Corr. 1A, H314; 1 - < 7 %: Skin | |
|--|--|
| Corr. 1B, H314; 0.1 - < 1 %: Eye Irrit. 2, H319; | |

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Countermeasurements must be implemented at once. First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. Keep respiratory tract clear. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

After contact with skin: Rinse with plenty of water for at least 10 minutes. Immediately remove contaminated clothes. Apply calcium gluconate gel (preparation: boil 5 g of calcium gluconate in 85 ml of hot distilled water, add 10 g glycerol. Allow 5 g of Carmellose-sodium to swell in the hot solution. Stable for 6 months, store in a cool place) and massage into the skin until the pain subsides, in between rinse with water and apply fresh gel. Continue gel therapy for another 15 minutes after the pain has subsided. If no calcium gluconate gel is available, apply several dressings thoroughly moistened with 20 % calcium gluconate solution. Medical advice absolutely required!

In case of eye contact

After contact with eyes: Rinse with plenty of water keeping eyelids open, protecting the unaffected eye (at least 10 minutes). Seek medical advice immediately! Remove contact lenses.

If swallowed

After swallowing: Immediately give to drink plenty of water, add calcium (in the form of calcium gluconate or calcium lactate). Caution: In the case of vomiting risk of perforation! Administer more calcium gluconate solution. Laxative: Sodium sulfate (1 tablespoon/1/4 l water). Seek medical advice immediately. Ensure that injured persons remain calm and protect them against heat loss.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

Note for the doctor: It is recommended to consult a doctor with experience in the

treatment of lesions caused by hydrofluoric acid. If a systemic effect is suspected,

monitoring and treatment in an intensive care unit is urgently required. Caution, ventricular
fibrillation due to electrolyte imbalance.

Millipore - HX0627



MILLIPORE



SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Hydrogen fluoride

Not combustible.

Fire may cause evolution of:

Hydrogen fluoride

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® HF, Merck Art. No. 101591). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Hygiene measures

Millipore - HX0627

Page 4 of 13



Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Recommended storage temperature see product label.

Storage class

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

| Ingredients with | | | ameters | |
|-------------------|-----------|--------------------------------|------------|---|
| Component | CAS-No. | Value | Control | Basis |
| | | | parameters | |
| Hydrofluoric acid | 7664-39-3 | TWA | 0.5 ppm | USA. ACGIH Threshold Limit |
| • | | | | Values (TLV) |
| | Remarks | Danger of cutaneous absorption | | |
| | | С | 2 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | Danger of cutaneous absorption | | |
| | | С | 6 ppm | USA. NIOSH Recommended |
| | | | 5 mg/m3 | Exposure Limits |
| | | TWA | 3 ppm | USA. NIOSH Recommended |
| | | | 2.5 mg/m3 | Exposure Limits |
| | | TWA | 3 ppm | USA. Occupational Exposure |
| | | | | Limits (OSHA) - Table Z-2 |
| | | PEL | 0.4 ppm | California permissible exposure |
| | | | 0.33 mg/m3 | limits for chemical |
| | | | | contaminants (Title 8, Article |
| | | | | 107) |
| | | Skin | | |
| | | STEL | 1 ppm | California permissible exposure |
| | | | 0.83 mg/m3 | limits for chemical |
| | | | | contaminants (Title 8, Article |
| | | | | 107) |
| | | Skin | | |

Millipore - HX0627 Page 5 of 13



Biological occupational exposure limits

| Component | CAS-No. | Parameters | Value | Biological specimen | Basis |
|-------------------|-----------|--|--------|---------------------|--|
| Hydrofluoric acid | 7664-39-3 | Fluoride | 2 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | Remarks | Prior to shift (16 hours after exposure ceases) | | | |
| | | Fluoride | 3 mg/l | Urine | ACGIH - Biological Exposure Indices (BEI) |
| | | End of shift (As soon as possible after exposure ceases) | | | |

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact Material: Viton®

Minimum layer thickness: 0.70 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Splash contact

Material: Chloroprene

Minimum layer thickness: 0.65 mm Break through time: 120 min

Material tested: KCL 720 Camapren®

Body Protection

protective clothing, Rubber or plastic boots

Respiratory protection

Recommended Filter type: Filter E-(P3)

Millipore - HX0627 Page 6 of 13



The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

0.1 Information on basic physical and chemical properties

a) Appearance Form: liquid

Color: colorless

b) Odor stinging

c) Odor Threshold No data available

d) pH at 20 °C (68 °F)strongly acid

e) Melting point: ca.-35 °C (ca.-31 °F) point/freezing point

f) Initial boiling point ca.106 °C ca.223 °F at 1,013 hPa and boiling range

g) Flash point ()Not applicable
h) Evaporation rate No data available

i) Flammability (solid, No data available gas)

j) Upper/lower No data available flammability or

k) Vapor pressure No data availablel) Vapor density No data available

m) Density 1.16 g/cm3 at 20 °C (68 °F)

Relative density No data available

n) Water solubility soluble

o) Partition coefficient: No data available

n-octanol/water

explosive limits

p) Autoignition No data available

temperature

q) Decomposition No data available

temperature

r) Viscosity No data available

Millipore - HX0627



- s) Explosive properties Not classified as explosive.
- t) Oxidizing properties

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature).

10.3 Possibility of hazardous reactions

Risk of ignition or formation of inflammable gases or vapours with:

Metals

Alkali metals

Fluorine

Risk of explosion/exothermic reaction with:

potassium permanganate

silicon compounds

alkali hydroxides

Oxides of phosphorus

bismuth acid

strong alkalis

10.4 Conditions to avoid

Heating.

no information available

10.5 Incompatible materials

glass, Metals, quartzes/silicate ceramicsGives off hydrogen by reaction with metals.

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture

Acute toxicity

Acute toxicity estimate Oral - 10.2 mg/kg

(Calculation method)

Symptoms: If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.

Acute toxicity estimate Inhalation - 4 h - 1.2 mg/l - vapor(Calculation method)

Millipore - HX0627

Page 8 of 13

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

respiratory tract

Acute toxicity estimate Dermal - 10.2 mg/kg

(Calculation method)

Skin corrosion/irritation

Remarks: Mixture causes severe burns.

Serious eye damage/eye irritation

Remarks: Mixture causes serious eye damage.

Risk of blindness!

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

No data available

Components

Hydrofluoric acid

Acute toxicity

Oral: No data available

LC50 Inhalation - Rat - 1 h - 1.34 mg/l - vapor

Remarks: (IUCLID)

Acute toxicity estimate Inhalation - 0.6 mg/l - vapor

(Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Symptoms: burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Resultant lesions may affect he following:,

bronchitis, Pneumonia, Lung edema

Millipore - HX0627

Page 9 of 13

Inhalation: Corrosive to respiratory system.

Dermal: No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 4 h (OECD Test Guideline 404)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table

3.1/3.2)

Remarks: Symptoms may be delayed.

Possible damages:

Necrosis

Tendency of poor wound-healing after penetration of the substance.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. (OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Causes serious eye damage.

Respiratory or skin sensitization

No data available

Germ cell mutagenicity

Test Type: Ames test

Test system: S. typhimurium

Result: negative

Test Type: Chromosome aberration test in vitro Test system: Chinese hamster ovary cells

Result: Positive results were obtained in some in vitro tests.

Species: Rat

Remarks: Cytogenetic analysis

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Acute inhalation toxicity - burns of mucous membranes, Cough, Shortness of breath, Possible damages:, damage of respiratory tract, Resultant lesions may affectthe following:, bronchitis, Pneumonia, Lung edema

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Millipore - HX0627



Page 10 of 13

SECTION 12: Ecological information

12.1 Toxicity

Mixture

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Biological effects:

Endangers drinking-water supplies if allowed to enter soil or water.

Harmful effect due to pH shift.

Forms toxic and corrosive mixtures with water even if diluted.

Further information on ecology

Discharge into the environment must be avoided.

Components

Hydrofluoric acid

Toxicity to daphnia static test NOEC - Daphnia magna (Water flea) - 3.7 mg/l - 21

and other aquatic c

invertebrates(Chronic Remarks: (ECHA)

toxicity)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Millipore - HX0627

AilliPORQ

SECTION 14: Transport information

DOT (US)

UN number: 1790 Class: 8 (6.1) Packing group: II

Proper shipping name: Hydrofluoric acid Reportable Quantity (RQ): 200 lbs Poison Inhalation Hazard: No

IMDG

UN number: 1790 Class: 8 (6.1) Packing group: II EMS-No: F-A, S-B

Proper shipping name: HYDROFLUORIC ACID

IATA

UN number: 1790 Class: 8 (6.1) Packing group: II

Proper shipping name: Hydrofluoric acid

SECTION 15: Regulatory information

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-------------------|-----------|-----------------------|--------------------------------|
| Hydrofluoric acid | 7664-39-3 | 100 | 200 |

SARA 304 Extremely Hazardous Substances Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) | Calculated product RQ (lbs) |
|-------------------|-----------|-----------------------|--------------------------------|
| Hydrofluoric acid | 7664-39-3 | 100 | 200 |

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

| Components | CAS-No. | Component TPQ (lbs) |
|-------------------|-----------|---------------------|
| Hydrofluoric acid | 7664-39-3 | 100 |

SARA 313 : The following components are subject to reporting

levels established by SARA Title III, Section 313:

Hydrofluoric 7664-39-3 >= 50 - < 70 %

acid

US State Regulations

Massachusetts Right To Know

| water | 7732-18-5 |
|-------------------|-----------|
| Hydrofluoric acid | 7664-39-3 |

Pennsylvania Right To Know

Hydrofluoric acid 7664-39-3

Maine Chemicals of High Concern

water 7732-18-5

Vermont Chemicals of High Concern

water 7732-18-5

Millipore - HX0627

Millipore

Washington Chemicals of High Concern

water 7732-18-5

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16: Other information

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact mlsbranding@sial.com.

Version: 8.6 Revision Date: 07/02/2024 Print Date: 07/03/2024

Millipore - HX0627

