339-S Grease

Revision Date August 29, 2018

1. Product and Company Identification

Product Information	
Trade Name	339-S Grease
Product Description	Graphite grease
Recommended Uses	Lubricant
Company	Cummings-Moore Graphite Co. (a division of Asbury Carbons, Inc.)
	1646 N.Green Ave.
	Detroit, MI 48209
Emergency Telephone	US: 1-800-255-3924; International: +01-813-248-0585; China: 400-120-0751;
	Brazil: 0-800-591-6042; India: 000-800-100-4086; Mexico: 01-800-099-0731
	ChemTel contract number: MIS0001931 (collect calls accepted)
Information Phone	1-908-537-2155
Website	www.asbury.com

2. Hazards Identification

Classification	Not a hazardous substance
Labeling	No label elements are required

3. Composition / Information on Ingredients

Components	CAS No.	Weight %	Hazard Code(s)
Distillates (petroleum)	Proprietary	45 - 75%	
Graphite	7782-42-5	20 - 40%	
Talcum	14807-96-6	5 - 15%	

4. First Aid Measures

Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.
Skin Contact	Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If skin irritation or an allergic skin reaction develops, get medical attention.
Eye contact	Flush thoroughly with water for 15 minutes. If irritation occurs, get medical assistance.
Ingestion	If conscious and alert, rinse mouth and drink 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid.
Symptoms / effects (acute and delayed)	Defatting of the skin.

5. Fire Fighting Measures

Suitable extinguishing	Use dry chemical, carbon dioxide, or chemical foam. Use agent most appropriate to
media	extinguish surrounding fire.
Unsuitable	Do not use water jet as an extinguisher, as this will spread the fire.
extinguishing media	
Special fire hazards	No unusual fire or explosion hazards noted.
Products of	Smoke, fume, incomplete combustion products, carbon dioxide (CO2), carbon
Combustion	monoxide (CO).
Protective equipment	Wear full protective clothing, including helmet, self-contained positive pressure or
for firefighters	pressure demand breathing apparatus, protective clothing and face mask.
NFP Rating	110

6. Accidental Release Measures

Personal	Use proper personal protective equipment as indicated in Section 8.	
precautions		
Environmental	Prevent spill from entering sewers and water courses. Report releases as required by local	
precautions	and national authorities.	
Methods for	Contain spillage, and then collect with non-combustible absorbent material. Place in	
cleaning up	suitable, closed containers for disposal.	

7. Handling and Storage

Precautions for	Avoid breathing dust, mist, or vapor. Avoid contact with eyes, skin, and clothing. Keep
safe handling	container tightly closed. Avoid ingestion and inhalation. Wash clothing before reuse.
Storage	Store in a cool, dry place. Keep container closed when not in use.
precautions	

8. Exposure Controls/ Personal Protection

Ingredients with control parameters / occupational exposure limits				
Component		CAS No.	TWA	Control Reference
Distillates (petroleum)		proprietary	5 mg/m ³	Inhalable mist, ACGIH
Graphite		7782-42-5	2.0 mg/m ³	Respirable dust, ACGIH
Talcum		14807-96-6	2.0 mg/m ³	Respirable dust, ACGIH
Engineering controls	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low.			
Respiratory Protection	Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.			
Eye Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.			
Skin Protection	Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Chemical/oil resistant clothing is recommended. Launder contaminated clothing before reuse.			
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.			

9. Physical and Chemical Properties

	u chichinoda i roportico		
Appearance	Black grease	Lower explosion limit	Not available
Odor	Mild petroleum	Upper explosion limit	Not available
рH	Not applicable	Vapor pressure	Not available
Freezing point	No data	Vapor density	Not available
Boiling point	No data	Water solubility	No data
Flash point	> 300 °F (> 149 °C)	Partition coefficient:	Not established
	Closed cup	n-octanol/water	
Evaporation rate	Not available	Autoignition	No data
		temperature	
Specific gravity	1.14 g/ml	% volatile	No data

10. Stability and Reactivity

Chemical stability	Stable under normal conditions of use.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Conditions to avoid	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
Materials to avoid	Strong oxidizers

Asbury Carbons SDS: 339-S Grease (August 29, 2018) - Page 2

11. Toxicological Information

Acute oral toxicity	Not classified. May cause gastrointestinal discomfort if swallowed.
Acute inhalation toxicity	Not classified. May cause respiratory tract irritation.
Acute dermal toxicity	Not classified. May cause skin irritation.
Skin corrosion/irritation	Not classified. May be irritating to the skin.
Eye damage/irritation	Not classified. May cause minor irritation on eye contact.
Respiratory or skin	Not classified.
sensitization	
Mutagenicity	No data available to indicate product or any components present at greater than
Mutagementy	0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or
	OSHA. Not classified.
Reproductive toxicity	Contains no ingredient listed as toxic to reproduction.
STOT - single exposure	Not classified.
STOT - repeated exposure	Not classified.
Aspiration hazard	Not classified.
Chronic effects	Prolonged inhalation of mist may be harmful.

12. Ecological Information

Ecotoxicity	Not expected to be harmful to aquatic organisms.		
Biodegradation	Not inherently biodegradable.		
Bioaccumulation	Bioaccumulation is unlikely to be significant because of the low water solubility of this product.		
Mobility	Not available.		

13. Disposal Considerations

Material Disposal	When this product as supplied is to be discarded as waste, it does not meet the definition of a RCRA waste under 40 CFR 261. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Regulatory Information	Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.
Packaging Disposal	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Offer rinsed packaging material to local recycling facilities.

14. Transport Information

UN number	Not regulated
Proper shipping name	n/a
Transport hazard class	n/a
Packing group	n/a
Marine pollutant?	Not classified as a marine pollutant

15. Regulatory Information

Listed / complies with the following	DSL, IECSC, TSCA, EINECS, KECI, PICCS, AICS			
chemical inventories:				
SARA (311/312) Hazard Classifications	No classification			
SARA (313) Toxic Release Inventory:	This material contains no chemicals subject to the supplier			
	notification requirements of the SARA 313 Toxic Release Program.			
The following ingredients are cited on the lists below:				

Asbury Carbons SDS: 339-S Grease (August 29, 2018) - Page 3

Chemical Name		CAS Number		List Citations	
Graphite		7782-42-5	1, 12, 16, 17, 18		
Talcum		14807-96-6	1, 17, 18		
Regulatory lists sear 1 = ACGIH ALL 2 = ACGIH A1 3 = ACGIH A2	rched: 6 = TSCA 5a2 7 = TSCA 5e 8 = TSCA 6		A P65 REPRO A RTK	16 = MN RTK 17 = NJ RTK 18 = PA RTK	
4 = OSHA Z 5 = TSCA 4	9 = TSCA 12b 10 = CA P65 CAF	14 = L	A RTK	19 = RI RTK 20 = MA RTK	

16. Other Information

The information contained herein is accurate to the best of our knowledge. Asbury Carbons makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances.

NFPA Classification	Health Hazard:	1
	Fire Hazard:	1
	Reactivity Hazard:	0