

Asbury Graphite Mills, Inc. **Cummings – Moore Graphite Co. Anthracite Industries Southwestern Graphite Asbury Graphite of California** Asbury - Wilkinson Asbury Graphite & Carbons NL B.V. Graphitos Mexicanos de Asbury, S.A. de C.V.

PO Box 144, 405 Old Main St. Asbury, NJ 08802	908-537-2155
1646 N. Green Ave. Detroit, MI 48209	313-841-1615
PO Box 112, Sunbury, PA 17801	570-286-2176
PO Box 876, 2564 Hwy 12 DeQuincy, LA 70633	337-786-5905
2855 Franklin Canyon Rd. Rodeo, CA 94572	510-799-3636
1115 Sutton Drive Burlington, ON, L7L 5Z8 Canada	905-332-0862
Fregatweg 46 B-C, Maastricht 6222 NZ Netherlands	+31437600610
Blvd José Maria Morelos No.389 Nte, Hermosillo 83148 Mexico	526622678598

Safety Data Sheet

Section 1 – Identification of the Substance / Preparation, and of the Company

1.1: Product Identifier

Trade Name: Wood Based Activated Carbon

Activated Carbon, CAS 7442-44-0 EC Number: 231-153-3 Substance Name:

1.2: Indentified uses of the substance or mixtures

1.2.1 Uses: Inorganic source of carbon, filler, liquid and/or gaseous adsorption trains, de-colorization, filtration, other processes and applications compatible with cellulostic-based activated carbon.

1.2.2 Uses Advised Against: For industrial use only, not for food, drug, or cosmetic applications.

1.3: Supplier Information

Company/Manufacturer: Asbury Carbons, Inc. Telephone: 908-537-2155 PO Box 144, 405 Old Main Street Telefax: 908-723-2908

Asbury, NJ 08802 Preparer: RTW

Email Address: rweir@asbury.com Date Prepared: July 24,2020

1.4: Emergency Telephone Number

Callers must reference the Contract Number:

Chemtel Contract Number: MIS0001931

Collect Calls are accepted US: 1-800-255-3924

International: +01-813-248-0585.

China: 400-120-0751, Brazil: 0-800-591-6042, India: 000-800-100-4086 Mexico: 01-800-099-0731















Section 2: Hazards Identification

2.1: Classification of substance

Wood based activated carbon is not a hazardous substance.

2.2: Label Elements

Wood based activated carbon is not a hazardous substance, no label elements are required

2.3: Other hazards

None known

Section 3 – Composition/Information on Ingredients:

Chemical Composition: Wood Based activated carbons 100%

CAS # 7440-44-0 EC # 264-864-4 Molecular Weight: 12.0

Section 4 - First Aid Measures

4.1.1	Remove patient to particulate-free environment. Wear approved dust mask to avoid breathing
Inhalation	dust. Seek medical attention if irritation persists.
4.1.2 Skin	Wash with mild soap and warm water: Wood Based activated carbon is not a chemical irritant.
Contact	
4.1.3 Eye	Rinse with tepid water until eyes are clear of particulates. Seek medical attention if irritation
Contact	persists. Mechanical/abrasion related irritation is possible
4.1.4	Get immediate medical attention. Do not induce vomiting unless directed by medical personnel.
Ingestion	Wood activated Carbon is not known to be toxic by ingestion. However, ingestion of large
	quantities of AC may cause digestive system blockage.
4.2 Most importa	ant symptoms and effects, both acute and delayed: No Data Available
4.3 Indication of	any immediate medical attention and special treatment needed: If patient exhibits shortness of
breath, choking,	powder inundated eyes or mouth; immediate medical attention may be required.

Section 5 – Fire Fighting Measures

5.1 Extinguishing Media	Dry chemical extinguisher, water, sand, limestone powder,
5.2 Special Hazards	Activated carbon can absorb atmospheric oxygen, especially when wet, resulting in a reduced local oxygen concentration. In confined spaces this may result in local levels of oxygen below that required to support life. Under these conditions immediate asphyxiation and death is possible. Activated carbon presents a confined-spaces hazard with respect to oxygen depletion.
	Activated carbon may react exothermically with certain organic compounds, ketones for example.
Products of Combustion	Carbon dioxide (CO ₂), Carbon monoxide (CO)
5.3 Advice for Fire Fighters:	Use self contained air pack, gloves, safety goggles
5.4 Additional Information: U	SA NFP Rating 010















Section 6 - Accidental Release Measures

	Wear approved dust mask, safety goggles, and conventional work gloves.	
Methods for Cleaning Up:	Conventional Sweep or vacuum. Avoid creating dusting conditions	
6.1 Personal precautions, protective equipment and emergency procedures		

- 6.1.1 For non-emergency personnel: Wear approved dust mask, safety goggles, and conventional work gloves. Use conventional cleanup techniques and avoid creating dust. Vacuum is preferred over sweeping. Be cautious of slip hazard on wet or dry pedestrian surfaces. Wear a dust mask/respirator to reduce the change of inhaled dust.
- 6.1.2 For emergency responders: Wear approved dust mask, safety goggles, and conventional work gloves. Same methodology as for non-emergency personnel(sec 6.1.1)
- 6.2 Environmental Precautions: Wood Based activated carbon is insoluble and will not pose any soluble ion hazards to the environment. However, good housekeeping practices should be followed and spilled material should be cleaned up, and disposed of in an appropriate manner.
- 6.3 Methods and material for containment and clean up: No special containment needed other than conventional vacuuming and waste containment. Avoid creating dust.
- 6.4 Reference to other sections: Not needed
- 6.5 Additional information: Not needed

Section 7 – Handling and Storage

7.1 Precautions for safe handling

7.1.1 Handling Use conventional methods, but avoid dusting conditions. Provide sufficient exhaust ventilation in areas where dust is created. Wear suitable respiratory protection. Keep powder from contacting eyes.

Activated carbon can absorb atmospheric oxygen, especially when wet, resulting in a reduced local oxygen concentration. In confined spaces this may result in local levels of oxygen below that required to support life. Under these conditions immediate asphyxiation and death is possible. Activated carbon presents a confinedspaces hazard with respect to oxygen depletion.

7.2 Conditions for safe storage, including any incompatibilities.

Storage: Store all carbonaceous materials in a dry location. Keep packaging closed or covered. Store away from heat or flame.

Incompatibilities: Activated carbon is incompatible with all oxidizing agents and certain organic substances.

Dust Explosibility Hazards: Very finely divided activated carbon powder poses a slight risk of dust explosion hazard: Dust class ST1, MIE greater that 10 J (very low hazard of spark ignition)

Section 8 – Exposure Controls/ Personal Protection: 8.1 Control parameters

8.1.1 Occupational expos	ure limits			
Component	CAS No.	%	ACGIH TWA	Control Reference
			3.0 mg/m ³	2014 ACGIH TLV Handbook:
Wood Based activated	7440-44-0	100	Respirable dust	Recommendations for insoluble
carbon	7440-44-0	.0-44-0 100	10.0 mg/m³	or poorly soluble materials of
			Inhalable dust	low toxicity
Engineering Measures	Use adequate dust collection to maintain dust levels below the control or			
	recommended values.			
Respiratory Protection	Approved dust mask, type N95 recommended.			
Eye Protection	Conventional safety glasses or goggles.			
Skin Protection	Conventional work gloves and clothing.			
Additional	Be aware of confined space hazards(see section 7.1.1)			















8.2 Exposure controls

8.2.1 Appropriate engineering controls: Use adequate dust collection to maintain dust levels below the control or recommended values.

8.2.2 Personal protective equipment

8.2.2.1 Eye/Face Protection: Wear laboratory goggles, or full side shielded safety glasses.

8.2.2.2 Skin Protection: Conventional work gloves and clothing.

8.2.2.3 Respiratory Protection: Approved dust mask, type N95 recommended.

8.2.3 Environmental exposure controls: Wood based activated carbon is inert and insoluble. To the best of our knowledge, wood based activated carbon does not present any environmental hazards. No special environmental exposure controls, other than standard practices for dust and spill control, are required. "Used" activated carbon may have toxicity properties similar to the adsorbate.

Section 9 - Physical and Chemical Properties: 9.1 Information on basic physical and chemical properties

Color:	Gray to Black	Material State	Solid, granular or powder
Odor	None		
Boiling Point:	NA	Melting Point	Sublimates at 3652C
Specific Gravity	1.5-1.9	Vapor Density	Not applicable
Vapor Pressure (mm	NA	% Volatile (By Wt.)	0-8% (non-VOC)
Hg)			
Solubility in Water	Insoluble	Evaporation Rate:	Not applicable
рН	9-11	Auto Ignition	Above 500 °C
Decomposition Temp	Oxidizes above 400C	Dust Explosion class	ST1=KST>0-200 bar m/s, MIE
,			above 10 J.
Flash Point	NA Solid substance with very high melting point.		

Section 10 - Stability and Reactivity

10.1 Reactivity	Wood based activated carbon is non-reactive under ambient conditions.
10.2 .Stability	Stable. Will not polymerize or self react spontaneously.
10.3 Possibility of	None known
hazardous reactions	
10.4 Conditions to Avoid	Avoid contact with oxidizing agents. Wood based activated carbon will begin to oxidize at temperatures above 400 C.
10.5 Incompatible materials	Oxidizing agents. Activated carbon may react exothermically with certain organic compounds, ketones for example
10.6 Hazardous products of decomposition	Carbon Dioxide (CO ₂), Carbon Monoxide (CO)
Flammable Limits (% by Vol.)	LEL and UEL values not available: Minimum Ignition Energy (MIE) greater than 10 joules. When exposed to extremely high energy ignition sources very finely divided wood based activated carbon powder can form explosive mixtures with air. Avoid contact between wood based activated carbon dust clouds and high energy ignition sources.















Section 11 – Toxicological Information

11.1 Information on toxicological effects

Acute toxicity: Data/information on acute toxicity of wood based activated carbon is not available. This material has low toxicity and is not expected to have any acute toxicity.

STOT-single exposure: Not available.

STOT-repeated exposure: Not available

Aspiration hazard: Solid substance. Based on available data the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

<u>In case of ingestion:</u> wood based activated carbon is non-toxic and is not expected to be an ingestion hazard. In case of skin contact: Mechanical irritation only is expected.

In case of inhalation: Usual signs after inhalation of poorly soluble dusts with low toxicity are the only effects expected. No symptoms are expected if relevant occupational exposure levels are complied with. In situations of repeated excessive lung overload due to a high airborne concentration of particles of respirable size for extended periods of time pneumoconiosis may develop. See section 4 for first aid measures.

<u>In case of eye contact:</u> No irritation other than mechanical irritation is expected. No human data on effects after eye contact is available. See section 4 for first aid measures.

Section 12 – Ecological Information

12.1 Toxicity:	Wood based activated carbon is inert and insoluble. To the best of our knowledge, wood based activated carbon does not present any significant environmental
	hazards.
12.1.1 Aquatic Toxicity: V	Vood based activated carbon is not water soluble and does not present a soluble-ion
hazard. Fine wood based	activated carbon particles suspended in natural water bodies may be harmful to
organisms sensitive to sus	spended solids.
12.1.2 Sediment toxicity: I	None known.
12.1.3 Terrestrial toxicity:	None known.
12.2 Persistence and deg	radability: Wood based activated carbon is a reduced form of carbon and will not
degrade further under nor	mal conditions. This form of carbon is stable, unreactive in water under ambient
conditions, and is insolubl	e.
12.3 Bioaccumulation pote	ential: There is no evidence indicating that wood based activated carbon is
bioaccumulative.	
12.4 Soil Mobility: Wood b	pased activated carbon is not expected to have mobility in soil as it is an insoluble,
inorganic substance.	
12.5 PBT and vPvB asses	ssment: Wood based activated carbon is not a persistent bioaccumulative and toxic
substance.	

12.6 Other adverse effects: None known. Wood based activated carbon has no ozone depleting potential.















Section 13 – Disposal Considerations:

Dispose of in a manner which conforms to local, state and Federal regulations.

Wood based activated carbon is a reduced form of carbon. Wood based activated carbon is non-hazardous but disposal of waste should be handled in a responsible matter.

Wood based activated carbon is a form of elemental carbon so it is not biodegradable.

Provision of a European Waste Catalog, waste code number, should be handled in agreement with the regional waste disposal company.

Packaging should be completely emptied of contents and disposed of in a manner specified by the recycler/regional disposal contractor. Dust formation from packaging residues should be avoided. Store empty packaging in a suitable receptacle

Section 14 – Transport Information

Section 14 - Hansport Information	
14.1 UN Number	Not applicable
14.2 UN Proper shipping name	Not applicable
14.3 Transport hazard class	Not applicable
14. 4 Packing Group	Not applicable
14.5 Environmental hazards	None known
Marine Transport	Not classified as a hazardous material
Land Transport	Not classified as a hazardous material
Air Transport	Not classified as a hazardous material per IATA
Transport Label Required	No label required
Additional Transport Information	Note that a representative sample of this activated carbon material was selected and tested per UN test methods/UN Recommendation of the Transport of Dangerous Goods, 9thEdition for "self heating" properties. Testing results indicated that this material has passed the "TEST FOR SELF HEATING SUBSTANCES" as reflected in the UJ\J Manual of Tests and Criteria as a non self-heating substance. As a result of this testing no UN number is required for this non-hazardous activated carbon product (Reference: RD 18010)

Section 15 – Regulatory Information

15 1 Regulatory Status and Inventories

13.1 Hegulatory Status and	Inventories
Not Classified	
Inventory Information:	
EEC EINECS	#231-153-3
US TSCA	Yes
Canada DSL	Yes
Canada NDSL	No
Australian AICS	Yes
Korean ECL	Yes
Asia PAC	Yes
PICCS	Yes
New Zealand NZLoC	Yes
HSNO Approval	HSR001271
REACH: On list of pre-regi	stered substances
RoHS: Wood based activa	ated carbon is compliant with the EU RoHS directive



directive















WEEE: Wood based activated carbon is compliant with the EU waste electrical and electronic equipment

15.2 Chemical Safety Assessment: For this substance a chemical safety assessment is not required

Asbury Carbons SDS: Wood-Based Activated Carbon, July 2020, Page 7

Section 16 - Other Information

Abbreviations Used:

ACGIH TWA American Council of Government and Industrial Hygienists Time Weighted Average value.

CAS Chemical Abstracts Service

NA Not applicable

N.O.S. Not otherwise specified

BW Body weight

Definitions:

Adsorbate: the substance adsorbed (or absorbed) into the activated carbon surface.













