



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

1 Identification

· Product identifier

· Trade name: Seed Slik Graphite

· Other means of identification: No other identifiers

· Recommended use and restriction on use

· Recommended use: Industrial uses.

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

Asbury Carbons, Inc. PO Box 144 405 Old Main Street Asbury, NJ 08802

USA

+1 908-537-2155

· Emergency telephone number:

ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) 1-300-954-583 (Australia) 0-800-591-6042 (Brazil) 400-120-0751 (China) 000-800-100-4086 (India)

2 Hazard(s) identification

01-800-099-0731 (Mexico)

· Classification of the substance or mixture

Carc. 1A H350 May cause cancer. Route of exposure: Inhalation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS08

· Signal word: Danger · Hazard statements:

H350 May cause cancer. Route of exposure: Inhalation.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/protective clothing/eye protection. P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

(Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

(Cont'd. of page 1)

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information: Long term inhalation of product dust may be harmful.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:				
14807-96-6	Talc		50-100%	
14808-60-7	Quartz (SiO2)	♦ Carc. 1A, H350	0-3.5%	

· Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Brush off loose particles from skin.

If skin irritation is experienced, consult a doctor.

· After eye contact:

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Coughing

Mechanical irritation to eyes.

May cause gastro-intestinal irritation if ingested.

- · Danger: May cause cancer. Route of exposure: Inhalation.
- Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

- Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

- For safety reasons unsuitable extinguishing agents: None.
- Special hazards arising from the substance or mixture

(Cont'd. on page 3)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

(Cont'd. of page 2)

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid formation of dust.

Use personal protective equipment as required.

Avoid breathing dust.

- · Environmental precautions Damp down dust with water spray.
- · Methods and material for containment and cleaning up

Sweep up and place into an appropriate container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- ·Handling
- Precautions for safe handling:

Use only in well ventilated areas.

Prevent formation of dust.

Any deposit of dust which cannot be avoided must be regularly removed.

Do not breathe dust.

Avoid contact with the eyes.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles:

Storage area should be dry and well-ventilated.

- Information about storage in one common storage facility: Store away from foodstuffs.
- Further information about storage conditions: Keep containers tightly sealed.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

14807-96-6 Talc

PEL (USA) Long-term value: 20 mppcf ppm (containing <1% Quartz)

(Cont'd. on page 4)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

	(Cont'd. of page 3)				
REL (USA)	Long-term value: 2* mg/m³ *respirable dust; and <1% Quartz				
TLV (USA)	Long-term value: 2* mg/m³ *as respirable fraction; E				
EL (Canada)	Long-term value: 2 *0.1 f/cc mg/m³ resp. *if contains asbestos : ACGIH A1, IARC 1				
EV (Canada)	Long-term value: 2* mg/m³, 2 f/cc ppm *respirable				
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable				
14808-60-7 Qua	14808-60-7 Quartz (SiO2)				
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2				
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A				
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction				
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1				
EV (Canada)	Long-term value: 0.10* mg/m³ *respirable fraction				
LMPE (Mexico)	Long-term value: 0.025* mg/m³ A2, *fracción respirable				

Exposure controls

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Do not breathe dust.

- · Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

NIOSH or EU approved dust respirator should be used for operations generating dust.

· Protection of hands:

Gloves are advised for repeated or prolonged contact.

Wear gloves for the protection against mechanical hazards according to OSHA and NIOSH rules.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- Eye protection: Follow relevant national guidelines concerning the use of protective eyewear.
- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

Avoid release to the environment.

· Risk management measures No relevant information available.

9 Physical and chemical properties

(Cont'd. on page 5)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

	(Cont'd. of page
Information on basic physical a	and chemical properties	
Appearance:	• •	
Form:	Solid in various forms	
Color:	Various colors	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	~9	
Melting point/Melting range:	>1300 °C (>2372 °F)	
Boiling point/Boiling range:	Not determined.	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Product is not flammable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	>950 °C (>1742 °F)	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	2.5-2.8	
Vapor density:	Not applicable.	
Evaporation rate:	Not applicable.	
Solubility in / Miscibility with		
Water:	Negligible	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Other information	No relevant information available.	

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid Prevent formation of dust.
- · Incompatible materials No relevant information available.
- · Hazardous decomposition products No dangerous decomposition products known.





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

(Cont'd. of page 5)

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.
- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:
- · On the skin: Based on available data, the classification criteria are not met.
- · On the eye: Based on available data, the classification criteria are not met.
- · Sensitization: Based on available data, the classification criteria are not met.

· IARC (International Agency for Research on Cancer):

14808-60-7 Quartz (SiO2)

1

· NTP (National Toxicology Program):

14808-60-7 Quartz (SiO2)

K

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

- · Repeated dose toxicity:
- Long-term inhalation of silica dusts may cause obstructive pulmonary disease including silicosis.
- Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: May cause cancer. Route of exposure: Inhalation.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: Based on available data, the classification criteria are not met.
- · STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- · Other adverse effects No relevant information available.

13 Disposal considerations

- Waste treatment methods
- · Recommendation:

(Cont'd. on page 7)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

(Cont'd. of page 6)

Smaller quantities can be disposed of with household waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · **Recommendation:** Disposal must be made according to official regulations.

14 Transport information		
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
Transport hazard class(es)		
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.	
Packing group DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.	
· Environmental hazards · Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.		

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- · Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Proposition 65 (California)

(Cont'd. on page 8)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: April 11, 2019

Trade name: Seed Slik Graphite

· Chemicals known to cause cancer:

Reference to talc not applicable to product, as product contains no asbestiform fibers.

14808-60-7 Quartz (SiO2)

14807-96-6 Talc

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

14808-60-7 Quartz (SiO2)

1

· Canadian Domestic Substances List (DSL): (Substances not listed.)

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistant, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health Administration

Carc. 1A: Carcinogenicity - Category 1A

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com

(Cont'd. of page 7)