

SAFETY DATA SHEET

Page 1 of 4

1. IDENTIFICATION

PRODUCT NAME: FURNITURE POLISH WITH LEMON OILRECOMMENDED USE: FURNITURE POLISH WITH LEMON OILRESTRICTIONS ON USE: DO NOT USE IN A MANNER INCONSISTENT WITH THE LABEL.LABEL BRAND: IND/COMSDS 064166

USCHEMICAL316 HART STREETMEDICAL EMERGENCY:1-866-836-8855 USASPILL EMERGENCY:1-800-424-9300 USAPRODUCT INFORMATION:1-800-558-9566 USAINTERNET ADDRESS:WWW.USCHEMICAL.COM

WATERTOWN, WI 53094 USA

(8 A.M. TO 5 P.M. CST MONDAY TO FRIDAY)

2. HAZARD(S) IDENTIFICATION

CLASSIFICATION: FLAMMABLE AEROSOLS (CATEGORY 1), EYE IRRITATION (CATEGORY 2B)

LABEL ELEMENTS SIGNAL WORD: DANGER PICTOGRAMS: FLAME

HAZARD STATEMENTS: EXTREMELY FLAMMABLE AEROSOL. CAUSES EYE IRRITATION. PRECAUTIONARY STATEMENTS: Avoid contact with eyes, skin, and clothing. Wash hands and affected areas thoroughly after handling. Keep away from heat, sparks, open flames and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

FIRST AID: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. If eye irritation persists, get medical attention. **IF ON SKIN:** Wash with plenty of water. If skin irritation occurs and persists, get medical attention. **IF SWALLOWED:** Rinse mouth. In the unlikely event of swallowing, contact a physician or poison control center. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **EMERGENCY TELEPHONE: 1-866-836-8855**

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C (122°F). Store in a well-ventilated place.

Disposal: Dispose of contents in accordance with all federal, state and local applicable laws and regulations. **KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. HAZARDS NOT OTHERWISE CLASSIFIED:** Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT(S)	CAS #	WEIGHT %
POLYDIMETHYLSILOXANE	63148-62-9	2.5-10.0
LIQUEFIED PETROLEUM GAS	68476-86-8	2.5-10.0
EXACT PERCENTAGES ARE BEING WITHHELD AS TRADE SECRET INFORMATION.		

STATE RIGHT TO KNOW: SEE SECTION 15 FOR STATE RTK CHEMICAL NAMES IN MIXTURE.



FURNITURE POLISH WITH LEMON OIL

SDS 064166

4. FIRST-AID MEASURES

Page 2 of 4

IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING FOR AT LEAST 15 MINUTES. IF EYE IRRITATION PERSISTS, GET MEDICAL ATTENTION.

IF ON SKIN: WASH WITH PLENTY OF WATER. IF SKIN IRRITATION OCCURS AND PERSISTS, GET MEDICAL ATTENTION.

IF SWALLOWED: RINSE MOUTH. IN THE UNLIKELY EVENT OF SWALLOWING, CONTACT A PHYSICIAN OR POISON CONTROL CENTER.

IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. **EMERGENCY TELEPHONE: 1-866-836-8855**

MOST IMPORTANT SYMPTOMS / EFFECTS: CAUSES EYE IRRITATION. MEDICAL CONDITIONS AGGRAVATED: NONE KNOWN.

NOTE TO PHYSICIAN: CALL 1-866-836-8855 FOR EXPOSURE MANAGEMENT ASSISTANCE.

5. FIRE-FIGHTING MEASURES

CHEMICAL HAZARDS: EXTREMELY FLAMMABLE AEROSOL. CAUSES EYE IRRITATION. PRESSURIZED CONTAINER MAY EXPLODE WHEN EXPOSED TO HEAT OR FLAME. COMBUSTION PRODUCT HAZARDS: OXIDES OF CARBON AND OTHER FUMES. METHODS: SELECT EXTINGUISHER AND METHODS BASED ON FIRE SIZE AND TYPE. COOL CONTAINERS EXPOSED TO HEAT WITH WATER SPRAY AND REMOVE CONTAINER IF NO RISK IS INVOLVED.

EQUIPMENT: WEAR SCBA AND FULL PROTECTIVE GEAR AS CONDITIONS WARRANT. NFPA RATING: HEALTH-2/FLAMMABILITY-2/ INSTABILITY-0/SPECIAL HAZARD-N.AP. SUITABLE EXTINGUISHERS: WATER FOG OR MIST SUITABLE FOR FIRE.

UNSUITABLE EXTINGUISHERS: DO NOT USE WATER JET AS THIS WILL SPREAD FIRE.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: EVACUATE UNPROTECTED PERSONNEL FROM AREA. WEAR PERSONAL PROTECTION INCLUDING RUBBER BOOTS. SEE SECTION 8. VENTILATE AREA IF NEEDED. BE CAREFUL NOT TO SLIP. WASH THOROUGHLY AFTER CLEAN-UP. **ENVIRONMENTAL PRECAUTIONS**: PREVENT SPILL FROM ENTERING DRAIN, STORM SEWER OR SURFACE WATERWAY. PREVENT WATER AND SOIL CONTAMINATION. **CLEAN-UP METHODS**: REMOVE ALL IGNITION SOURCES. IF CONTAINERS BEGIN TO LEAK THROUGH PUNCTURE OR DEFECTIVE PACKAGING, ALLOW IT TO DISCHARGE COMPLETELY IN A WELL VENTILATED AREA. SMALL SPILLS MAY BE WIPED UP AND RINSED WITH WATER. FOR LARGER SPILLS, DIKE TO CONTAIN. PUMP TO LABELED CONTAINER OR ABSORB SPILLAGE AND SCOOP UP WITH INERT ABSORBENT MATERIAL. AFTER SPILL COLLECTION, RINSE AREA WITH WATER AND FOLLOW WITH NORMAL CLEAN-UP PROCEDURES.

7. HANDLING AND STORAGE

HANDLING: PRESSURIZED CONTAINER. DO NOT PIERCE OR BURN EVEN AFTER USE. DO NOT USE IF SPRAY BUTTON IS MISSING OR DEFECTIVE. INSTRUCT PERSONNEL ABOUT PROPER USE, HAZARDS, PRECAUTIONS, AND FIRST AID MEASURES. AVOID INHALATION, INGESTION, AND CONTACT WITH EYES, SKIN AND CLOTHING. INTENTIONAL MISUSE BY CONCENTRATING AND INHALING THE PRODUCT CAN BE HARMFUL OR FATAL. USE IN A WELL-VENTILATED PLACE. AVOID SPRAYING TOWARDS FACE. AVOID OVERSPRAY DURING USE. HANDLE CAREFULLY TO AVOID DAMAGING CONTAINER. **STORAGE:** PRESSURIZED CONTAINER. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C (122°F). STORE IN A WELL-VENTILATED PLACE. DO NOT PUNCTURE, INCINERATE OR CRUSH. KEEP AWAY FROM INCOMPATIBLE MATERIALS. KEEP FROM FREEZING. STORE AS LEVEL 1 AEROSOL (NFPA 30B).

SDS 064166

8. EXPOSURE CONTROLS	/ PERSONAL PROTECTION Page 3 of 4	
EXPOSURE LIMITS: POLYDIMETHYLSILOXANE = NONE		
LIQUEFIED PETROLEUM GAS = 1000 PPM TWA (ACGIH/OSHA)		
ENGINEERING CONTROLS: NONE REQUIRED. GENERAL ROOM VENTILATION IS TYPICALLY ADEQUATE.		
PERSONAL PROTECTION		
EYES: NONE REQUIRED WITH NORMAL USE.		
HANDS: NONE REQUIRED WITH NORMAL USE.		
RESPIRATORY: SUITABLE RESPIRATOR IF MISTS/VAPORS ARE NOT CONTROLLED BY VENTILATION.		
FEET: NONE REQUIRED WITH NORMAL USE.		
BODY: NONE REQUIRED WITH NORMAL USE.		
9. PHYSICAL AND CHEMICAL PROPERTIES		
APPEARANCE: MILKY WHITE LIQUID	AUTO-IGNITION TEMPERATURE: N.AV.	
ODOR: LEMON	DECOMPOSITION TEMPERATURE: N.AV.	
pH CONCENTRATE: 10.5	EXPLOSIVE LIMITS (LEL/UEL): N.AV.	
pH @ 2500 PPM SOLUTION: N.AV.	EVAPORATION RATE: N.AV.	
pH @ USE DILUTION: N.AV.	FLAMMABILITY (SOLID, GAS): N.AP.	
PHYSICAL STATE: LIQUID+GAS (AEROSOL)	FLASH POINT: -156°F(-104.4°C) LPG ESTIMATED	
RELATIVE DENSITY (WATER): 0.996	INITIAL BOILING POINT/RANGE: N.AV.	
SOLUBILITY (WATER): COMPLETE	MELTING POINT/FREEZING POINT: N.AV.	
VAPOR PRESSURE: 65 to 85 PSIG @70°F	ODOR THRESHOLD: N.AV.	
VAPOR DENSITY: N. AV.	PARTITION COEFF. (N-OCTANOL/WATER): N.AV. OTHER: *LIQUID AND GAS IN AEROSOL CAN	
VISCOSITY: NON-VISCOUS		
AEROSOL SPRAY ENCLOSED SPACE DEFLAGRATION DENSITY: NOT AVAILABLE AEROSOL SPRAY IGNITION DISTANCE: NOT AVAILABLE		
10. STABILITY AND REACTIVITY		
CHEMICAL STABILITY: STABLE.		
POSSIBILITY OF HAZARDOUS REACTIONS: NONE KNOWN. WILL NOT POLYMERIZE.		
CONDITIONS TO AVOID: DO NOT STORE ABOVE 49°C OR 120°F. KEEP AWAY FROM HEAT,		
DIRECT SUNLIGHT, OPEN FLAMES OR SPARKS. AVOID SPRAYING ON HOT SURFACES.		
FIRE, INTENSE HEAT OR DROPPING MAY CAUSE VIOLENT RUPTURE OF AEROSOL CAN.		
MATERIALS TO AVOID: AVOID CONTACT WITH OTHER CLEANING PRODUCTS.		
HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.		
11. TOXICOLOGICAL INFORMATION		
ROUTES OF EXPOSURE: EYES, SKIN, INGESTION, INHALATION. INFORMATION ON ROUTES OF EXPOSURE: NO LC50/LD50 TEST DATA ON MIXTURE.		
ACUTE EFFECTS /SYMPTOMS		
EYES: CAUSES EYE IRRITATION. MAY CAUSE DISCOMFORT, REDNESS AND WATERING.		
SKIN: MAY BE MILDLY IRRITATING TO SENSITIVE SKIN. MAY CAUSE DRY SKIN.		
INGESTION: MAY CAUSE IRRITATION, NAUSEA, VOMITING AND DIARRHEA.		
INHALATION: NO ADVERSE EFFECTS WITH NORMAL USE.		
CHRONIC / OTHER EFFECTS: NO REPORTABLE GERM CELL MUTAGENS, SKIN SENSITIZERS,		
RESPIRATORY SENSITIZERS, REPRODUCTIVE TOXINS OR ASPIRATION HAZARDS.		
SPECIFIC TARGET ORGANS (SINGLE/REPEATED): NONE KNOWN.		
NUMERICAL MEASURES OF TOXICITY: ATEmix (ORAL-RAT) = ABOVE 2000 MG / KG		
CARCINOGENS: NO REPORTABLE ACGIH, IA	RC, NTP, OR OSHA CARCINOGENS.	

12. ECOLOGICAL INFORMATION

Page 4 of 4

ECOTOXICITY / CHEMICAL FATE: NOT AVAILABLE.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: IGNITABLE WASTE (RCRA CLASS D001). DISPOSE OF CONTENTS IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL APPLICABLE LAWS AND REGULATIONS. CONSULT STATE AND LOCAL AUTHORITIES FOR RESTRICTIONS ON DISPOSAL OF CHEMICAL WASTE. MANAGE CHEMICAL WASTES THROUGH AN APPROVED WASTE TREATMENT FACILITY. PRESSURIZED CONTAINER: DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT INCINERATE. WHEN CONTENTS ARE DEPLETED CONTINUE TO DEPRESS BUTTON UNTIL ALL GAS IS EXPELLED. AEROSOL CYLINDER IS NOT REFILLABLE. GIVE TO A DISPOSAL SERVICE EQUIPPED TO SAFELY DISPOSE OF PRESSURIZED CONTAINERS. PLEASE RECYCLE PACKAGING WHENEVER POSSIBLE.

14. TRANSPORT INFORMATION

DOT / IMDG / TDG: UN1950, AEROSOLS, 2.1, LTD. QTY.

15. REGULATORY INFORMATION

EPA CERCLA RQ: NO EPA REGISTERED: NO OSHA HAZARDOUS: YES PHOSPHORUS CONTENT: 0.00% PROPOSITION 65: NO SARA 311/312 HAZARDS: ACUTE, FIRE, PRESSURE SARA 313 CHEMICALS: NO STATE RIGHT TO KNOW: WATER/7732-18-5, POLYDIMETHYLSILOXANE/63148-62-9, EMULSIFIER MIXTURE/MIXTURE, FRAGRANCE/PROPRIETARY, LIQUEFIED PETROLEUM GAS/68476-86-8 TSCA INVENTORY STATUS: ALL COMPONENTS ARE LISTED ON THE INVENTORY. VOC: 4.00% CALCULATION METHOD USED IS BASED ON CALIFORNIA ARB STANDARD.

16. OTHER INFORMATION

PREPARATION DATE: 1-15-15 PREPAR	
ABBREVIATIONS: N.AV. = NOT AVAILA	BLE N.AP. = NOT APPLICABLE

NOTICE TO READER

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED WITHIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE FOR EVALUATING ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.