

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: AQUACENT LT 68

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Hydraulic fluid

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

FUCHS LUBRICANTS (UK) PLC.
New Century Street
Hanley
Stoke-on-Trent, Staffordshire, ST1 5HU
UK

Telephone:

+44 (0) 1782 203700

Contact Person:

Telephone:

E-mail:

Product Safety department
+44 (0) 1782 203700
product.safety@fuchs-oil.com

1.4 Emergency telephone number:

UK NHS: Dial 111. Ireland NPIS: Dial +353 1 8092566.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

|| The product has not been classified as hazardous, but needs to be labelled according to regulation (EU) 1272/2008 (CLP).

Hazard summary

Physical Hazards:

No data available.

2.2 Label Elements

EUH208: Contains Oxazolidine derivative. May produce an allergic reaction.

|| EUH210: Safety data sheet available on request.

2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Product name: AQUACENT LT 68

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information: Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
base oil, paraffinic	EINECS: 265-159-2	20,00 - <50,00%	01-2119480132-48	
Ethanediol	EINECS: 203-473-3	1,00 - <5,00%	01-2119456816-28	
Oxazolidine derivative	EINECS: 266-235-8	0,01 - <0,10%		

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
base oil, paraffinic	EINECS: 265-159-2	CLP: Asp. Tox. 1;H304
Ethanediol	EINECS: 203-473-3	CLP: Acute Tox. 4;H302, STOT RE 2;H373
Oxazolidine derivative	EINECS: 266-235-8	CLP: Acute Tox. 4;H302, Acute Tox. 4;H332, Acute Tox. 3;H311, Skin Corr. 1B;H314, Skin Sens. 1A;H317, Eye Dam. 1;H318, Muta. 2;H341, Carc. 1B;H350, STOT RE 2;H373, Aquatic Chronic 2;H411

CLP: Regulation No. 1272/2008.

For the wording of the listed hazard statements refer to section 16.

SECTION 4: First aid measures

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed: Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

Product name: AQUACENT LT 68

5.1 Extinguishing media

Suitable extinguishing media:

CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions:

Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities:

Local regulations concerning handling and storage of waterpolluting products have to be followed.

7.3 Specific end use(s):

No data available.

Product name: AQUACENT LT 68

Storage Class: 12, Non-combustible liquids

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Ethanediol - Vapor.	TWA	20 ppm 52 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
Ethanediol - Vapor.	STEL	40 ppm 104 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)
Ethanediol - Particulate.	TWA	10 mg/m ³	UK. EH40 Workplace Exposure Limits (WELs) (12 2011)

8.2 Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Safety glasses (EN 166) recommended during refilling. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile-butadiene rubber (NBR).
 Min. Breakthrough time: ≥ 480 min
 Recommended thickness of the material: $\geq 0,38$ mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

Thermal hazards:

Not known.

Product name: AQUACENT LT 68

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls: No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	liquid
Form:	Emulsion
Color:	Off-white
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	not applicable
Freezing point:	Not applicable for mixtures
Boiling Point:	Value not relevant for classification
Flash Point:	> 200 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)—:	Not applicable for mixtures
Flammability Limit - Lower (%)—:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	0,95 g/cm ³ (15 °C)
Solubility(ies)	
Solubility in Water:	Emulsifiable in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	68 mm ² /s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.

Product name: AQUACENT LT 68

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition Products: Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral

Product:	ATEmix: 48.458 mg/kg
Specified substance(s) base oil, paraffinic	LD 50 (Rat): > 5.000 mg/kg
Ethenediol	LD 50 (Human): 1.600 mg/kg
Oxazolidine derivative	LD 50 (Rat): 630 mg/kg

Dermal

Product:	Not classified for acute toxicity based on available data.
Specified substance(s) base oil, paraffinic	LD 50 (Rabbit): > 5.000 mg/kg
Ethenediol	LD 50 (Mouse): 3.500 mg/kg
Oxazolidine derivative	LD 50 (Rat): 760 mg/kg (OECD 402)

Inhalation

Product:	Not classified for acute toxicity based on available data.
Specified substance(s) base oil, paraffinic	LC 50 (Rat, 4 h): > 5 mg/l
Oxazolidine derivative	LC 50 (Rat, 4 h): 2 mg/l (OECD 403)

Skin Corrosion/Irritation:

Product:	Based on available data, the classification criteria are not met.
-----------------	---

Serious Eye Damage/Eye Irritation:

Product:	Based on available data, the classification criteria are not met.
-----------------	---

Respiratory or Skin Sensitization:

Product:	Skin sensitizer: Based on available data, the classification criteria are not met. Respiratory sensitizer: Based on available data, the classification criteria are not met.
-----------------	---

Specified substance(s)

Ethenediol	No sensitizing effect (guinea pig); OECD 406
------------	--

Product name: AQUACENT LT 68

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

Other adverse effects: No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

base oil, paraffinic LC 50 (Fish, 96 h): > 101 mg/l

Ethanediol LC 50 (Fish, 96 h): 72.860 mg/l

Oxazolidine derivative LC 50 (Fish, 96 h): 57,7 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)

Ethanediol EC 50 (Water Flea, 48 h): > 100 mg/l (OECD 202)

Oxazolidine derivative EC 50 (Water Flea, 48 h): 37,9 mg/l (OECD 202)

Chronic Toxicity**Product:** Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Ethanediol NOEC (Fish, 7 d): 15.380 mg/l

Aquatic Invertebrates

Specified substance(s)

Ethanediol NOEC (Water Flea, 7 d): 8.590 mg/l

Toxicity to Aquatic Plants

Specified substance(s)

Oxazolidine derivative EC 50 (Alga, 72 h): 5,7 mg/l (OECD 201)

Product name: AQUACENT LT 68

12.2 Persistence and Degradability

Biodegradation

Product:	Not applicable for mixtures
Specified substance(s)	
Ethanediol	> 90 % (10 d, OECD 301A) The product is easily biodegradable.
Oxazolidine derivative	89,8 % (28 d, OECD 301B) Readily biodegradable

12.3 Bioaccumulative potential

Product:	Not applicable for mixtures
-----------------	-----------------------------

12.4 Mobility in soil:

Product:	Not applicable for mixtures
-----------------	-----------------------------

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

Water Hazard Class (WGK):

WGK 1: slightly water-endangering.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information:	Dispose in accordance with all applicable regulations.
-----------------------------	--

Disposal methods:	When storing used products, ensure that the waste categories and mixing instructions are observed. Do not empty into drains; dispose of this material and its container in a safe way. Product contains in the application concentration traces of iodine containing substances; this can result in an AOX value.
--------------------------	---

European Waste Codes

13 01 05*: non-chlorinated emulsions

SECTION 14: Transport information

ADR/RID

14.1 UN Number:	—
14.2 UN Proper Shipping Name:	—
14.3 Transport Hazard Class(es)	
Class:	Non-dangerous goods
Label(s):	—
Hazard No. (ADR):	—
Tunnel restriction code:	—
14.4 Packing Group:	—
14.5 Environmental hazards:	—

Product name: AQUACENT LT 68

14.6 Special precautions for user: –

ADN

14.1 UN Number: –
 14.2 UN Proper Shipping Name: –
 14.3 Transport Hazard Class(es)
 Class: Non-dangerous goods
 Label(s): –
 14.3 Packing Group: –
 14.5 Environmental hazards: –
 14.6 Special precautions for user: –

IMDG

14.1 UN Number: –
 14.2 UN Proper Shipping Name: –
 14.3 Transport Hazard Class(es)
 Class: Non-dangerous goods
 Label(s): –
 EmS No.: –
 14.3 Packing Group: –
 14.5 Environmental hazards: –
 14.6 Special precautions for user: –

IATA

14.1 UN Number: –
 14.2 Proper Shipping Name: –
 14.3 Transport Hazard Class(es):
 Class: Non-dangerous goods
 Label(s): –
 14.4 Packing Group: –
 14.5 Environmental hazards: –
 14.6 Special precautions for user: –

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

DIRECTIVE 2012/18/EU (SEVESO III) on the control of major-accident hazards involving dangerous substances

The product does not fall into the scope of the SEVESO III Directive.

Product name: AQUACENT LT 68

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Other information: The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. It was derived from the test data and/or the application of the conventional method.

Revision Date: 21.11.2018

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.