

SAFETY DATA SHEET

1. Identification

Product name RENOFORM CM

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: FUCHS LUBRICANTS CANADA LTD.

Address: 405 Dobbie Drive

Cambridge, ON N1T 1S8

Telephone: 519-622-2040 Fax: 519-622-2220

Contact Person: Technical Services Department

Emergency telephone number: 519-622-2040 (Bus. hrs) CANUTEC 1-888-226-8832 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 3

Health Hazards

Skin Corrosion/Irritation Category 2
Specific Target Organ Toxicity - Category 3¹

Single Exposure

Aspiration Hazard Category 1

Target Organs

1.Narcotic effect.

Unknown toxicity - Health

Acute toxicity, oral 0 %
Acute toxicity, dermal 0 %
Acute toxicity, inhalation, vapor 90.45 %
Acute toxicity, inhalation, dust 8.55 %

or mist

Label Elements

Hazard Symbol:

SDS CA 1/11





Signal Word: Danger

Hazard Statement: Flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

[electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take

action to prevent static discharges. Avoid breathing

dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only

outdoors or in a well-ventilated area. Wear protective gloves/eye

protection/face protection.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT

induce vomiting. IF ON SKIN (or hair): Take off immediately all

contaminated clothing and wash it before reuse. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. Specific treatment (see this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE/doctor/ if you feel

unwell. In case of fire: Use ... to extinguish.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked

up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

SDS CA 2/11



Mixtures

| Chemical Identity | Common name and synonyms | CAS number | Content in percent (%)* | |
|---|--------------------------|------------|-------------------------|--|
| Distillates (petroleum), hydrotreated light | Mineral spirits, | 64742-47-8 | 60 - 100% | |
| Mineral oil | | 64741-88-4 | 1 - 10% | |
| n-Nonane | | 111-84-2 | 1 - 10% | |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air. Call a POISON CENTRE/doctor/ if you feel unwell.

Skin Contact: Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of

vapors or gases to explosive concentrations.

Special protective equipment and precautions for firefighters

SDS CA 3/11



Special fire fighting procedures:

No data available.

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep unauthorized personnel away. Ensure adequate ventilation. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. In case of leakage, eliminate all ignition sources. Dike far ahead of larger spill for later recovery and disposal. Use non-sparking tools.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place. Flammable liquid storage.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | Туре | Exposure Limit Values | Source |
|-------------------|------|-----------------------|--------|
|-------------------|------|-----------------------|--------|

SDS CA 4/11



| Distillates (petroleum), hydrotreated light - Vapor as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
|--|---------------|---------------------|---|
| Distillates (petroleum), hydrotreated light - Non- aerosol as total hydrocarbon vapor | TWA | 200 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Distillates (petroleum), hydrotreated light - Vapor as total hydrocarbons | 8 HR ACL | 200 mg/m3 | Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009) |
| | 15 MIN ACL | 250 mg/m3 | Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009) |
| Distillates (petroleum), hydrotreated light | TWA | 400 ppm 1,590 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| Distillates (petroleum), hydrotreated light - Non- aerosol as total hydrocarbon vapor | TWA | 200 mg/m3 | US. ACGIH Threshold Limit Values (03 2012) |
| Mineral oil - Mist. | TWA | 1 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011) |
| Mineral oil - Mist. | TWA | 5 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| | STEL | 10 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| Mineral oil - Inhalable fraction. | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| | TWA | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |
| n-Nonane | TWA | 200 ppm 1,050 mg/m3 | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009) |
| n-Nonane | 8 HR ACL | 200 ppm | Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009) |
| | 15 MIN ACL | 250 ppm | Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009) |
| n-Nonane | TWA | 200 ppm 1,050 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (11 2011) |
| n-Nonane | TWA | 200 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013) |
| n-Nonane | TWA | 200 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015) |

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:

Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.

SDS_CA 5/11



Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state: Liquid

Form: No data available.

Color: Yellow

Odor: Mild petroleum/solvent

Odor threshold:

pH:

No data available.

No data available.

Melting point/freezing point:

No data available.

Initial boiling point and boiling range:

No data available.

Flash Point: 54 °C

Evaporation rate:No data available. **Flammability (solid, gas):**No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): 5 %(V)
Flammability limit - lower (%): 0.8 %(V)

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

No data available.

No data available.

Vapor density:No data available.Density:No data available.

Relative density: 0.791

Solubility(ies)

Solubility in water: Insoluble

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.

SDS CA 6/11



Viscosity: < 20 mm2/s (40 °C)

10. Stability and reactivity

Reactivity: Not reactive during normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Heat, sparks, flames.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin irritation.

Eye contact: Eye contact is possible and should be avoided. May irritate eyes.

Ingestion: Harmful if swallowed. Ingestion may result in vomiting; aspiration

(breathing) of vomitus into lungs must be avoided as even small quantities

may result in aspiration pneumonitis.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix (): > 5000 mg/kg

Dermal

Product: ATEmix (): 1000 - 2000 mg/kg

Inhalation

SDS CA 7/11



Product: ATEmix (, 4 h): > 20 mg/l Vapour

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

ACGIH Carcinogen List:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

SDS CA 8/11



12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for

recycling or disposal.

SDS CA 9/11



14. Transport information

TDG

UN Number: UN 1268

UN Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. (Mineral Spirits)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.:

Packing Group:

Excepted quantity PIN for exception quantity

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IMDG

UN Number: UN 1268

UN Proper Shipping Name: PETROLEUM DISTILLATES, N.O.S. (Mineral Spirits)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.: F-E, S-E

Packing Group: III
Limited quantity 5.00L

Excepted quantity PIN for exception quantity

Environmental Hazards: No Marine Pollutant No

Special precautions for user: Not regulated.

IATA

UN Number: UN 1268

Proper Shipping Name: Petroleum distillates, n.o.s.(Mineral Spirits)

Transport Hazard Class(es):

Class: 3
Label(s): 3

Packing Group: III
Limited quantity 10.00L

Excepted quantity PIN for exception quantity

Environmental Hazards: No Marine Pollutant No

SDS CA 10/11



Special precautions for user: Not regulated.

Cargo aircraft only: Allowed.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Not Regulated

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional

Reporting Requirements

NPRI PT5 Distillates (petroleum), Listed.

hydrotreated light

NPRI PT5 n-Nonane Listed.

Canada. Canadian Environmental Protection Act (CEPA). National Pollutant Release Inventory

(NPRI) (Parts 1-4)

NPRI Not Regulated

Greenhouse Gases

Not Regulated

16.Other information, including date of preparation or last revision

Issue Date: 06/15/2017

Revision Date: 06/15/2017

Version #: 1.1

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS CA 11/11