

1. Identification			
Product name		ANTICORIT SL 50276 HFA	
Other means of identification		No data available.	
Recommended use:		Corrosion inhibitor	
Restrictions on use:		Industrial use only	
Manufacturer/Importer/Su	upplier/Distributor Information	on	
Manufacturer			
Company Name:	Fuchs Lubricants Co.		
Address:	17050 Lathrop Avenue		
	Harvey, Illinois 60426		
Telephone:	708-333-8900		

Fax:	708-333-9180
Contact Person: E-mail:	EHS Department msds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

Hazard Classification		
Physical Hazards	Cotosoni A	
Flammable liquids Health Hazards	Category 4	
Aspiration Hazard	Category 1	
Label Elements		
Hazard Symbol:		

Signal Word:

Danger

Hazard Statement:

Combustible liquid. May be fatal if swallowed and enters airways.



Precautionary Statement	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection.
Response:	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. In case of fire: Use CO2, dry chemical, or foam to extinguish.
Storage:	Store in well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not	None.
result in GHS classification:	

Unknown toxicity Health	
Acute toxicity, oral	11.4 %
Acute toxicity, dermal	11.4 %
Acute toxicity, inhalation, vapor	90.49 %
Acute toxicity, inhalation, dust or mist	11.61 %

## 3. Composition/information on ingredients

### Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Mineral spirits	Confidential	60 - 100%
Mineral oil	Confidential	7 - 13%
Barium compound	Confidential	1 - 5%
Butylhydroxytoluene	Confidential	0.1 - 1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

## 4. First-aid measures

Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air. Call a Poison Center or doctor if you feel unwell.



Skin Contact:	Remove contaminated/saturated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.		
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.		
Most important symptoms/effects	s, acute and delayed		
Symptoms:	No data available.		
Indication of immediate medical a	ttention and special treatment needed		
Treatment:	Get medical attention as appropriate or if symptoms persist.		
5. Fire-fighting measures			
General Fire Hazards:	Move containers from fire area if you can do so without risk.		
Suitable (and unsuitable) extinguishing media			
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.		
Unsuitable extinguishing media:	Avoid water in straight hose stream as this will scatter and spread fire.		
Specific hazards arising from the chemical:	Heat may cause the containers to pressurize and possibly rupture. During fire, gases hazardous to health may be formed.		
Special protective equipment and	d precautions for firefighters		
Special fire fighting procedures:	No data available.		
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment appropriate for industrial fires.		
6. Accidental release measures	6		
Personal precautions,	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in		

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ensure adequate ventilation. Keep unauthorized personnel away. See Section 8 of the SDS for Personal Protective Equipment. Do not handle damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them.



Methods and material for containment and cleaning up:	Absorb spill with an inert material, then place in a container for safe and proper disposal. Eliminate all ignition sources if safe to do so. Dike far ahead of larger spill for later recovery and disposal. Use only non-sparking tools.
Environmental Precautions:	Prevent further leakage or spillage if safe to do so and protect against releases into the environment. Remediate as appropriate.
7. Handling and storage	
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharges.
Conditions for safe storage, including any incompatibilities:	Store locked up. Store in a well-ventilated place. Store in a cool place. Flammable liquid storage.

## 8. Exposure controls/personal protection

### **Exposure Limits**

Chemical name	type	Exposure Limit Values	Source
Mineral spirits - Non-aerosol as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Mineral oil - Mist.	STEL	10 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Barium compound - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Barium compound - as Ba	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Butylhydroxytoluene - Inhalable fraction and vapor.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (03 2012)

Protective Measures:	Use personal protective equipment as required.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.



LUBRICANTS. TECHNOLOGY.

# SAFETY DATA SHEET

### Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Discard contaminated footwear that cannot be cleaned. Avoid contact with skin, eyes, and clothing.

## 9. Physical and chemical properties

Appearance	
Physical state:	Liquid
Form:	No data available.
Color:	Amber
Odor:	Mild petroleum
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	67.22 °C (153.00 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	0.807
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	2 mm2/s (40 °C)

## 10. Stability and reactivity

**Reactivity:** 

Not reactive during normal use.

**Chemical Stability:** 

Material is stable under normal conditions.

MSDS\_US - R00000450080



Possibility of Hazardous Reactions:	None under normal conditions.
Conditions to Avoid:	Heat, sparks, flames.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

Information on likely routes of exposure Ingestion: Harmful if swallowed.	
Inhalation:	Harmful if inhaled.
Skin Contact:	Prolonged skin contact may cause redness and irritation.
Eye contact:	Eye contact is possible and should be avoided.
Symptoms related to the physic Ingestion:	al, chemical and toxicological characteristics No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Information on toxicological effects	
Acute toxicity (list all possible routes of exposure)	
Oral Product:	ATEmix (): > 5000 mg/kg
Dermal Product:	ATEmix (): 2000 - 5000 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
MSDS US B00000450080	



### Serious Eye Damage/Eye Irritation Product: No data available.

Respiratory or Skin Sensitization Product: No data available.

#### Carcinogenicity Product:

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

### **Germ Cell Mutagenicity**

General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
12. Ecological information	
Other effects:	No data available.
Aspiration Hazard Product:	May be fatal if swallowed and enters airways.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Specific Target Organ Toxicity - Product:	Single Exposure No data available.
Reproductive toxicity Product:	No data available.
In vivo Product:	No data available.
In vitro Product:	No data available.

### 13. Disposal considerations



Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

DOT	
UN Number:	NA 1993
UN Proper Shipping Name:	Combustible liquid, n.o.s.(Petroleum distillates)
Transport Hazard Class(es)	
Class:	CBL
Label(s):	NONE
Packing Group:	III
Marine Pollutant:	No
Special precautions for user:	-

### IMDG

Not regulated.

#### ΙΑΤΑ

Not regulated.

### 15. Regulatory information

#### **US Federal Regulations**

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Fire Hazard Immediate (Acute) Health Hazards

#### SARA 313 (TRI Reporting)

	Reporting threshold for	<u>Reporting threshold for</u> manufacturing and
Chemical Identity	other users	processing
Barium compound	10000 lbs	25000 lbs.
Barium compound	10000 lbs	25000 lbs.

MSDS\_US - R00000450080



## **US State Regulations**

## US. California Proposition 65

No component is regulated by CA Prop 65.

16.Other information, including date of preparation or last revision	
Issue Date:	14.05.2015
Revision Date:	14.05.2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	<b>This information is provided without warranty</b> . The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.