

# **SAFETY DATA SHEET**

## 1. Identification

ANTICORIT SV 50276 X **Product name** 

Other means of identification No data available.

Recommended use: Corrosion inhibitor

Restrictions on use: Industrial use only

## Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co. Address: 17050 Lathrop Avenue

Harvey, Illinois 60426

708-333-8900 Telephone: Fax: 708-333-9180

Contact Person: **EHS** Department E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

#### **Hazard Classification**

**Physical Hazards** 

Flammable liquids Category 3

**Health Hazards** 

Skin Corrosion/Irritation Category 2 Specific Target Organ Toxicity -Category 3

Single Exposure

Aspiration Hazard Category 1

#### **Label Elements**

#### **Hazard Symbol:**

SDS\_US 1/10





Signal Word: Danger

**Hazard Statement:** Flammable liquid and vapor.

Causes skin irritation.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Keep container tightly closed. Ground and bond

container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated

area.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see in product SDS). Take off contaminated clothing. In case of fire: Use water mist, dry chemical

extinguisher, or foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

**Unknown toxicity - Health** 

Acute toxicity, oral 5.53 %
Acute toxicity, dermal 4.57 %
Acute toxicity, inhalation, vapor 14.64 %

SDS\_US 2/10



Acute toxicity, inhalation, dust 96.99 % or mist

# 3. Composition/information on ingredients

**Hazardous Component(s):** 

Chemical name	CAS-No.	Concentration
Mineral spirits	Confidential	50 - <100%
Mineral oil	Confidential	1 - <5%
Barium compound	Confidential	1 - <5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

#### 4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth, Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention. Wash

contaminated clothing before reuse.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a protected location. Move

containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-

extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Avoid water in straight hose stream; will scatter and spread fire.

SDS\_US 3/10



Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

## Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep unauthorized personnel away. Ensure adequate ventilation. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. In case of leakage, eliminate all ignition sources. Dike far ahead of larger spill for later recovery and disposal. Use non-sparking tools.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

#### 7. Handling and storage

Precautions for safe handling:

Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.

Conditions for safe storage, including any

incompatibilities:

Store locked up. Store in a well-ventilated place. Store in a cool place.

Flammable liquid storage.

SDS\_US 4/10



#### 8. Exposure controls/personal protection

**Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Mineral spirits - Non-aerosol as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Barium compound - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Barium compound - as Ba	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)

**Protective Measures:** Use explosion-proof ventilation equipment. Good general ventilation (typically

10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain

airborne levels to an acceptable level. Provide easy access to water supply and

eye wash facilities.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

# 9. Physical and chemical properties

#### **Appearance**

Physical state: liquid

Form: No data available.

Color: Light amber

Odor: Mild petroleum/solvent

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.

SDS\_US 5/10



Flash Point: 40.56 °C (105.01 °F)
Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density:

No data available.

Relative density: 0.8

Solubility(ies)

Solubility in water: Insoluble

Solubility (other):

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

No data available.

1.75 mm2/s (40 °C)

Other information

**VOC:** 628.56 g/l (ASTM E 1868-10)

#### 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

Products:

None under normal conditions.

**Conditions to avoid:** Heat, sparks, flames.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

#### Information on likely routes of exposure

**Ingestion:** Ingestion may cause irritation and malaise. Ingestion may result in vomiting;

aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis. Harmful if swallowed.

SDS\_US 6/10



**Inhalation:** Harmful if inhaled. May cause nausea, headache, dizziness and

intoxication.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): 2000 - 5000 mg/kg

**Dermal** 

**Product:** ATEmix (): 2000 - 5000 mg/kg

Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

**Skin Corrosion/Irritation** 

**Product:** No data available.

**Serious Eye Damage/Eye Irritation** 

**Product:** No data available.

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

SDS\_US 7/10



#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

#### **Germ Cell Mutagenicity**

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** May be fatal if swallowed and enters airways.

Other effects: No data available.

#### 12. Ecological information

**General information:** This product has not been evaluated for ecological toxicity or other

environmental effects.

## 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

SDS\_US 8/10



#### 14. Transport information

DOT

UN Number: NA 1993

UN Proper Shipping Name: Combustible liquid, n.o.s.(Petroleum distillates)

Transport Hazard Class(es)

Class: CBL
Label(s): NONE
Packing Group: III
Marine Pollutant: No

Special precautions for user: –

**IMDG** 

UN Number: UN 1993

UN Proper Shipping Name: FLAMMABLE LIQUID, N.O.S.(Petroleum distillates)

Transport Hazard Class(es)

Class: 3 Label(s): 3

EmS No.: F-E, S-E

Packing Group:

Marine Pollutant: Not regulated.

Special precautions for user: –

IATA

UN Number: UN 1993

Proper Shipping Name: Flammable liquid, n.o.s.(Petroleum distillates)

Transport Hazard Class(es):

Class: 3
Label(s): 3
Packing Group: III

Environmental Hazards Not regulated.

Special precautions for user:

Other information

Passenger and cargo aircraft: Allowed. Cargo aircraft only: Allowed.

## 15. Regulatory information

#### **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Fire Hazard

Immediate (Acute) Health Hazards

Flammable (gases, aerosols, liquids, or solids)

SDS\_US 9/10



Skin Corrosion or Irritation Specific target organ toxicity (single or repeated exposure) Aspiration Hazard

#### SARA 313 (TRI Reporting)

Reporting threshold for manufacturing and processing

Barium compound 10000 lbs 25000 lbs.

Reporting threshold for manufacturing and processing 25000 lbs.

25000 lbs.

## **US State Regulations**

## **US. California Proposition 65**

No ingredient requiring a warning under CA Prop 65.

# 16.Other information, including date of preparation or last revision

**Issue Date:** 16.02.2022

**Revision Date:** 16.02.2022

Version #: 1.4

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS\_US 10/10