

SAFETY DATA SHEET

1. Identification

Product identifier	ECOCOOL S PT 45 B
Other means of identification	No data available.
Recommended use:	Metalworking fluid
Restrictions on use:	Industrial use only

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
 Address: 17050 Lathrop Avenue
 Harvey, Illinois 60426
 Telephone: 708-333-8900
 Fax: 708-333-9180
 Contact Person: EHS Department
 E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard identification

Hazard Classification

Health Hazards

Skin sensitizer Category 1

Unknown toxicity - Health

Acute toxicity, oral	5.01 %
Acute toxicity, dermal	3.04 %
Acute toxicity, inhalation, vapor	24.54 %
Acute toxicity, inhalation, dust or mist	17.89 %

% of the mixture consists of an ingredient or ingredients of unknown acute toxicity

Label Elements

Hazard Symbol:



Signal Word:	Warning
Hazard Statement:	May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.
Response:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). Take off contaminated clothing and wash it before reuse.
Disposal:	Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	45 - 70%
Poly(oxy-1,2-ethanediyl), #- (9Z)-9-octadecen-1-yl-#-hydroxy-		9004-98-2	3 - 7%
Sulfonated petroleum, sodium salt	Sulfonic acids, petroleum, sodium salts,	68608-26-4	3 - 7%
Tall oil, compound with triethanolamine		68092-29-5	1 - 5%
Triethanolamine		102-71-6	1 - 5%
Distillates (petroleum), hydrotreated heavy paraffinic		64742-54-7	1 - 5%
Polyethylene glycol monotallate		61791-00-2	0.5 - 1.5%
Hexylene glycol		107-41-5	0.1 - 1%
Organic copper salt	Organic copper salt,	866-82-0	0.1 - 1%
3(2H)-Isothiazolone, 2-methyl-		2682-20-4	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water.
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.

Most important symptoms/effects, acute and delayed

Symptoms:	No data available.
Hazards:	No data available.

Indication of immediate medical attention and special treatment needed

Treatment:	Get medical attention if symptoms occur.
-------------------	--

5. Fire-fighting measures

General Fire Hazards:	No unusual fire or explosion hazards noted.
------------------------------	---

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.
--	---

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
---	---

Methods and material for containment and cleaning up:

Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable dusts and mists.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable dusts and mists.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Triethanolamine	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Triethanolamine	TWA	5 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Triethanolamine	TWA	0.5 ppm 3.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Triethanolamine	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)

Triethanolamine	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Triethanolamine	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Hexylene glycol	CEILING	25 ppm 121 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Hexylene glycol	CEILING	25 ppm	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Hexylene glycol	CEILING	25 ppm	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2012)
Hexylene glycol	Ceiling	25 ppm	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Hexylene glycol	CEILING	25 ppm 121 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Hexylene glycol - Vapor fraction	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	STEL	50 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Hexylene glycol - Vapor fraction	TWA	25 ppm	US. ACGIH Threshold Limit Values, as amended (03 2017)
Hexylene glycol - Aerosol, inhalable.	STEL	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
Hexylene glycol - Vapor fraction	STEL	50 ppm	US. ACGIH Threshold Limit Values, as amended (03 2017)
Organic copper salt - Fume. - as Cu	TWA	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Organic copper salt - Fume. - as Cu	TWA	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Organic copper salt - Dust and mist. - as Cu	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	TWA	5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
	STEL	10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	8 HR ACL	5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL	10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	TWA	1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable dusts and mists.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Chemical Identity	Type	Exposure Limit Values	Source

Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	TWA		1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable dusts and mists.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Triethanolamine	TWA		5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Triethanolamine	TWA		5 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Triethanolamine	TWA	0.5 ppm	3.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Triethanolamine	8 HR ACL		5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
	15 MIN ACL		10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Triethanolamine	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Triethanolamine	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Distillates (petroleum), hydrotreated heavy paraffinic - Mist.	TWA		1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Distillates (petroleum), hydrotreated heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Distillates (petroleum), hydrotreated heavy paraffinic - Inhalable dusts and mists.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Hexylene glycol	CEILING	25 ppm	121 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)
Hexylene glycol	CEILING	25 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Hexylene glycol	CEILING	25 ppm		Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended (03 2012)
Hexylene glycol	Ceiling	25 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended (05 2009)
Hexylene glycol	CEILING	25 ppm	121 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Hexylene glycol - Vapor fraction	TWA	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	STEL	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)

Hexylene glycol - Vapor fraction	TWA	25 ppm	US. ACGIH Threshold Limit Values, as amended (03 2017)
Hexylene glycol - Aerosol, inhalable.	STEL	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
Hexylene glycol - Vapor fraction	STEL	50 ppm	US. ACGIH Threshold Limit Values, as amended (03 2017)
Organic copper salt - Fume. - as Cu	TWA	0.2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Organic copper salt - Fume. - as Cu	TWA	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Organic copper salt - Dust and mist. - as Cu	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

- General information:** Use personal protective equipment as required.
- Eye/face protection:** Wear safety glasses with side shields (or goggles).
- Skin Protection**
 - Hand Protection:** No data available.
 - Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
- Hygiene measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

- Appearance**
- Physical state:** liquid
 - Form:** liquid
 - Color:** Green
 - Odor:** Mild
 - Odor threshold:** No data available.
 - pH:** No data available.
 - Melting point/freezing point:** No data available.
 - Initial boiling point and boiling range:** No data available.
 - Flash Point:** 151.67 °C
 - Evaporation rate:** No data available.
 - Flammability (solid, gas):** No data available.
 - Upper/lower limit on flammability or explosive limits**
 - Flammability limit - upper (%):** No data available.

Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Density:	No data available.
Relative density:	0.945 (15 °C)
Solubility(ies)	
Solubility in water:	Emulsifiable in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	> 20.5 mm ² /s (40 °C)
Other information	
VOC:	13.19 % (Method 24) 57.39 g/l (ASTM E 1868-10) 5.74 g/l

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	May cause an allergic skin reaction.
Eye contact:	Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: > 5000 mg/kg

Dermal

Product: ATEmix: 2000 - 5000 mg/kg

Inhalation

Product:

Delayed and immediate effects, including chronic effects from short- and long-term exposure

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

ACGIH Carcinogen List:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity
Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product: No data available.

Aspiration Hazard
Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Chronic hazards to the aquatic environment:

Fish
Product: No data available.

Aquatic Invertebrates
Product: No data available.

Toxicity to Aquatic Plants
Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil:

No data available.

Other adverse effects:

Harmful to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions:

Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not Regulated.

IMDG

Not Regulated.

IATA

Not Regulated.

15. Regulatory information

