

SAFETY DATA SHEET

1. Identification

Product identifier ECOCOOL S PT 45 B

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co. Address: 17050 Lathrop Avenue

Harvey, Illinois 60426

Telephone: 708-333-8900 Fax: 708-333-9180

Contact Person: EHS Department sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard identification

Hazard Classification

Health Hazards

Serious Eye Damage/Eye Irritation Category 2A Skin sensitizer Category 1

Unknown toxicity - Health

Acute toxicity, oral 9.32 %
Acute toxicity, dermal 13.22 %
Acute toxicity, inhalation, vapor 93.31 %
Acute toxicity, inhalation, dust 89.49 %

or mist

% of the mixture consists of an ingredient or ingredients of unknown acute toxicity

Label Elements

Hazard Symbol:

SDS_CA 1/12





Signal Word: Warning

Hazard Statement: Causes serious eye irritation.

May cause an allergic skin reaction.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after

handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/eye protection/face protection.

Response: IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get

medical advice/attention. Specific treatment (see in product SDS). Take off

contaminated clothing and wash it before reuse. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

SDS_CA 2/12



Mixtures

Chemical Identity	Common name and synonyms	CAS number	Content in percent (%)*
Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil,	64742-52-5	45 - 70%
Ethoxylated alcohol	Ethoxylated alcohol,	68920-66-1	1 - 5%
Distillates (petroleum), hydrotreated heavy naphthenic	Mineral oil,	64742-52-5	1 - 5%
Triethanolamine	Triethanolamine,	102-71-6	1 - 5%
Alkyl Sodium Sulfonate	Alkyl Sodium Sulfonate,	148520-82-5	1 - 5%
Poly(oxy-1,2-ethanediyl), #- (9Z)-9-octadecen-1-yl-#- hydroxy-	Polyethylene glycol monooleyl ether,	9004-98-2	1 - 5%
Polyethylene glycol monotallate	Fatty acids, tall-oil, ethoxylated,	61791-00-2	0.5 - 1.5%
Hexylene glycol	Hexylene glycol,	107-41-5	0.1 - 1%
Organic copper salt		866-82-0	0.1 - 1%
3(2H)-Isothiazolone, 2-methyl-	3(2H)-Isothiazolone, 2-methyl-,	2682-20-4	0.1 - 1%
Distillates (petroleum), solvent- dewaxed heavy paraffinic	Mineral oil,	64742-65-0	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion: Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

Immediately remove contaminated clothing and shoes and wash skin with

soap and plenty of water.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

SDS_CA 3/12



Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Contains a component that when heated at or above 300F (150C) may generate Formaldehyde vapors. Wash hands thoroughly after handling. Add material slowly when mixing with water. Do not add water to the material; instead, add the material to the water. Avoid contact with eyes, skin, and clothing.

Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

SDS CA 4/12



8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit	Values	Source
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Distillates (petroleum), hydrotreated heavy naphthenic - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Triethanolamine	TWA		5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Triethanolamine	TWA		5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Triethanolamine	TWA	0.5 ppm	3.1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Triethanolamine	8 HR ACL		5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL		10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21 (05 2009)

SDS_CA 5/12



Triethanolamine	TWA	5 mg/m3		Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Triethanolamine	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Hexylene glycol	CEILING	25 ppm	121 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Hexylene glycol	CEILING	25 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Hexylene glycol	CEILING	25 p _l	om	Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) (03 2012)
Hexylene glycol	CEV	25 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hexylene glycol	Ceiling	25 ppm		Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Hexylene glycol	CEILING	25 ppm	121 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hexylene glycol - Vapor fraction	TWA	25 ppm		US. ACGIH Threshold Limit Values (03 2017)
Hexylene glycol - Aerosol, inhalable.	STEL		10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Hexylene glycol - Vapor fraction	STEL	50 ppm		US. ACGIH Threshold Limit Values (03 2017)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	TWA		5 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL		10 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Distillates (petroleum), solvent-dewaxed heavy paraffinic	8 HR ACL		5 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
	15 MIN ACL		10 mg/m3	Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) (05 2009)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	TWA		1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Inhalable fraction.	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Distillates (petroleum), solvent-dewaxed heavy paraffinic - Mist.	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls

No data available.

SDS_CA 6/12



Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process

enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable

level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: No data available.

Color: Green Odor: Mild

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.

Flash Point: 151.67 °C

Evaporation rate:No data available.
Flammability (solid, gas):
No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

No data available.

Vapor density:No data available.Density:No data available.

Relative density: 0.945

SDS CA 7/12



Solubility(ies)

Solubility in water: Emulsifiable in water Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.

Viscosity: > 20.5 mm2/s (40 °C)

Other information

VOC: 13.19 % (Method 24)

57.39 g/I (ASTM E 1868-10)

5.74 g/l

10. Stability and reactivity

Reactivity: Not reactive during normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors. formaldehyde

11. Toxicological information

Information on likely routes of exposure

Inhalation: Harmful if inhaled.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

SDS_CA 8/12



Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: > 5000 mg/kg

Dermal

Product:

Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Delayed and immediate effects, including chronic effects from short- and long-term exposure

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

ACGIH Carcinogen List:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

SDS_CA 9/12



Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

SDS_CA 10/12



Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for

recycling or disposal.

14. Transport information

TDG

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

15. Regulatory information

Canada Federal Regulations

List of Toxic Substances (CEPA, Schedule 1)

Not Regulated

Export Control List (CEPA 1999, Schedule 3)

Not Regulated

National Pollutant Release Inventory (NPRI)

Canada. National Pollutant Release Inventory (NPRI) Substances, Part 5, VOCs with Additional

Reporting Requirements

NPRI PT5 Not Regulated

Canada. National Pollutant Release Inventory (NPRI) (Schedule 1, Parts 1-4)

NPRI Not Regulated

Greenhouse Gases

Not Regulated

16.Other information, including date of preparation or last revision

Issue Date: 07/01/2019

Revision Date: 07/01/2019

Version #: 1.1

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS_CA 11/12



SDS_CA 12/12