

SAFETY DATA SHEET

1. Identification

Product name ECOCUT 2200 SAZ

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426
Telephone: 708-333-8900
Fax: 708-333-9180

Contact Person: EHS Department
E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Specific Target Organ Toxicity - Single Exposure	Category 3

Label Elements

Hazard Symbol:



Signal Word: Warning

Hazard Statement: Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.

Precautionary Statements

Prevention: Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards which do not result in GHS classification: None.

Unknown toxicity - Health

Acute toxicity, oral	37.9 %
Acute toxicity, dermal	49.92 %
Acute toxicity, inhalation, vapor	56.67 %
Acute toxicity, inhalation, dust or mist	52.15 %

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	25 - <50%
Silicon carbide (SiC)	409-21-2	20 - <50%
Aluminum oxide (Al ₂ O ₃)	1344-28-1	5 - <10%
Zirconium oxide (ZrO ₂)	1314-23-4	1 - <5%
Poly(oxy-1,2-ethanediyl), #- (4-nonylphenyl)-#-	127087-87-0	1 - <3%

hydroxy-, branched		
Quaternary ammonium compounds, bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite	68953-58-2	1 - <5%
Graphite	7782-42-5	1 - <5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures

Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Water spray, fog, CO ₂ , dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling: Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Wash hands thoroughly after handling. Add material slowly when mixing with water. Do not add water to the material; instead, add the material to the water. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities: Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

8. Exposure controls/personal protection

Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon carbide (SiC) - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon carbide (SiC) - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon carbide (SiC) - Respirable fraction.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2014)
Silicon carbide (SiC) - Inhalable fraction.	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2014)
Silicon carbide (SiC) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Fiber.	TWA	0.1 fibers/cm ³	US. ACGIH Threshold Limit Values, as amended (03 2018)
Silicon carbide (SiC) - Respirable particles.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Silicon carbide (SiC) - Inhalable particles.	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Aluminum oxide (Al ₂ O ₃) - Respirable fraction.	TWA	1 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2012)
Aluminum oxide (Al ₂ O ₃) - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide (Al ₂ O ₃) - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum oxide (Al ₂ O ₃) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide (Al ₂ O ₃) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide (Al ₂ O ₃) - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide (Al ₂ O ₃) - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum oxide (Al ₂ O ₃) - Inhalable particles.	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Aluminum oxide (Al ₂ O ₃) - Respirable particles.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Zirconium oxide (ZrO ₂) - as Zr	STEL	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2012)
Zirconium oxide (ZrO ₂) - as Zr	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2012)

Zirconium oxide (ZrO ₂) - as Zr	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Zirconium oxide (ZrO ₂) - Inhalable particles.	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Zirconium oxide (ZrO ₂) - Respirable particles.	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2021)
Zirconium oxide (ZrO ₂) - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Zirconium oxide (ZrO ₂) - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Zirconium oxide (ZrO ₂) - Respirable fraction.	TWA	5 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Zirconium oxide (ZrO ₂) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Zirconium oxide (ZrO ₂) - Total dust.	TWA	15 mg/m ³	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Zirconium oxide (ZrO ₂) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Graphite - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Graphite - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Graphite - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)

Protective Measures:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

Eye Protection:

Wear safety glasses with side shields (or goggles).

Skin and Body Protection:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state:	Gel
Form:	Gel
Color:	Gray
Odor:	mild petroleum
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.439 (15 °C)
Solubility(ies)	
Solubility in water:	Slightly Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
VOC:	7.2 %

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	No data available.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.

Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	Harmful if swallowed. May be harmful if swallowed.
Inhalation:	Harmful if inhaled.
Skin Contact:	Causes skin irritation.
Eye contact:	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix (): > 5000 mg/kg
Dermal Product:	ATEmix (): 2000 - 5000 mg/kg
Inhalation Product:	

Repeated dose toxicity Product:	No data available.
--	--------------------

Skin Corrosion/Irritation Product:	No data available.
---	--------------------

Serious Eye Damage/Eye Irritation Product:	No data available.
---	--------------------

Respiratory or Skin Sensitization Product:	No data available.
---	--------------------

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

General information:

This product has not been evaluated for ecological toxicity or other environmental effects.

13. Disposal considerations

Disposal instructions:

Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Crystalline silica	kidney effects
	lung effects
	immune system effects
	Cancer

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Skin Corrosion or Irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Aluminum oxide	10000 lbs	25000 lbs.
Nonylphenol polyethylene glycol ether	10000 lbs10000 lbs	25000 lbs.

US State Regulations

US. California Proposition 65



This product can expose you to chemicals including Ethylene oxide which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

Crystalline silica, 1,4-Dioxane which is [are] known to the State of California to cause cancer.
For more information go to www.P65Warnings.ca.gov.

16. Other information, including date of preparation or last revision

Issue Date: 03.12.2024

Revision Date: 29.11.2024

Version #: 1.0

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.