

# **SAFETY DATA SHEET**

### 1. Identification

ECOCUT 2800 S **Product name** 

Other means of identification No data available.

Recommended use: Lubricant

Restrictions on use: Industrial use only

## Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Fuchs Lubricants Co. Company Name: Address: 17050 Lathrop Avenue Harvey, Illinois 60426

708-333-8900

Telephone: Fax: 708-333-9180

Contact Person: **EHS** Department E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A Specific Target Organ Toxicity -Category 3

Single Exposure

#### **Label Elements**

## **Hazard Symbol:**



**Signal Word:** Warning

SDS\_US 1/10



Hazard Statement: Causes skin irritation.

Causes serious eye irritation. May cause respiratory irritation.

Precautionary Statements

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Wash face, hands and

any exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing/ eye protection/

face protection.

**Response:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs:

Get medical advice/attention. Take off contaminated clothing. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a

POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked

up.

**Disposal:** Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Other hazards which do not result in GHS classification:

None.

#### **Unknown toxicity - Health**

Acute toxicity, oral 49.54 % Acute toxicity, dermal 49.56 % Acute toxicity, inhalation, vapor 56.67 % Acute toxicity, inhalation, dust 56.15 %

or mist

#### 3. Composition/information on ingredients

## **Hazardous Component(s):**

Chemical name	CAS-No.	Concentration
Silicon carbide (SiC)	409-21-2	20 - <50%
Distillates (petroleum), hydrotreated heavy	64742-52-5	25 - <50%
naphthenic		
Poly(oxy-1,2-ethanediyl), #-(4-nonylphenyl)-#-	127087-87-0	1 - <3%
hydroxy-, branched		
Quaternary ammonium compounds,	68953-58-2	1 - <5%

SDS\_US 2/10



bis(hydrogenated tallow alkyl)dimethyl, salts with bentonite		
Graphite	7782-42-5	1 - <5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

#### 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing

before reuse. Get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-

extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

SDS\_US 3/10



Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

#### 7. Handling and storage

Precautions for safe handling:

Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Wash hands thoroughly after handling. Add material slowly when mixing with water. Do not add water to the material; instead, add the material to the water. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

SDS\_US 4/10



## 8. Exposure controls/personal protection

**Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Silicon carbide (SiC) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon carbide (SiC) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Silicon carbide (SiC) - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Silicon carbide (SiC) - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Silicon carbide (SiC) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Silicon carbide (SiC) - Fiber.	TWA	0.1 fibers/cm3	US. ACGIH Threshold Limit Values, as amended (03 2018)
Silicon carbide (SiC) - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Silicon carbide (SiC) - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)

#### **Protective Measures:**

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

SDS\_US 5/10



**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

## 9. Physical and chemical properties

**Appearance** 

Physical state:GelForm:GelColor:Gray

Odor: mild petroleum **Odor threshold:** No data available. pH: No data available. Melting point/freezing point: No data available. Initial boiling point and boiling range: No data available. Flash Point: > 160 °C (> 320 °F) **Evaporation rate:** No data available. Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

Relative density: 1.439

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

SDS\_US 6/10



VOC: 7.2 %

## 10. Stability and reactivity

Reactivity: Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

## 11. Toxicological information

Information on likely routes of exposure

Ingestion: May be harmful if swallowed.

Inhalation: Harmful if inhaled.

**Skin Contact:** Causes skin irritation.

Causes serious eye irritation. Eye contact:

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

**Skin Contact:** No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): > 5000 mg/kg

**Dermal** 

**Product:** ATEmix (): 2000 - 5000 mg/kg

Inhalation

SDS\_US 7/10



**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

**Respiratory or Skin Sensitization** 

**Product:** No data available.

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

SDS\_US 8/10



12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

## 14. Transport information

DOT

Not Regulated.

**IMDG** 

Not Regulated.

**IATA** 

Not Regulated.

#### 15. Regulatory information

## **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Crystalline silica kidney effects lung effects

immune system effects

Cancer

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Skin Corrosion or Irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

SDS\_US 9/10



**SARA 313 (TRI Reporting)** 

Reporting threshold for other users 10000 lbs10000 Reporting threshold for manufacturing and processing 25000 lbs.

Nonylphenol polyethylene glycol ether

**Chemical Identity** 

lbs

#### **US State Regulations**

#### **US. California Proposition 65**



This product can expose you to chemicals including Ethylene oxidewhich is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

Crystalline silica1,4-Dioxanewhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

## 16.Other information, including date of preparation or last revision

**Issue Date:** 18.02.2025

**Revision Date:** No data available.

Version #: 1.1

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS\_US 10/10