according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date : 03.02.2023 **Version (Revision) :** 1.3.0 (1.2.0)

Print date : 03.02.2023

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

ELASTOLUB S 300

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Product Categories [PC]

PC24 - Lubricants, greases, release products

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream

user/distributor)

Lubricant Consult GmbH

Street: Gutenbergstraße 13

Postal code/city: 63477 MAINTAL (GERMANY)

US Distributor
Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Telephone: +49 6109/7650-0 (708) 333-8900 (800) 255-3924 24 hrs Emergency

Telefax: +49 6109/7650-51

E-mail: msds-request@lubcon.com

Information contact: Environment, Health & Safety: Dr. Rüdiger Hofmann

1.4 Emergency telephone number

+49 6109/7650-0

Monday to Friday 8:00 AM to 4:00 PM (CET)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

None

2.2 Label elements

None

2.3 Other hazards

None

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

None

Further ingredients

PFPE oil (Perfluoropolyethers)

Inorganic solid compounds

SECTION 4: First aid measures

4.1 Description of first aid measures

Page: 1 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date : 03.02.2023

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Change contaminated, saturated clothing. Wash immediately with: Water and soap In case of skin irritation, consult a physician.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

The product itself does not burn. Reactions with combustible materials are possible.

5.1 Extinguishing media

Suitable extinguishing media

Dry extinguishing powder. Carbon dioxide (CO2). ABC-powder. BC-powder. Foam. Dry sand.

Unsuitable extinguishing media

Water. Strong water jet. High power water jet.

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products:

Gases/vapours, corrosive. Very toxic by inhalation. Pyrolysis products, toxic, containing fluorine. Hydrogen fluoride.

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

5.4 Additional information

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: Accidental release measures

Special danger of slipping by leaking/spilling product. Keep away from sources of ignition - No smoking.

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Ensure waste is collected and contained. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

6.3 Methods and material for containment and cleaning up

Take up mechanically, placing in appropriate containers for disposal. Soak up inert absorbent and dispose as waste

Page: 2 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date: 03.02.2023

requiring special attention. Suitable material for taking up: Universal binder. Kieselguhr.

6.4 Reference to other sections

None

SECTION 7: Handling and storage



7.1 Precautions for safe handling

It is recommended to design all work processes always so that the following is excluded: Generation/formation of mist. Avoid: Inhalation of vapours or spray/mists Skin contact. Eye contact. When using do not eat, drink, smoke, sniff.

7.2 Conditions for safe storage, including any incompatibilities

Hints on joint storage

Storage class: 13

Storage class (TRGS 510): 13

Keep away from

Food and feedingstuffs

Further information on storage conditions

Keep/Store only in original container. Keep container tightly closed. Protect against Humidity. Dust deposits.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and after work. Separate storage of work clothes. Take the precautions customary when handling chemicals.

8.1 Control parameters

None

8.2 Exposure controls

Personal protection equipment

Eye/face protection

None, if handled according to order. Eye protection: not required. Avoid: Eye contact.

Recommended eye protection articles

DIN EN 166

Skin protection

Hand protection

Hand protection is not required

By long-term hand contact: Wear suitable gloves.

Suitable material: PE (Polyethylene). NR (natural rubber, natural latex). NBR (Nitrile rubber). BR (Butyl

caoutchouc, butyl rubber).

Breakthrough time (maximum wearing time): PE > 480 min.; NR > 480 min.; CR > 480 min.; NBR > 480

min.; BR > 480 min.

Thickness of the glove material: min. 0,38 mm

Recommended glove articles: EN ISO 374; DIN EN 420 Uvex. KCL, MAPA. Or comparable articles from other

companies.

Respiratory protection

No special measures are necessary. Avoid: Inhalation of vapours or spray/mists

Page: 3 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date : 03.02.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour: whitish

Safety relevant basis data

Physical state: pasty Initial boiling point and boiling (1013 hPa) 300 °C range: **Decomposition temperature:** (1013 hPa) 300 °C Flash point : (1013 hPa) none Vapour pressure: (50°C) hPa 0,01 Density: (20 °C) 1,86 q/cm³

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable.

10.3 Possibility of hazardous reactions

Alkali metals. Alkaline earth metal. Powdered metals. Light metals. Aluminium. Titanium. Lewis-acid.

10.4 Conditions to avoid

Thermal decomposition can lead to the release of toxic and corrosive gases.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

Carbon monoxide. Carbon dioxide. Pyrolysis products, toxic, containing fluorine. Hydrogen fluoride.

SECTION 11: Toxicological information

This product is unlikely to harm health, given normal and proper handling and hygenic precautions.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

By analogy:

Acute effects

Acute oral toxicity

Parameter: max. tolerant dose

Exposure route: Oral Species: Rat

Effective dose : > 5000 mg/kg

Acute dermal toxicity

Parameter: max. tolerant dose

Exposure route: Dermal
Species: Rabbit
Effective dose: > 5000 mg/kg

11.2 Information on other hazards

No information available.

Page: 4 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date : 03.02.2023

SECTION 12: Ecological information

Discharge into the environment must be avoided.

12.1 Toxicity

By analogy:

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter: LC50

Species: Brachydanio rerio (Zebrafish)
Evaluation parameter: Acute (short-term) fish toxicity

Effective dose : = 1300 mg/l Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter: EC50

Species: Daphnia magna (Big water flea)

Effective dose : = 200 mg/l Exposure time : 24 h

Bacteria toxicity

Parameter: EC50

Species: Pseudomonas putida
Effective dose: > 1000 mg/l
Exposure time: 3 h

12.2 Persistence and degradability

Biodegradation

Overall evaluation on the mixture: The product is difficult to biologically degrade.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

Endocrine disrupting potential: None known.

12.7 Other adverse effects

This product does not contain nanoparticles.

12.8 Overall evaluation

If product enters soil, it will be mobile and may contaminate groundwater. In accordance with the required stability the product is poorly biodegradable.

SECTION 13: Disposal considerations

Dispose according to legislation. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.1 Waste treatment methods

Send to a hazardous waste incinerator facility under observation of official regulations. Collect the waste separately. Evidence for disposal must be provided.

Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Page: 5 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date : 03.02.2023

Waste code product

07 06 07 - Halogenated still bottoms and reaction residues. - Contains Fluoropolymers

Waste code packaging

15 01 10 - Packaging containing residues of or contaminated by hazardous substances.

SECTION 14: Transport information

14.1 UN number or ID number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Restrictions of occupation

Not relevant

Störfallverordnung

Not subject to StörfallVO.

Water hazard class (WGK)

Class: nwg (Non-hazardous to water) Classification according to AwSV

Other regulations, restrictions and prohibition regulations

Switzerland

VOCV-Regulation

Volatile organic compounds (VOC) content in percent by weight: 0 %

Additional information

TSCA (Toxic Substances Control Act) - USA, United States of America

All chemical substances in this mixture are included on or are exempted from listing on the TSCA Inventory for Chemical Substances.

California Proposition 65 - State of California

Based on available information this product does not contain any components or chemicals currently known to the State of California to cause cancer, birth defects or reproductive harm at levels which would be subject to Proposition 65.

15.2 Chemical safety assessment

No information available.

SECTION 16: Other information

Page: 6 / 7

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : ELASTOLUB S 300

Revision date: 03.02.2023 **Version (Revision):** 1.3.0 (1.2.0)

Print date : 03.02.2023

16.1 Indication of changes

13. Waste codes/waste designations according to EWC/AVV · 15. National regulations · 15. Water hazard class (WGK)

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The statement is derived from the properties of the single components.

16.5 Relevant H- and EUH-phrases (Number and full text)

None

16.6 Training advice

None

16.7 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 7 / 7