



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 1. Identification

**Product name** HYKOGREEN 707 CONC  
**Other means of identification** No data available.  
**Recommended use:** Metalworking fluid  
**Restrictions on use:** Industrial use only

### Manufacturer/Importer/Supplier/Distributor Information

#### Manufacturer

**Company Name:** Fuchs Lubricants Co.  
**Address:** 17050 Lathrop Avenue  
Harvey, Illinois 60426  
**Telephone:** 708-333-8900  
**Fax:** 708-333-9180

**Contact Person:** EHS Department  
**E-mail:** sds@fuchsus.com

**Emergency telephone number:** 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Toxic to reproduction Category 2

### Label Elements

#### Hazard Symbol:



**Signal Word:** Warning

**Hazard Statement:** Suspected of damaging fertility or the unborn child.

#### Precautionary Statements



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:** If exposed or concerned: Get medical advice/attention.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

#### Unknown toxicity - Health

Acute toxicity, oral	11 %
Acute toxicity, dermal	11 %
Acute toxicity, inhalation, vapor	86.86 %
Acute toxicity, inhalation, dust or mist	89.4 %

### 3. Composition/information on ingredients

#### Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Mineral oil	Confidential	60 - 100%
Graphite	7782-42-5	10 - 20%
Aluminum compound	Confidential	1 - 5%
2-Ethylhexanoic acid	149-57-5	1 - 3%
Zinc compound	Confidential	0.1 - 1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

### 4. First-aid measures

**Ingestion:** Rinse mouth thoroughly. Call a POISON CENTER/doctor/.../if you feel unwell. Do NOT induce vomiting.

**Inhalation:** Move to fresh air. Call a POISON CENTER/doctor/.../if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

## Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

## 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Water spray, fog, CO<sub>2</sub>, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.

### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures:** See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.

**Methods and material for containment and cleaning up:** Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

**Environmental Precautions:** Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

---

## 7. Handling and storage

**Precautions for safe handling:** End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required.

**Conditions for safe storage, including any incompatibilities:** Store locked up.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 8. Exposure controls/personal protection

### Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Mineral oil - Mist.	STEL	10 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Graphite - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Graphite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Aluminum compound - Respirable fraction.	TWA	1 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Aluminum compound	TWA	10 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Aluminum compound - as Al	TWA	2 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Zinc compound	TWA	10 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Zinc compound - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Zinc compound - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

### Protective Measures:

Use personal protective equipment as required.

### Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

### Eye Protection:

Wear safety glasses with side shields (or goggles).

### Skin and Body Protection:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

### Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 9. Physical and chemical properties

### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	No data available.
<b>Color:</b>	Black
<b>Odor:</b>	Mild petroleum/solvent
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	240.56 °C (465.01 °F)
<b>Evaporation rate:</b>	No data available.
<b>Flammability (solid, gas):</b>	No data available.
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Relative density:</b>	1.004
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	> 22 mm <sup>2</sup> /s (40 °C, Measured)

## 10. Stability and reactivity

<b>Reactivity:</b>	Not reactive during normal use.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	None under normal conditions.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	No data available.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## Hazardous Decomposition Products:

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

**Ingestion:** May be ingested by accident. Ingestion may cause irritation and malaise.

**Inhalation:** Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.

**Skin Contact:** Prolonged skin contact may cause redness and irritation.

**Eye contact:** Eye contact is possible and should be avoided.

### Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

##### Oral

**Product:** ATEmix (): > 5000 mg/kg

##### Dermal

**Product:** ATEmix (): 2000 - 5000 mg/kg

##### Inhalation

**Product:** Not classified for acute toxicity based on available data.

##### Repeated dose toxicity

**Product:** No data available.

##### Skin Corrosion/Irritation

**Product:** No data available.

##### Serious Eye Damage/Eye Irritation

**Product:** No data available.

##### Respiratory or Skin Sensitization

**Product:** No data available.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## Carcinogenicity

**Product:** No data available.

### **IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

### **US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

## Germ Cell Mutagenicity

### **In vitro**

**Product:** No data available.

### **In vivo**

**Product:** No data available.

## Reproductive toxicity

**Product:** No data available.

## Specific Target Organ Toxicity - Single Exposure

**Product:** No data available.

## Specific Target Organ Toxicity - Repeated Exposure

**Product:** No data available.

## Aspiration Hazard

**Product:** No data available.

**Other effects:** No data available.

## 12. Ecological information

**General information:** This product has not been evaluated for ecological toxicity or other environmental effects.

## 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for





LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

recycling or disposal.

## 14. Transport information

### DOT

Not regulated.

### IMDG

Not regulated.

### IATA

Not regulated.

## 15. Regulatory information

### US Federal Regulations

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### Hazard categories

Delayed (Chronic) Health Hazard

##### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

### US State Regulations

#### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## 16. Other information, including date of preparation or last revision

**Issue Date:** 03.02.2017

**Revision Date:** 03.02.2017

**Version #:** 1.1

**Further Information:** No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.