



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 1. Identification

**Product name** HYKOGREEN AL 2543 C

**Other means of identification** No data available.

**Recommended use:** Metalworking fluid

**Restrictions on use:** Industrial use only

### Manufacturer/Importer/Supplier/Distributor Information

#### Manufacturer

Company Name: Fuchs Lubricants Co.  
Address: 17050 Lathrop Avenue  
Harvey, Illinois 60426  
Telephone: 708-333-8900  
Fax: 708-333-9180

Contact Person: EHS Department  
E-mail: sds@fuchsus.com

**Emergency telephone number:** 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 2
Toxic to reproduction	Category 2

### Label Elements

#### Hazard Symbol:



**Signal Word:** Danger



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Hazard Statement:** Causes skin irritation.  
Causes serious eye irritation.  
May cause an allergic skin reaction.  
May cause genetic defects.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.

## Precautionary Statements

**Prevention:** Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.

**Response:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. Collect spillage.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

## Unknown toxicity - Health

Acute toxicity, oral	9.99 %
Acute toxicity, dermal	19.73 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	99.83 %

## 3. Composition/information on ingredients

### Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Polyisobutylene	Confidential	20 - 50%
Stannous compound	Confidential	20 - 50%



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

Graphite	7782-42-5	10 - 20%
Asphalt, non-oxidized	8052-42-4	10 - 20%
Chlorinated paraffin	Confidential	5 - 10%
Naphtha (petroleum), hydrotreated heavy	64742-48-9	5 - 10%
Zinc compound	Confidential	1 - 5%
Mineral oil	Confidential	1 - 5%
Phosphoric acid	7664-38-2	0.1 - 1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

## 4. First-aid measures

<b>Ingestion:</b>	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
<b>Inhalation:</b>	Call a POISON CENTER/doctor/.../if you feel unwell. Move to fresh air.
<b>Skin Contact:</b>	If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
<b>Eye contact:</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

### Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

## 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Water spray, fog, CO<sub>2</sub>, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## Special protective equipment and precautions for firefighters

### Special fire fighting procedures:

No data available.

### Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

### Methods and material for containment and cleaning up:

Absorb spill with an inert material, then place in a container for safe and proper disposal. Dike far ahead of larger spill for later recovery and disposal.

### Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

### Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Avoid contact with molten material. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly closed. Store locked up. Store in a well-ventilated place.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 8. Exposure controls/personal protection

### Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Stannous compound - as Sn	STEL	0.2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Stannous compound - as Sn	PEL	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Graphite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Asphalt, non-oxidized - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Naphtha (petroleum), hydrotreated heavy	PEL	100 ppm 400 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral oil - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Mineral oil - Mist.	STEL	10 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Phosphoric acid	TWA	1 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Phosphoric acid	STEL	3 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)
Phosphoric acid	PEL	1 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

### Protective Measures:

Provide easy access to water supply and eye wash facilities. Good general ventilation should be provided. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

### Eye Protection:

Wear safety glasses with side shields (or goggles).

### Skin and Body Protection:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

### Hygiene measures:

Always observe good personal hygiene measures, such as washing after



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

handling the material and before eating, drinking, and/or smoking. Contaminated work clothing should be laundered prior to re-use. Discard contaminated footwear that cannot be cleaned. Avoid contact with skin, eyes, and clothing.

## 9. Physical and chemical properties

### Appearance

**Physical state:**

Liquid

**Form:**

No data available.

**Color:**

Brown

**Odor:**

Mild petroleum

**Odor threshold:**

No data available.

**pH:**

No data available.

**Melting point/freezing point:**

No data available.

**Initial boiling point and boiling range:**

No data available.

**Flash Point:**

168 °C (334 °F)

**Evaporation rate:**

No data available.

**Flammability (solid, gas):**

No data available.

**Upper/lower limit on flammability or explosive limits**

**Flammability limit - upper (%):**

No data available.

**Flammability limit - lower (%):**

No data available.

**Explosive limit - upper (%):**

No data available.

**Explosive limit - lower (%):**

No data available.

**Vapor pressure:**

No data available.

**Vapor density:**

No data available.

**Relative density:**

1.1

**Solubility(ies)**

**Solubility in water:**

Insoluble

**Solubility (other):**

No data available.

**Partition coefficient (n-octanol/water):**

No data available.

**Auto-ignition temperature:**

No data available.

**Decomposition temperature:**

No data available.

**Viscosity:**

> 22 mm<sup>2</sup>/s (40 °C, Measured)

## 10. Stability and reactivity

**Reactivity:**

Not reactive during normal use.

**Chemical Stability:**

Material is stable under normal conditions.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

<b>Possibility of hazardous reactions:</b>	None under normal conditions.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	No data available.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion:</b>	May irritate and cause malaise.
<b>Inhalation:</b>	May cause irritation to the respiratory system.
<b>Skin Contact:</b>	Causes skin irritation.
<b>Eye contact:</b>	Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Ingestion:</b>	No data available.
<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

<b>Oral</b>	
<b>Product:</b>	ATEmix (): 2000 - 5000 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix (): 2000 - 5000 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	Not classified for acute toxicity based on available data.
<b>Repeated dose toxicity</b>	
<b>Product:</b>	No data available.

<b>Skin Corrosion/Irritation</b>	
<b>Product:</b>	No data available.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## Serious Eye Damage/Eye Irritation

**Product:** No data available.

## Respiratory or Skin Sensitization

**Product:** No data available.

## Carcinogenicity

**Product:** No data available.

### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Asphalt, Asphalt, Overall evaluation: 2B. Possibly carcinogenic to humans.  
non-oxidized

### US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

## Germ Cell Mutagenicity

### In vitro

**Product:** No data available.

### In vivo

**Product:** No data available.

## Reproductive toxicity

**Product:** No data available.

## Specific Target Organ Toxicity - Single Exposure

**Product:** No data available.

## Specific Target Organ Toxicity - Repeated Exposure

**Product:** No data available.

## Aspiration Hazard

**Product:** No data available.

**Other effects:** No data available.

## 12. Ecological information

### General information:

This product has not been evaluated for ecological toxicity or other environmental effects.





LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 13. Disposal considerations

### Disposal instructions:

Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

### Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

Not regulated.

### IMDG

Not regulated.

### IATA

Not regulated.

## 15. Regulatory information

### US Federal Regulations

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### Hazard categories

Immediate (Acute) Health Hazards

Delayed (Chronic) Health Hazard

##### SARA 313 (TRI Reporting)

##### Chemical Identity

##### Chemical Identity

Zinc compound

##### Reporting threshold for other users

##### Reporting threshold for other users

10000 lbs

##### Reporting threshold for manufacturing and processing

##### Reporting threshold for manufacturing and processing

25000 lbs.

### US State Regulations



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

### 16. Other information, including date of preparation or last revision

**Issue Date:** 18.10.2016

**Revision Date:** 18.10.2016

**Version #:** 1.1

**Further Information:** No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.