

# **SAFETY DATA SHEET**

## 1. Identification

**Product name** LBF ALLCURVE

Other means of identification No data available.

Recommended use: Grease

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co. Address: 17050 Lathrop Avenue Harvey, Illinois 60426

708-333-8900

Telephone: 708-333-9180 Fax:

Contact Person: **EHS** Department E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A

#### **Label Elements**

## **Hazard Symbol:**



Signal Word: Warning

SDS\_US 1/9



**Hazard Statement:** Causes skin irritation.

Causes serious eye irritation.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/protective

clothing/eye protection/face protection.

**Response:** IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Specific treatment (see in product SDS). Take off contaminated clothing.

Other hazards which do not result in GHS classification:

None.

**Unknown toxicity - Health** 

Acute toxicity, oral 51.67 %
Acute toxicity, dermal 16.32 %
Acute toxicity, inhalation, vapor 99.16 %
Acute toxicity, inhalation, dust 88.99 %

or mist

#### 3. Composition/information on ingredients

**Hazardous Component(s):** 

Chemical name	CAS-No.	Concentration
Mineral oil	Confidential	20 - <50%
Mineral oil	Confidential	25 - <50%
Dodecylbenzene calcium sulfonate	Confidential	10 - <20%
Magnesium silicate	14807-96-6	1 - <5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

#### 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

SDS\_US 2/9



Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fireextinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and

disposal.

**Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so.

SDS\_US 3/9



#### 7. Handling and storage

**Precautions for safe handling:** Observe good industrial hygiene practices. Wear appropriate personal

protective equipment. Do not expose to intense heat as product may expand and pressurize container. Wash hands thoroughly after handling.

Avoid contact with skin and eyes.

Conditions for safe storage,

including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing

agents. Store away from incompatible materials.

# 8. Exposure controls/personal protection

**Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Mineral oil	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesium silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Magnesium silicate	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

**Protective Measures:** Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

SDS\_US 4/9



## 9. Physical and chemical properties

**Appearance** 

Physical state: solid
Form: Grease
Color: Black
Odor: Mild

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:520 °C (968 °F)Evaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

Relative density: 1.01

Solubility(ies)

Solubility in water: Insoluble

Solubility (other):

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

No data available.

No data available.

No data available.

No data available.

## 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

SDS\_US 5/9



**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

## 11. Toxicological information

Information on likely routes of exposure

**Ingestion:** May be harmful if swallowed.

**Inhalation:** None under normal conditions. This product contains a low concentration of

hydrated magnesium silicate (Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix (grease). As a consequence, exposure to

airborne Talc particles/dusts is not anticipated.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): > 5000 mg/kg

Dermal

**Product:** ATEmix (): 2000 - 5000 mg/kg

Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

SDS\_US 6/9



**Product:** No data available.

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** This product contains a low concentration of hydrated magnesium silicate

(Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix

(grease). As a consequence, exposure to airborne Talc particles/dusts is not

anticipated.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Magnesium silicate Overall evaluation: 1. Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

SDS\_US 7/9



12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

## 14. Transport information

DOT

Not regulated.

**IMDG** 

Not regulated.

**IATA** 

Not regulated.

#### 15. Regulatory information

## **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Crystalline silica kidney effects lung effects

immune system effects

Cancer

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Immediate (Acute) Health Hazards Skin Corrosion or Irritation Serious eye damage or eye irritation

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

SDS\_US 8/9



#### **US State Regulations**

## **US. California Proposition 65**



This product can expose you to chemicals including Magnesium silicate Crystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

# 16.Other information, including date of preparation or last revision

**Issue Date:** 29.06.2021

**Revision Date:** 29.06.2021

Version #: 1.1

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS\_US 9/9