

SAFETY DATA SHEET

1. Identification

Product nameLBF DURACURVE C2 SUMMEROther means of identificationNo data available.Recommended use:Lubricating greaseRestrictions on use:Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
Telephone: Fax:	Harvey, Illinois 60426 708-333-8900 708-333-9180
Contact Person:	EHS Department
E-mail:	sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Not classified as hazardous under GHS

Label Elements

Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement:	Not applicable
Precautionary Statements	Not applicable

None.

Other hazards which do not result in GHS classification:



3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Distillates (petroleum), hydrotreated heavy	64742-52-5	25 - <50%
naphthenic		
Magnesium silicate	14807-96-6	1 - <5%
Graphite	7782-42-5	1 - <5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures	
Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.
Most important symptoms/effe	cts, acute and delayed
Symptoms:	No data available.
Indication of immediate medical	attention and special treatment needed
Treatment:	Get medical attention if symptoms occur.
5. Fire-fighting measures	
General Fire Hazards:	No unusual fire or explosion hazards noted.
Suitable (and unsuitable) exting	guishing media
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.
Special protective equipment a	and precautions for fire-fighters

Special protective equipment and precautions for fire-fighters



Special fire-fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
6. Accidental release measures	S
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.
Methods and material for containment and cleaning up:	Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.
Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Distillates (petroleum), hydrotreated heavy naphthenic - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesium silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Magnesium silicate	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Magnesium silicate - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)

Protective Measures:	Use personal protective equipment as required.
----------------------	--

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties



Appearance

Physical state: Form: Color: Odor: Odor threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash Point: **Evaporation rate:** Flammability (solid, gas): Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): Flammability limit - lower (%): **Explosive limit - upper: Explosive limit - lower:** Vapor pressure: Vapor density: **Relative density:** Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water): Auto-ignition temperature: **Decomposition temperature:** Viscosity:

solid Grease Black Mild Not available. No data available. 248 °C (478 °F) No data available. No data available.

No data available. No data available. No data available. No data available. Not available. No data available. No data available. 1.01

Insoluble No data available. No data available. No data available. No data available. Not available. No data available.

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



11. Toxicological information

Information on likely routes of exposure Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise. Inhalation: None under normal conditions. This product contains a low concentration of hydrated magnesium silicate (Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix (grease). As a consequence, exposure to airborne Talc particles/dusts is not anticipated. **Skin Contact:** Prolonged skin contact may cause redness and irritation. Eye contact: Eye contact is possible and should be avoided. Symptoms related to the physical, chemical and toxicological characteristics No data available. Ingestion: Inhalation: No data available. **Skin Contact:** No data available. Eye contact: No data available. Information on toxicological effects Acute toxicity (list all possible routes of exposure) Oral Product: ATEmix (): > 5000 mg/kg Dermal **Product:** ATEmix (): 2000 - 5000 mg/kg Inhalation Product: No data available. Repeated dose toxicity Product: No data available. Skin Corrosion/Irritation Product: No data available.

Serious Eye Damage/Eye Irritation Product: No data available.

Respiratory or Skin Sensitization Product: No data available.



This product contains a low concentration of hydrated magnesium silicate (Talc). Under the International Agency for Research on Cancer (IARC), Talc in powder form is classified as Group 1: Carcinogenic to Humans. This is based on exposure through inhalation and perineal dusting with talc-based body powders. For this product, Talc is bound in the product's matrix

(grease). As a consequence, exposure to airborne Talc particles/dusts is not

In vitro No data available. **Product:** In vivo **Product:** No data available. Reproductive toxicity **Product:** No data available. Specific Target Organ Toxicity - Single Exposure **Product:** No data available. Specific Target Organ Toxicity - Repeated Exposure No data available. Product: Aspiration Hazard **Product:** No data available. Other effects: No data available.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

anticipated.

US. National Toxicology Program (NTP) Report on Carcinogens:

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

12. Ecological information

Germ Cell Mutagenicity

Carcinogenicity Product:

Magnesium silicate

No carcinogenic components identified

No carcinogenic components identified

General information:	This product has not been evaluated for ecological toxicity or other environmental effects.

13. Disposal considerations



Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not Regulated.

IMDG

Not Regulated.

ΙΑΤΑ

Not Regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Crystalline silica kidr

kidney effects lung effects immune system effects Cancer

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Not classified as hazardous under GHS

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



This product can expose you to chemicals includingMagnesium silicateCrystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.



16.Other information, including date of preparation or last revision	
Issue Date:	07.02.2025
Revision Date:	29.06.2021
Version #:	1.2
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.