

SAFETY DATA SHEET

1. Identification

Product name LUBRODAL A 9039 N M1

Other means of identification No data available.

Recommended use: For Performance Evaluation Only

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426

Telephone: 708-333-8900 Fax: 708-333-9180

Contact Person: EHS Department sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin sensitizer Category 1
Toxic to reproduction Category 1B
Aspiration Hazard Category 1

Label Elements

Hazard Symbol:



Signal Word: Danger

SDS_US 1/10



Hazard Statement: May cause an allergic skin reaction.

May damage fertility or the unborn child. May be fatal if swallowed and enters airways.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Avoid breathing

dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/ protective clothing/ eye protection/ face protection. Use personal protective equipment as

required.

Response: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT

induce vomiting. IF ON SKIN: Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF exposed or concerned: Get medical

advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.

Other hazards which do not result in GHS classification:

None.

Unknown toxicity - Health

Acute toxicity, oral 17.25 %
Acute toxicity, dermal 17.58 %
Acute toxicity, inhalation, vapor 36.31 %
Acute toxicity, inhalation, dust 30.32 %

or mist

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration	
White mineral oil	8042-47-5	50 - <100%	
Graphite	7782-42-5	1 - <5%	
Stannous compound	Confidential	1 - <5%	
Hexanoic acid, 2-ethyl-, bismuth(3+) salt (3:1)	67874-71-9	1 - <5%	
Sulfur	7704-34-9	1 - <5%	
2-Ethylhexanoic acid	149-57-5	0.3 - <1%	

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

SDS_US 2/10



4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so

that stomach content doesn't get into the lungs.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: If burned by contact with hot material, cool molten material adhering to skin

as quickly as possible with water, and see a physician for removal of adhering material and treatment of burn. Immediately remove contaminated

clothing and shoes and wash skin with soap and plenty of water.

Eye contact: Flush thoroughly with water. If irritation occurs, get medical assistance.

Continue to rinse for at least 15 minutes.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

SDS_US 3/10



Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning up:

Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

Environmental Precautions:

Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Avoid contact with molten material. Contains a component that when heated at or above 300F (150C) may generate Formaldehyde vapors. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities:

Store locked up.

SDS US 4/10



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
White mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
White mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Stannous compound - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Stannous compound - as Sn	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Stannous compound - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2019)
Stannous compound - Inhalable fraction as Sn	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2019)
Stannous compound - as Sn	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2019)
Stannous compound - as Sn	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Stannous compound - as Sn	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)

Protective Measures: Use personal protective equipment as required.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

SDS_US 5/10



Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state:liquidForm:liquid

Color: Dark brown

Odor: Mild

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:140 °C (284 °F)Evaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Decomposition temperature:
No data available.
Viscosity:
< 20.5 mm2/s (40 °C)

Other information

VOC: 26.59 g/l (ASTM E 1868-10)

10. Stability and reactivity

Reactivity: Not reactive during normal use.

SDS_US 6/10



Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Products:

formaldehyde

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation: Harmful if inhaled.

Skin Contact: May cause an allergic skin reaction.

Eye contact: Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix (): > 5000 mg/kg

Dermal

Product: ATEmix (): 2000 - 5000 mg/kg

Inhalation

Product: No data available.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

SDS_US 7/10



Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

No carcinogenic components identified US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

SDS_US 8/10



Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for

recycling or disposal.

14. Transport information

DOT

Not Regulated.

IMDG

Not Regulated.

IATA

Not Regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Crystalline silica kidney effects

lung effects

immune system effects

Cancer

Crystalline silica kidney effects

lung effects

immune system effects

Cancer

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Respiratory or Skin Sensitization Reproductive toxicity Aspiration Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

SDS_US 9/10



US. California Proposition 65



This product can expose you to chemicals includingPetroleum resinsCrystalline silicaCrystalline silicaTremolitewhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision

Issue Date: 05.08.2025

Revision Date: 04.08.2025

Version #: 1.4

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS_US 10/10