

SAFETY DATA SHEET

1. Identification

Product name LUBRODAL C AM

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co. Address: 17050 Lathrop Avenue Harvey, Illinois 60426

708-333-8900 Telephone: Fax: 708-333-9180

Contact Person: **EHS** Department E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Category 1A Carcinogenicity

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: May cause cancer.

SDS_US 1/10



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

Unknown toxicity - Health

Acute toxicity, oral 5.9 %
Acute toxicity, dermal 6.58 %
Acute toxicity, inhalation, vapor 32.06 %
Acute toxicity, inhalation, dust 31.91 %

or mist

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Graphite	7782-42-5	20 - <50%
Sodium silicate	Confidential	1 - <5%
Crystalline silica	14808-60-7	0.1 - <1%
Magnesium oxide (MgO)	1309-48-4	0.1 - <1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures

Ingestion: Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Flush thoroughly with water. If irritation occurs, get medical assistance.

Continue to rinse for at least 15 minutes.

SDS US 2/10



Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-

extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame

retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and

emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate

ventilation.

Methods and material for containment and cleaning

up:

Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

Environmental Precautions: Avoid release to the environment. Do not contaminate water sources or

sewer. Prevent further leakage or spillage if safe to do so.

SDS US 3/10



7. Handling and storage

Precautions for safe handling: End-users should follow industry best practices for handling and using this

product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Do not handle until all safety precautions have been read and understood. Obtain special instructions

before use. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities:

Store locked up.

SDS_US 4/10



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline silica - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Crystalline silica - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline silica - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline silica - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Magnesium oxide (MgO) - Total particulate.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Magnesium oxide (MgO) - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Magnesium oxide (MgO) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Magnesium oxide (MgO) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Magnesium oxide (MgO) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Magnesium oxide (MgO) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)

Protective Measures: Use personal protective equipment as required.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

SDS_US 5/10



9. Physical and chemical properties

Appearance

Physical state: liquid

Form: No data available.

Color: Gray
Odor: Mild

Odor threshold: No data available.

pH: 11

Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:not applicableEvaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

Vapor density:

No data available.

No data available.

No data available.

No data available.

Relative density: 1.3

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Decomposition temperature:
No data available.
Viscosity:
22 mm2/s (40 °C)

10. Stability and reactivity

Reactivity: Not reactive during normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

SDS US 6/10



Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors. formaldehyde

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation: May be harmful if inhaled.

Skin Contact: Prolonged skin contact may cause redness and irritation.

Eye contact: Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix (): > 5000 mg/kg

Dermal

Product: ATEmix (): > 5000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

SDS_US 7/10



Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline silica Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

Crystalline silica

Cancer

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

SDS_US 8/10



Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for

recycling or disposal.

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Crystalline silica kidney effects

lung effects

immune system effects

Cancer

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard Carcinogenicity

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

SDS_US 9/10



US. California Proposition 65



This product can expose you to chemicals includingCrystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision

Issue Date: 22.07.2020

Revision Date: 22.07.2020

Version #: 1.1

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS_US 10/10