

SAFETY DATA SHEET

1. Identification

Product name LUBRODAL F 3962

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co. Address: 17050 Lathrop Avenue Harvey, Illinois 60426

Telephone: 708-333-8900 Fax: 708-333-9180

Contact Person: EHS Department sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Not classified as hazardous under GHS

Label Elements

Hazard Symbol: No symbol

Signal Word: No signal word.

Hazard Statement: Not applicable

Precautionary Statements Not applicable

Other hazards which do not result in GHS classification:

None.

SDS_US 1/9



3. Composition/information on ingredients

Hazardous Component(s):

| Chemical name | CAS-No. | Concentration | | |
|-------------------|--------------|---------------|--|--|
| Graphite | 7782-42-5 | 10 - 20% | | |
| Sodium silicate | Confidential | 1 - 5% | | |
| Aluminum silicate | Confidential | 1 - 5% | | |
| Triazine compound | Confidential | 0.1 - 1% | | |

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures

Ingestion: Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Flush thoroughly with water. If irritation occurs, get medical assistance.

Continue to rinse for at least 15 minutes.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use water fog, alcohol-resistant foam, dry chemical or carbon dioxide (CO2) to extinguish flames. Use fire-extinguishing media appropriate for

surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for firefighters

SDS US 2/9



Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate

Methods and material for containment and cleaning

Environmental Precautions:

up:

Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.

Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.

ventilation.

7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Contains a component that when heated at or above 300F (150C) may generate Formaldehyde vapors. Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.

Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing

agents. Store away from incompatible materials.

SDS_US 3/9



8. Exposure controls/personal protection

Exposure Limits

| Chemical name | Туре | Exposure Limit Values | Source |
|--|------|--|---|
| Graphite - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values, as amended (03 2012) |
| Graphite - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |
| Graphite - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |
| Graphite | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000) |
| Aluminum silicate - Respirable fraction. | TWA | 2 mg/m3 | US. ACGIH Threshold Limit Values, as amended (03 2012) |
| Aluminum silicate - Respirable fraction. | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |
| Aluminum silicate - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006) |
| Aluminum silicate - Total dust. | TWA | 15 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989) |
| Aluminum silicate - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989) |
| Aluminum silicate - Total dust. | TWA | 50 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016) |
| Aluminum silicate - Respirable fraction. | TWA | 15 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016) |
| Aluminum silicate - Respirable fraction. | TWA | 5 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016) |
| Aluminum silicate - Total dust. | TWA | 15 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016) |

Protective Measures: Use personal protective equipment as required.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

Eye Protection: Wear safety glasses with side shields (or goggles).

Skin and Body Protection: Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

SDS_US 4/9



9. Physical and chemical properties

Appearance

Physical state: liquid

Form: No data available.

Color: Gray
Odor: Mild

Odor threshold: No data available.

pH: 11.3

Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:Not applicableEvaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

Vapor density:

No data available.

Relative density: 1.08

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
Auto-ignition temperature:
No data available.
Decomposition temperature:
No data available.
Viscosity:
No data available.

Other information

VOC: 0.01 g/l (ASTM E 1868-10)

10. Stability and reactivity

Reactivity: Not reactive during normal use.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

Conditions to avoid: Avoid heat or contamination.

SDS_US 5/9



Incompatible Materials: No data available.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors. formaldehyde

11. Toxicological information

Information on likely routes of exposure

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation: Inhalation is the primary route of exposure. In high concentrations, vapors,

fumes or mists may irritate nose, throat and mucus membranes.

Skin Contact: Prolonged skin contact may cause redness and irritation.

Eye contact: Eye contact is possible and should be avoided.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix (): > 5000 mg/kg

Dermal

Product: ATEmix (): > 5000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

SDS_US 6/9



Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

No data available. **Product:**

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure No data available. **Product:**

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for

SDS_US 7/9



recycling or disposal.

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Not classified as hazardous under GHS

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



This product can expose you to chemicals includingCrystalline silicaCristobaliteTitanium dioxideCrystalline silicawhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision

Issue Date: 12.02.2020

Revision Date: 12.02.2020

Version #: 1.6

Further Information: No data available.

SDS_US 8/9



Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS_US 9/9