

SAFETY DATA SHEET

1. Identification of the hazardous chemical and of the supplier

Product identifier: LUBRODAL FC 336 S

Other means of identification: No data available.

Recommended use of the chemical and restrictions on use

Recommended use: Metalworking fluid

Recommended restrictions: Industrial use only

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426
Telephone: 708-333-8900
Fax: 708-333-9180

Contact Person: EHS Department
E-mail: sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation Category 1

Serious Eye Damage/Eye Irritation Category 1

Unknown toxicity - Health

Acute toxicity, oral 2.93 %

Acute toxicity, dermal 3.37 %

Acute toxicity, inhalation, vapor 26.36 %

Acute toxicity, inhalation, dust
or mist 26.16 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	H314: Causes severe skin burns and eye damage.
Precautionary Statements	
Prevention:	P260: Do not breathe dust/fume/gas/mist/vapors/spray. P264: Wash face, hands and any exposed skin thoroughly after handling. P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:	P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P363: Wash contaminated clothing before reuse. P321: Specific treatment (see supplemental first aid instructions on this label). P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310: Immediately call a POISON CENTER or doctor/ physician. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Storage:	P405: Store locked up.
Disposal:	P501: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Graphite	7782-42-5	15 - 40%
Silicic acid, sodium salt	1344-09-8	5 - 10%
Ammonia	7664-41-7	0.1 - 1%
Triazine compound	4719-04-4	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact: Wash contaminated clothing before reuse. Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.

Ingestion: Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.
For non-emergency personnel:	No data available.
For emergency responders:	No data available.
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:	<p>End-users should follow industry best practices for handling and using this product.</p> <p>Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Wash hands thoroughly after handling. Do not get in eyes, on skin, on clothing. Use caution when adding this material to water. Add material slowly when mixing with water. Do not add water to the material; instead, add the material to the water. Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines.</p>
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Graphite - Respirable fraction.	VLE-PPT	2 mg/m3	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
Ammonia	VLE-PPT	25 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)
	VLE-CT	35 ppm	Mexico. OELs. (NOM-010-STPS-2014 Chemical Pollutants at the Workplace; Assessment and Control), as amended (04 2014)

Appropriate Engineering Controls No data available.

Individual protection measures, such as personal protective equipment

General information: Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Eye/face protection: Wear safety glasses with side shields (or goggles).

**Skin Protection
Hand Protection:** No data available.

Other: Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

Hygiene measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Black

Odor: Characteristic

Odor threshold: No data available.

pH: 11.95

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: no data available

Evaporation rate: No data available.

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

Flammability limit - lower (%): No data available.

Explosive limit - upper: No data available.

Explosive limit - lower: No data available.

Vapor pressure: No data available.

Vapor density:	No data available.
Density:	No data available.
Relative density:	1.158 (15 °C)
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	> 21 mm ² /s (40 °C)

Other information

VOC: 141.82 g/l 70.91 g/l

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix (): > 5000 mg/kg

Dermal

Product: ATEmix (): > 5000 mg/kg

Inhalation

Product: No data available.

Specified substance(s):

Graphite LC 50 (Rat): > 2,000 mg/m³

Ammonia
 LC 50 (Rat): 28,130 mg/m³
 LC 50 (Rat): 18,693 mg/m³
 LC 50 (Rat): 11,590 mg/m³
 LC 50 (Rat): 13,770 mg/m³
 LC 50 (Rat): 14,170 mg/m³
 LC 50: 11 mg/l
 LC 50 (Rabbit): 7,050 mg/m³
 LC 50 (Rat): 5.131 mg/l
 LC 50 (Rat): 7,939 mg/m³
 LC 50 (Rat): 9,850 mg/m³
 LC 50 (Rat): 19,960 mg/m³
 LC 50 (Rat): 7,035 mg/m³
 LC 50 (Rat): 11,342 mg/m³

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Graphite in vivo (Rabbit): Not irritant , 24 - 72 h Experimental result, Key study
 In vitro (In vitro): Not irritant , 3 min Experimental result, Supporting study
 Triazine compound in vivo (Rabbit): Not irritant , 24 - 72 h Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: No data available.

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects:

pneumoconiosis eye damage Upper Respiratory Tract irritation Lung cancer pulmonary fibrosis Skin irritation Eye irritation Larynx metaplasia

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Graphite LC 50 (Fish, 96 h): > 100 mg/l

Silicic acid, sodium salt
LC 50 (Western mosquitofish (*Gambusia affinis*), 24 h): 3,200 mg/l Mortality
LC 50 (Western mosquitofish (*Gambusia affinis*), 48 h): 2,400 mg/l Mortality
LC 50 (Western mosquitofish (*Gambusia affinis*), 96 h): 1,800 mg/l Mortality

Ammonia
LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 48 h): 0.37 mg/l Mortality
LC 50 (Carp (*Hypophthalmichthys nobilis*), 48 h): 0.4 mg/l Mortality

Triazine compound LC 50 (Fish, 96 h): 10 - 100 mg/l

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Graphite	EC50 (Daphnia, 48 h): > 100 mg/l
Silicic acid, sodium salt	LC 50 (Water flea (Daphnia magna), 24 h): 247 mg/l Mortality LC 50 (Water flea (Daphnia magna), 96 h): 216 mg/l Mortality
Triazine compound	EC50 (Daphnia, 48 h): 10 - 100 mg/l

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Specified substance(s):

Graphite	EC50 (Algae (Pseudokirchneriella subcapitata), 72 h): > 100 mg/l
----------	--

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Ammonia	Log Kow: -2.66
---------	----------------

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Graphite	No data available.
Silicic acid, sodium salt	No data available.
Ammonia	No data available.
Triazine compound	No data available.

Not applicable

16. Other information, including date of preparation or last revision
--

Issue Date: 02/16/2026

Revision Information: 02/16/2026: ARGHS_MX

Version #: 1.1

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.