

# **SAFETY DATA SHEET**

# 1. Identification

Product name LUBRODAL F 645 HD

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426

700 222 0000

Telephone: 708-333-8900 Fax: 708-333-9180

Contact Person: EHS Department sds@fuchs.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

# 2. Hazard(s) identification

#### **Hazard Classification**

## **Health Hazards**

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A

#### **Label Elements**

# **Hazard Symbol:**



Signal Word: Warning

SDS\_US 1/9



**Hazard Statement:** Causes skin irritation.

Causes serious eye irritation.

Precautionary Statements

**Prevention:** Wash face, hands and any exposed skin thoroughly after handling. Wear

protective gloves/protective clothing/eye protection/face protection.

**Response:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs:

Get medical advice/attention. Take off contaminated clothing. Specific treatment (see supplemental first aid instructions on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Other hazards which do not result in GHS classification:

None.

#### **Unknown toxicity - Health**

Acute toxicity, oral 3.44 %
Acute toxicity, dermal 3.82 %
Acute toxicity, inhalation, vapor 19.33 %
Acute toxicity, inhalation, dust or mist

## 3. Composition/information on ingredients

#### **Hazardous Component(s):**

Chemical name	CAS-No.	Concentration	
Graphite	7782-42-5	10 - <25%	
Silicic acid, sodium salt	Confidential	1 - <3%	
Aluminum silicate	Confidential	0.25 - <1%	
1,3,5-Triazine-1,3,5(2H,4H,6H)-triethanol	4719-04-4	0.1 - <1%	

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

# 4. First-aid measures

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation: Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

SDS US 2/9



**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Methods and material for containment and cleaning

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

SDS US 3/9



# 7. Handling and storage

Precautions for safe handling: End-users should follow industry best practices for handling and using this

product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not get in eyes and avoid contact with skin and clothing.

Conditions for safe storage, including any incompatibilities:

Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

## 8. Exposure controls/personal protection

**Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Aluminum silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2012)
Aluminum silicate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum silicate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Aluminum silicate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Aluminum silicate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Aluminum silicate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum silicate - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum silicate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Aluminum silicate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)

**Protective Measures:** 

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates

SDS\_US 4/9



should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear

that cannot be cleaned.

# 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: No data available.

Color: Black
Odor: Mild

Odor threshold: No data available.

**pH:** 11.0

Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:Not applicableEvaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

Relative density: 1.107

Solubility(ies)

Solubility in water:Miscible with water.Solubility (other):No data available.Partition coefficient (n-octanol/water):No data available.

SDS\_US 5/9



Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:> 2 mm2/s (40 °C)

# 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure

**Ingestion:** May be harmful if swallowed.

**Inhalation:** Spray mist may irritate the respiratory system. Harmful if inhaled.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): > 5000 mg/kg

Dermal

**Product:** ATEmix (): > 5000 mg/kg

SDS US 6/9



Inhalation

**Product:** No data available.

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Respiratory or Skin Sensitization

**Product:** No data available.

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

SDS\_US 7/9



# 12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other

environmental effects.

# 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

# 14. Transport information

DOT

Not regulated.

**IMDG** 

Not regulated.

**IATA** 

Not regulated.

# 15. Regulatory information

# **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

None present or none present in regulated quantities.

Crystalline silica kidney effects

lung effects

immune system effects

Cancer

Cristobalite kidney effects

Cancer

immune system effects

lung effects

Tridymite lung effects

Cancer

immune system effects

kidney effects

SDS US 8/9



## Superfund Amendments and Reauthorization Act of 1986 (SARA)

# **Hazard categories**

Immediate (Acute) Health Hazards Skin Corrosion or Irritation Serious eye damage or eye irritation

## SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

## **US State Regulations**

## **US. California Proposition 65**



This product can expose you to chemicals including Crystalline silica Cristobalite Tridymite Formaldehydewhich is [are] known to the State of California to cause cancer.

Methanolwhich is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

# 16.Other information, including date of preparation or last revision

Issue Date: 03.05.2023

**Revision Date:** 03.05.2023

Version #: 1.6

Further Information: No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS US 9/9