



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

1. Identification

Product name LUBRODAL W 775 MG

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426
Telephone: 708-333-8900
Fax: 708-333-9180

Contact Person: EHS Department
E-mail: sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation Category 1A

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Causes severe skin burns and eye damage.
Toxic to aquatic life.

Precautionary Statements



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

Prevention: Do not breathe dust or mists. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Other hazards which do not result in GHS classification: None.

Unknown toxicity - Health

Acute toxicity, oral	14.26 %
Acute toxicity, dermal	14.28 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	23.64 %

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Molybdenum compound	Confidential	10 - 20%
Inorganic silicate compound	Confidential	5 - 10%
Graphite	7782-42-5	1 - 5%
Sodium hydroxide	1310-73-2	0.1 - 1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. Do not induce vomiting without advice from poison control center.



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

Inhalation: Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.

Skin Contact: Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention. Call a physician or poison control center immediately. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Get medical attention if symptoms occur.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Water spray, fog, CO₂, dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

**Personal precautions,
protective equipment and
emergency procedures:**

See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

**Methods and material for
containment and cleaning
up:**

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.

7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Do not get in eyes, on skin, on clothing. Wash hands thoroughly after handling. Use caution when adding this material to water.

**Conditions for safe storage,
including any
incompatibilities:**

Store locked up.



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

8. Exposure controls/personal protection

Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Molybdenum compound - Inhalable fraction. - as Mo	TWA	10 mg/m ³	US. ACGIH Threshold Limit Values (03 2012)
Molybdenum compound - Respirable fraction. - as Mo	TWA	3 mg/m ³	US. ACGIH Threshold Limit Values (03 2012)
Molybdenum compound - Total dust. - as Mo	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	TWA	2 mg/m ³	US. ACGIH Threshold Limit Values (03 2012)
Graphite - Total dust.	PEL	15 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Sodium hydroxide	PEL	2 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Sodium hydroxide	Ceiling	2 mg/m ³	US. ACGIH Threshold Limit Values (03 2012)

Protective Measures:

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

Eye Protection:

Wear safety glasses with side shields (or goggles).

Skin and Body Protection:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

Appearance

Physical state:	liquid
Form:	No data available.
Color:	Black
Odor:	Mild
Odor threshold:	No data available.
pH:	11.45
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	not applicable
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.24
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	> 22 mm ² /s (40 °C)

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. formaldehyde



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

11. Toxicological information

Information on likely routes of exposure

Ingestion:	Harmful if swallowed.
Inhalation:	Harmful if inhaled.
Skin Contact:	Causes severe skin burns.
Eye contact:	Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion:	No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral	
Product:	ATEmix (): > 5000 mg/kg
Dermal	
Product:	ATEmix (): > 5000 mg/kg
Inhalation	
Product:	Not classified for acute toxicity based on available data.

Repeated dose toxicity	
Product:	No data available.

Skin Corrosion/Irritation	
Product:	No data available.

Serious Eye Damage/Eye Irritation	
Product:	No data available.

Respiratory or Skin Sensitization	
Product:	No data available.

Carcinogenicity	
Product:	No data available.



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

General information: This product has not been evaluated for ecological toxicity or other environmental effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

Contaminated Packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal.



LUBRICANTS.
TECHNOLOGY.
PEOPLE.

SAFETY DATA SHEET

14. Transport information

DOT

Not regulated.

IMDG

Not regulated.

IATA

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

16. Other information, including date of preparation or last revision

Issue Date: 07.01.2017

Revision Date: 07.01.2017

Version #: 1.3

Further Information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.