

SAFETY DATA SHEET

1. Identification

Product name	MONTG DQ 4254 DW 180
Other means of identification	No data available.
Recommended use:	Metalworking fluid
Restrictions on use:	Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
Telephone: Fax:	Harvey, Illinois 60426 708-333-8900 708-333-9180
Contact Person:	EHS Department
E-mail:	sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Inhalation - vapor)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Specific Target Organ Toxicity -	Category 3
Single Exposure	

Label Elements

Hazard Symbol:





Signal Word:	Warnir	ng
Hazard Statement:	Cause: Cause:	ul if inhaled. s skin irritation. s serious eye irritation. ause respiratory irritation.
Precautionary Statements		
Prevention:	well-ve	preathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a entilated area. Wash thoroughly after handling. Wear protective /protective clothing/eye protection/face protection.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/ If skin irritation occurs: Get medical advice/attention. Call a POISON CENTER/doctor/ if you feel unwell. Specific treatment (see this label). Take off contaminated clothing.	
Storage:	Store i up.	n a well-ventilated place. Keep container tightly closed. Store locked
Disposal:	facility	e of contents/container to an appropriate treatment and disposal in accordance with applicable laws and regulations, and product teristics at time of disposal.
Other hazards which do not result in GHS classification:	None.	
Unknown toxicity - Health		
Acute toxicity, oral		51.25 %
Acute toxicity, dermal		51.35 %
Acute toxicity, inhalation,	vapor	97.98 %
Acute toxicity, inhalation, or mist	dust	100 %

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Silicon carbide (SiC)	409-21-2	20 - 50%
Mineral oil	Confidential	20 - 50%
Nonylphenol ethoxylate	Confidential	1 - 3%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.



4. First-aid measures		
Ingestion:	Call a POISON CENTER/doctor/ if you feel unwell. Rinse mouth.	
Inhalation:	Call a POISON CENTER/doctor/ if you feel unwell. Move to fresh air.	
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	No data available.	
Indication of immediate medical attention and special treatment needed		
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) extingu	iishing media	
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment and precautions for firefighters		
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	

6. Accidental release measures



Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	End-users should follow industry best practices for handling and using this product.
	Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not get in eyes. Wash hands thoroughly after handling. Use caution when adding this material to water. Add material slowly when mixing with water. Do not add water to the material; instead, add the material to the water. Avoid contact with skin.
Conditions for safe storage, including any incompatibilities:	Keep container tightly closed. Store locked up. Store in a well-ventilated place.



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Silicon carbide (SiC) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Silicon carbide (SiC) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Silicon carbide (SiC) - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Silicon carbide (SiC) - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Silicon carbide (SiC) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Protective Measures:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties



Appearance

Physical state:	Liquid
Form:	Liquid
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	No data available.
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.25
Solubility(ies)	
Solubility in water:	Soluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	130 mm2/s (40 °C)

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



11. Toxicological information

Information on likely routes of exposure Ingestion: Harmful if swallowed.		
Inhalation:	Harmful if inhaled.	
Skin Contact:	Causes severe skin burns.	
Eye contact:	Causes serious eye damage.	
Symptoms related to the physic Ingestion:	al, chemical and toxicological characteristics No data available.	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Information on toxicological effects		
Acute toxicity (list all possible routes of exposure)		
Oral Product:	ATEmix (): > 5000 mg/kg	
Dermal Product:	ATEmix (): 2000 - 5000 mg/kg	
Inhalation Product:	ATEmix (, 4 h): 10 - 20 mg/l Vapour	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Serious Eye Damage/Eye Irritat Product:	ion No data available.	
Respiratory or Skin Sensitizatio Product:	on No data available.	
Carcinogenicity Product:	No data available.	



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity Product:	- Single Exposure No data available.
Specific Target Organ Toxicity - Repeated Exposure Product:No data available.	
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

12. Ecological information

General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
13. Disposal considerations	
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.



14. Transport information

DOT

Not regulated.

IMDG Not regulated.

ΙΑΤΑ

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Acute toxicity Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Specific Target Organ Toxicity - Single Exposure

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

16.Other information, including date of preparation or last revision	
Issue Date:	18.09.2017
Revision Date:	18.09.2017
Version #:	1.1
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

