

# SAFETY DATA SHEET

## 1. Identification

Product name MONTG DQ4254DW 220/270 UK

Other means of identification No data available.

Recommended use: Metalworking fluid

Restrictions on use: Industrial use only

## Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name: Fuchs Lubricants Co.
Address: 17050 Lathrop Avenue
Harvey, Illinois 60426

700 222 0000

Telephone: 708-333-8900 Fax: 708-333-9180

Contact Person: EHS Department E-mail: sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Acute toxicity (Inhalation - vapor)

Skin Corrosion/Irritation

Category 2

Serious Eye Damage/Eye Irritation

Category 1

Specific Target Organ Toxicity 
Category 3

Single Exposure

#### **Label Elements**

## **Hazard Symbol:**



SDS\_US 1/10



Signal Word: Danger

**Hazard Statement:** Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage. May cause respiratory irritation.

Precautionary Statements

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a

well-ventilated area. Wash thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water/... If skin irritation occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor/... Specific

treatment (see this label). Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked

up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

#### **Unknown toxicity - Health**

Acute toxicity, oral 53.08 %
Acute toxicity, dermal 53.78 %
Acute toxicity, inhalation, vapor 98.57 %
Acute toxicity, inhalation, dust 99.93 %

or mist

#### 3. Composition/information on ingredients

# **Hazardous Component(s):**

Chemical name	CAS-No.	Concentration
Silicon carbide (SiC)	409-21-2	20 - <50%
Mineral oil	Confidential	20 - <50%
Alkyl Sodium Sulfonate	Confidential	1 - <3%
Graphite	7782-42-5	1 - <5%
Nonylphenol ethoxylate	Confidential	1 - <3%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

SDS US 2/10



4. First-aid measures

Ingestion: Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation: Call a POISON CENTRE/doctor/ if you feel unwell. Move to fresh air.

**Skin Contact:** Remove contaminated clothing and shoes. Wash contact areas with soap

and water. If skin irritation occurs: Get medical advice/attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do,

remove contact lenses. Call a physician or poison control center

immediately.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Water spray, fog, CO2, dry chemical, or regular foam. Use fireextinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Heat may cause the containers to explode. During fire, gases hazardous to

health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

## 6. Accidental release measures

SDS US 3/10



Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

**Environmental Precautions:** 

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

# 7. Handling and storage

Precautions for safe handling:

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not get in eyes. Wash hands thoroughly after handling. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed. Store locked up. Store in a well-ventilated place.

SDS US 4/10



#### 8. Exposure controls/personal protection

**Exposure Limits** 

Chemical name	Туре	Exposure Limit Values	Source
Silicon carbide (SiC) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Silicon carbide (SiC) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Silicon carbide (SiC) - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Silicon carbide (SiC) - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Silicon carbide (SiC) - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Silicon carbide (SiC) - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Graphite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Graphite	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

Protective Measures: Provide easy access to water supply and eye wash facilities. Good general

ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

**Respiratory Protection:** In case of inadequate ventilation use suitable respirator. Seek advice from

supervisor on the company's respiratory protection standards.

**Eye Protection:** Wear safety glasses with side shields (or goggles).

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate

for the risk of exposure. Contact health and safety professional or manufacturer

for specific information.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

SDS\_US 5/10



handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

### 9. Physical and chemical properties

**Appearance** 

Physical state: solid
Form: Paste
Color: Black
Odor: Mild

Odor threshold:No data available.pH:No data available.Melting point/freezing point:No data available.Initial boiling point and boiling range:No data available.Flash Point:151.67 °C (305.01 °F)Evaporation rate:No data available.Flammability (solid, gas):No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper (%):

Explosive limit - lower (%):

Vapor pressure:

No data available.

Relative density: 1.000

Solubility(ies)

Solubility in water: Dispersible

Solubility (other):

Partition coefficient (n-octanol/water):

Auto-ignition temperature:

No data available.

No data available.

No data available.

Viscosity:

No data available.

#### 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

None under normal conditions.

SDS US 6/10



**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

### 11. Toxicological information

Information on likely routes of exposure

**Ingestion:** Harmful if swallowed.

**Inhalation:** Harmful if inhaled.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix (): > 5000 mg/kg

**Dermal** 

**Product:** ATEmix (): 2000 - 5000 mg/kg

Inhalation

**Product:** ATEmix (, 4 h): 10 - 20 mg/l Vapour

Repeated dose toxicity

**Product:** No data available.

Skin Corrosion/Irritation

**Product:** No data available.

Serious Eye Damage/Eye Irritation

**Product:** No data available.

**Respiratory or Skin Sensitization** 

SDS\_US 7/10



**Product:** No data available.

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Specific Target Organ Toxicity - Single Exposure
Product:
No data available.

10 data available

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** No data available.

**Aspiration Hazard** 

**Product:** No data available.

Other effects: No data available.

12. Ecological information

**General information:** This product has not been evaluated for ecological toxicity or other

environmental effects.

13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws. Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must

be applied.

SDS US 8/10



**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for

recycling or disposal.

## 14. Transport information

DOT

Not regulated.

**IMDG** 

Not regulated.

IATA

Not regulated.

# 15. Regulatory information

# **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Crystalline silica kidney effects

lung effects

immune system effects

Cancer

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### **Hazard categories**

Immediate (Acute) Health Hazards
Acute toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific Target Organ Toxicity - Single Exposure

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

## **US State Regulations**

## **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

# 16.Other information, including date of preparation or last revision

**Issue Date:** 30.08.2017

**Revision Date:** 30.08.2017

Version #: 1.1

SDS\_US 9/10



**Further Information:** No data available.

Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SDS\_US 10/10