



SAFETY DATA SHEET

POLYSI® Lubricants
PST-5880

Issued 10/07/2014
Revision 2 10/12/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PST-5880
Recommended Use: Lubricant (not for medical purposes)
Company: Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426, USA
Telephone: 1-708-333-8900 (Business hours)
Emergency Telephone: 1-800-255-3924 (24 hours)

2. HAZARDS IDENTIFICATION

Classification: Not hazardous

Labeling: Symbol: None
Signal Word: None
Hazard statements:
Not Hazardous

Precautionary Statements:

Use personal protective equipment as required. Wear safety glasses and gloves.
Avoid contact with eyes.
Non flammable or combustible, but may burn if involved in a fire.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contain no hazardous components above reportable concentrations.

4. FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain medical attention.
Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.
Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.
Ingestion: If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

5. FIRE FIGHTING MEASURES

Autoignition Temperature: >300°C
Flash point: >300°C
Flammable Limits (LEL) Not determined
Flammable Limits(UEL) Not determined
Suitable Extinguishing Media: On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical, or water spray. Water can be used to cool fire exposed containers.
Unsuitable Extinguishing Media: None.



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 10/07/2014

PST-5880

Revision 2 10/12/2016

Specific hazards in case of fire: Decomposes on heating and can release formaldehyde. Avoid reaction with oxidizers. At extreme elevated temperatures HF, perfluoroisobutylene, perfluorinated acid fluorides and other toxic vapors can be generated. Hydrogen Fluoride has an ACGH TLV of 3 ppm as fluoride as a Ceiling Limit and a OSHA PEL of 3ppm of fluoride as an eight hour TWA and 6 ppm as a Short Term Exposure Limit. The odor threshold for HF is 0.04 ppm, providing good warning properties for exposure.

Special protective equipment and precautions for fire fighters:

No acute hazard. Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use appropriate personal protection. (See section 8.)

Environmental precautions: For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material containment and cleaning up: Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated. Wash hands thoroughly before using tobacco or other products intended to be burned and inhaled.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Under most handling conditions, this product will not generate mist or dust.

Engineering Controls: In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is heated above 150°C or atomized ventilation should be used.

Personal Protective Equipment (PPE):





SAFETY DATA SHEET

POLYSI® Lubricants

Issued 10/07/2014

PST-5880

Revision 2 10/12/2016

Eyes: Safety glasses recommended.
Skin: Impermeable gloves should be worn. Product is compatible with most elastomers.
Inhalation: No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment must be used.

9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state: Solid. Liquid may separate from product.
Color: Off white
Odor: Mild
Odor Threshold: Not available
pH Value: Not applicable
Melting Point: Decomposes
Freezing Point: Becomes very stiff with decreasing temperature around -55°C
Initial Boiling Point: >200°C
Flash Point: >300°C COC (Base oil)
Evaporation rate: Not available
Flammability (solid, gas): Not applicable
Explosion limits: Not available
Vapor pressure: Negligible at 20°C
Vapor density: Not available
Solubility: Insoluble in water at 20°C
Partition coefficient: Not available
Auto-ignition temperature: Not available
Decomposition temperature: Begins to decompose at 150°C.

10. STABILITY AND REACTIVITY

Chemical stability: Stable under ambient temperatures and pressures
Possibility of hazardous reactions: May react with air under very high pressure. Otherwise will not react or polymerize.
Conditions to avoid: No specific conditions to avoid have been identified.
Materials to avoid: Oxidizers
Hazardous decomposition products: Decomposes on heating and produces formaldehyde, silicone dioxide, and incompletely burned carbon compounds.

11. TOXICOLOGICAL INFORMATION

Ingestion LD₅₀ (rat) > 10,000 mg/kg, Dermal LD₅₀ (rabbit) > 2,000 mg/kg
Ingestion LD₅₀ (rat) > 5,000 mg/kg, Inhalation LC₅₀ (rat) > 0.477 mg/L / 4h Method: Analogy OECD (maximum concentration attainable in experiments)
Ingestion LD₅₀ (rat) > 10,000 mg/kg; Repeated dose No toxicologically significant effects were found.
Acute inhalation toxicity: The thermal decomposition vapors of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
Skin irritation (rabbit) Not classified as irritant. No skin irritation. (human) Not classified as irritant
No skin irritation
Sensitisation (human) Not a skin sensitizer. Does not cause skin sensitization. Patch test on human volunteers did not demonstrate sensitization properties.



SAFETY DATA SHEET

POLYSI® Lubricants

Issued 10/07/2014

PST-5880

Revision 2 10/12/2016

Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Not classifiable as a human carcinogen.

No toxicity to reproduction

12. ECOLOGICAL INFORMATION

Toxicity:

Invertebrates: *Daphnia magna* 48h-LC₅₀ >10,000 mg/L

Invertebrates: *Daphnia magna* 24h-LC₅₀ >10,000 mg/L Method OECD 202

Fish: *Brachydanio rerio* 96h-LC₅₀ >10,000 mg/L Method OECD 203

Alge: *Scenedesmus subspicatus* 72h-LC₅₀ >10,000 mg/L Method OECD 201

PTFE is a polymer and is not expected to produce toxic effects in fish.

Persistence and degradability: In soil, siloxanes are degraded.

Bioaccumulative potential: Not expected to bioaccumulate.

Mobility in soil: Siloxanes are removed from water by sedimentation or binding to sewage sludge. PTFE and silica are not mobile.

13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to the European Waste Catalogue, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

U. S. Regulatory information

TSCA Inventory Status: All ingredients listed or exempt

TSCA 12 (b) Export Notification: Not listed

CERCLA Section 103 (40 CFR 302.4): N

SARA Section 302 (40 CFR 355.30): N

SARA Section 304 (40 CFR 355.40): N

SARA Section 313 (40 CFR 372.65): N

OSHA Process Safety (29 CFR 1910.119): N

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -

Acute Hazard: N

Chronic Hazard: N

Fire Hazard: N

Reactivity Hazard: N

Sudden Release Hazard: N





SAFETY DATA SHEET

POLYSI® Lubricants

Issued 10/07/2014

PST-5880

Revision 2 10/12/2016

State Regulations: Not on California Proposition 65 list. Does not contain any contaminants or by-products known to the State of California to cause cancer or reproductive toxicity.

Note – There are no known safety, health or environmental restrictions or prohibitions in any country where this product is produced, imported or marketed.

Chemical Inventories:

DSL (Canada)

All ingredients listed or exempt

IECSC (Peoples Republic of China)

All ingredients listed or exempt

TSCA (United States of America)

All ingredients listed or exempt

16. OTHER INFORMATION

NFPA Hazard Classification:

Health: 0

Flammability: 1

Reactivity: 0

Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 0

Flammability: 1

Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.