

POLYSI® Lubricants Issued 8/25/20 PST-1041 Revision 0 8/25/20

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PST-1041

**Recommended Use:** Cable pulling (not for medical purposes)

**Company:** Fuchs Lubricants Co. 17050 Lathrop Avenue

Harvey, Illinois 60426

**Telephone:** 708-333-8900

Emergency Telephone: 800-255-3924 (24 hrs)

### 2. HAZARDS IDENTIFICATION

Classification: This mixture is considered hazardous. May cause eye damage, allergic skin

reaction or irritation.

Labeling: Symbol:



Signal Word: Danger!

May be damaging to eyes. Harmful if swallowed

May cause allergic skin reaction and irritation.

## **Precautionary Statements:**

Use personal protective equipment as required. Wear safety glasses and gloves.

Do not ingest.

Avoid contact with eyes.

Avoid breathing spray. Use in well ventilated area.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Identity: Biocides; < 0.5%
CAS Number: Proprietary mixture

### 4. FIRST AID MEASURES





POLYSI® Lubricants Issued 8/25/20
PST-1041 Revision 0 8/25/20

Eye Contact: If in eyes rinse cautiously with plenty of water. Remove contact lenses, if present

and easy to do. Rinse for at least 15 minutes. If signs/symptoms persist, get

medical attention. Obtain medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical

attention. No need for first aid is anticipated.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms

persist, get medical attention.

Ingestion: If swallowed, DO NOT induce vomiting. If irritation or discomfort occurs, obtain

medical assistance.

### 5. FIRE FIGHTING MEASURES

Autoignition Temperature: Not determined None determined Flammable Limits (LEL) Not determined Not determined Not determined Not determined

Suitable Extinguishing Media: Water spray, fog, dry chemical, regular foam or carbon dioxide.

Unsuitable Extinguishing Media: None known

Specific hazards in case of fire: Irritating and possible toxic vapors may be produced in the

case of a fire.

### Special protective equipment and precautions for fire fighters:

Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Use appropriate personal protection. (See section 8.)

**Environmental precautions:** For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**Methods for material containment and cleaning up:** Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

### 7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that

cannot be decontaminated.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store





POLYSI® Lubricants Issued 8/25/20 **PST-1041** 

Revision 0 8/25/20

in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

#### **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Control Parameters: if vapor levels exceed 9.5 mg/m^3 use ventilation

Engineering Controls: Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Processing may form hazardous compounds (see Section 10). Vapors not expected under normal use.

### Personal Protective Equipment (PPE):

Eyes: Safety goggles recommended.

Skin: Impermeable gloves should be worn. Product is compatible with most

elastomers.

Inhalation: No respiratory protection required under most conditions. If workplace

concentrations are excessive, approved respiratory equipment must be used.

### 9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state: Gel Color: Blue Odor: Mild

Odor Threshold: Not available 6.5 to 8.5 pH Value: **Melting Point:** Not determined

**Freezing Point:**  $0^{\circ}C$ **Initial Boiling Point:** 100°C Flash Point: None known **Evaporation rate:** Not available Flammability (solid, gas): Not applicable **Explosion limits:** Not available Vapor pressure: Not determined Vapor density: Not available Solubility: Soluble Specific Gravity: 1.00

Auto-ignition temperature: Not available **Decomposition temperature:** Not determined **Dynamic Viscosity:** 21.000 cP Percent Non-Volatile Solids: 3.3%

# 10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal ambient temperatures and pressures

Possibility of hazardous reactions: None under normal conditions. Conditions to avoid: Avoid heat and contamination.

Materials to avoid: No data is available

Hazardous decomposition products: Thermal decomposition and combustion may liberate

carbon dioxide and other toxic vapors and gases.

### 11. TOXICOLOGICAL INFORMATION

(a) acute toxicity Estimate: calculated oral > 80,000 mg/kg; dermal > 100,000 mg/kg

(b) skin corrosion/irritation Can cause skin irritation





POLYSI® Lubricants PST-1041

Issued 8/25/20 Revision 0 8/25/20

- (c) serious eye damage/irritation May be irritating to the eyes.
- (d) respiratory or skin sensitization Biocides may cause skin sensitization
- (e) germ-cell mutagenicity Not a germ cell mutagen.
- (f) carcinogenicity Not a carcinogen.
- (g) reproductive toxicity Not a reproductive toxin
- (h) aspiration hazard Not applicable (not an aerosol/mist).

#### 12. ECOLOGICAL INFORMATION

## Toxicity:

The ecological effects are not established for this mixture. Highly recommended that material be prevented from entering waterways and soil. May be harmful to aquatic life.

### 13. DISPOSAL PROCEDURES

**Waste treatment methods:** Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

**According to the European Waste Catalogue**, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

**For USA Disposal:** Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

### 14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Not a dangerous good

## 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

### Other Information:

# U. S. Regulatory information

TSCA Inventory Status: All ingredients listed or exempt

TSCA 12 (b) Export Notification: Not listed

CERCLA Section 103 (40 CFR 302.4): N
SARA Section 302 (40 CFR 355.30): N
SARA Section 304 (40 CFR 355.40): N
SARA Section 313 (40 CFR 372.65): N
OSHA Process Safety (29 CFR 1910.119): N

SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -

Acute Hazard: Y
Chronic Hazard: N
Fire Hazard: N
Reactivity Hazard: N
Sudden Release Hazard: N

### State Regulations:

California Proposition 65: Warning! This product does not contain any chemical known in the state of California to cause cancer.





POLYSI® Lubricants PST-1041

Issued 8/25/20 Revision 0 8/25/20

Chemical Inventories:

DSL (Canada)

EINECS (European Union)

ENCS/ISHL (Japan)

IECSC (Peoples Republic of China)

TSCA (United States of America)

All ingredients listed or exempt All ingredients listed or exempt

### **16. OTHER INFORMATION**

NFPA Hazard Classification:

Health: 1
Flammability: 0
Reactivity: 0
Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 1 Flammability: 0 Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

