



SAFETY DATA SHEET

POLYSI® Lubricants PST-1052 SLIP STREAM

Issued 07/20/17
Revision 1 7/20/17

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PST-1052
Recommended Use: Lubricant (not for incidental food contact or medical purposes)
Company: Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, Illinois 60426
Telephone: 708-333-8900
Emergency Telephone: 800-255-3924 (24 hrs)

2. HAZARDS IDENTIFICATION

Classification: Moderately hazardous.
Labeling: Symbol: None

Signal Word: None

Hazard statements:
May cause eye irritation
May cause skin irritation
May be harmful if swallowed

Precautionary Statements:

Use personal protective equipment as required. Wear safety glasses and gloves.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This product contains no hazardous components above reportable concentrations.

4. FIRST AID MEASURES

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. Obtain medical attention.
Skin Contact: Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.
Inhalation: If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.
Ingestion: If swallowed, do not induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

5. FIRE FIGHTING MEASURES

Autoignition Temperature: Not determined
Flash point: > 100°C (estimated due to water content)
Flammable Limits (LEL) Not determined
Flammable Limits(UEL) Not determined
Suitable Extinguishing Media: On large fires used dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical, or alcohol resistant foam. Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media: Water with full jet.

Specific hazards in case of fire: Decomposes on heating and produces incompletely burned oxides of phosphorous, silicon dioxide, carbon compounds and aldehydes. Avoid reaction with oxidizers.

Special protective equipment and precautions for fire fighters:

Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-





SAFETY DATA SHEET

POLYSI® Lubricants PST-1052 SLIP STREAM

Issued 07/20/17

Revision 1 7/20/17

demand or other positive pressure mode in combination with a separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use appropriate personal protection. (See section 8.)

Environmental precautions: For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material containment and cleaning up: Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Under most handling conditions, this product will not generate mist or dust.

Engineering Controls: In most conditions, no special local ventilation is needed. General ventilation recommended. If the product is atomized ventilation should be used.

Personal Protective Equipment (PPE):

Eyes: Safety glasses recommended.

Skin: Impermeable gloves should be worn. Product is compatible with most elastomers.

Inhalation: No respiratory protection required under most conditions. If concentrations exceed exposure limits, approved respiratory equipment must be used.

9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state:	Liquid
Color:	Clear colorless
Odor:	Mild glycol
Odor Threshold:	Not available
pH Value:	Not applicable
Melting Point:	Not applicable
Freezing Point:	Not determined
Initial Boiling Point:	Not determined
Flash Point:	> 100°C mixture contains water
Evaporation rate:	Not available
Flammability (solid, gas):	Not applicable
Explosion limits:	Not available
Vapor pressure:	Not determined
Vapor density:	Not determined





SAFETY DATA SHEET

POLYSI® Lubricants PST-1052 SLIP STREAM

Issued 07/20/17
Revision 1 7/20/17

Solubility: Soluble
Partition coefficient: Not available
Auto-ignition temperature: Not available
Decomposition temperature: Not available

10. STABILITY AND REACTIVITY

Chemical stability: Stable under ambient temperatures and pressures
Possibility of hazardous reactions: Can react with strong oxidizers. Other hazardous reactions have not been identified. Otherwise will not react or polymerize.
Conditions to avoid: No specific conditions to avoid have been identified.
Materials to avoid: Oxidizers.
Hazardous decomposition products: The following decomposition products may form during fire or at very high temperatures: oxides of phosphorous, silicon dioxide, carbon compounds and aldehydes.

11. TOXICOLOGICAL INFORMATION

Exposure Routes:

Eye
Skin
Oral
Inhalation

Information on toxicological effects: May cause eye and skin irritation. Repeated ingestion of large amounts may injure internally.

Acute Toxicity Estimate:

Ingestion LD₅₀, Rat >2,000 mg/kg, Dermal LD₅₀, Rabbit >2,000 mg/kg

Respiratory Sensitization: Not classified based available information.

Skin Sensitization: Not classified based available information.

Carcinogenicity: Not classified based available information.

Germ Cell Mutagenicity: Not classified based available information.

Reproductive Toxicity: Not classified based available information.

Specific Organ Toxicity (SE or RE): Not classified based available information.

12. ECOLOGICAL INFORMATION

Toxicity:

The ecological hazards associated with this mixture are not known. Recommend all efforts to limit material from entering water ways or soil.

13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to the European Waste Catalogue, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state, and local environmental control regulations.



SAFETY DATA SHEET

POLYSI® Lubricants PST-1052 SLIP STREAM

Issued 07/20/17
Revision 1 7/20/17

14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Non-hazardous

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

Worldwide Chemical Inventories and lists: MoS₂ is not a SEVESO substance, not an ozone-depleting substance and not a persistent organic pollutant.

Other regulatory information: Germany (base on read across) Water Hazard class, WGK = 1 (low hazard to water)

Chemical safety assessment: MoS₂ is REACH exempt as per Annex V and registration is not required.

Other Information:

U. S. Regulatory information

TSCA Inventory Status:	Y or exempt
CEPA Inventory Status:	Y or exempt
TSCA 12 (b) Export Notification:	Not listed
CERCLA Section 103 (40 CFR 302.4):	N
SARA Section 302 (40 CFR 355.30):	N
SARA Section 304 (40 CFR 355.40):	N
SARA Section 313 (40 CFR 372.65):	N
OSHA Process Safety (29 CFR 1910.119):	N
SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -	
Acute Hazard:	N
Chronic Hazard:	N
Fire Hazard:	N
Reactivity Hazard:	N
Sudden Release Hazard:	N

State Regulations: This product may contain a chemical known to the State of California to cause cancer. Formaldehyde (50-00-0) could be present at concentrations no greater than 50 parts per billion.

Note – There are no known safety, health or environmental restrictions or prohibitions in any country where this product is produced, imported or marketed.

16. OTHER INFORMATION

NFPA Hazard Classification:

Health: 1

Flammability: 1

Reactivity: 0

Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 1

Flammability: 1

Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.





SAFETY DATA SHEET

POLYSI® Lubricants **PST-1052 SLIP STREAM**

Issued 07/20/17

Revision 1 7/20/17

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

