



SAFETY DATA SHEET

POLYSI® Lubricants
PST-1220

Issued 2/14/18
Revision 0 2/14/18

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PST-1220
Recommended Use: Metal removal and forming (not for medical purposes)
Company: Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, Illinois 60426
Telephone: 708-333-8900
Emergency Telephone: 800-255-3924 (24 hrs)

2. HAZARDS IDENTIFICATION

Classification: This mixture is considered hazardous. Can cause allergic skin reaction/sensitization. Can cause severe eye and skin irritation. May cause harm to breast fed children.

Labeling: Symbol:



Signal Word: Warning!

Reproductive toxicant.

Hazard statements: Causes serious eye irritation. Category 2A

Harmful if swallowed

May cause allergic skin reaction.

Precautionary Statements:

Use personal protective equipment as required. Wear safety glasses and gloves.

Do not ingest.

Avoid contact with eyes.

Avoid breathing spray. Use in well ventilated area.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Identity: Biocides; < 5%
CAS Number: Proprietary mixture

Chemical Identity: Ethoxylated Alcohols; < 10%
CAS Number: Proprietary mixture

Chemical Identity: Sulfonic Acids, Petroleum, Sodium Salts; < 25%
CAS Number: 68608-26-4

Chemical Identity: Mineral Oil; 50 - 75%
CAS Number: 64742-52-5

Chemical Identity: Medium Chain, C14-17, Chlorinated Alkanes; 5 - 10%
CAS Number: 85535-85-9



SAFETY DATA SHEET

POLYSI® Lubricants
PST-1220

Issued 2/14/18
Revision 0 2/14/18

4. FIRST AID MEASURES

- Eye Contact:** If in eyes. Rinse cautiously with plenty of water. Remove contact lenses, if present and easy to do. Rinse for at least 15 minutes. If signs/symptoms persist, get medical attention. Obtain medical attention.
- Skin Contact:** Wash affected area with soap and water. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.
- Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention.
- Ingestion:** If swallowed, **DO NOT** induce vomiting. If irritation or discomfort occurs, obtain medical assistance.

5. FIRE FIGHTING MEASURES

- Autoignition Temperature:** Not determined
- Flash point:** > 150°C
- Flammable Limits (LEL)** Not determined
- Flammable Limits(UEL)** Not determined
- Suitable Extinguishing Media:** Dry chemical, regular foam or carbon dioxide.
- Unsuitable Extinguishing Media:** Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards in case of fire: Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire fighters:

Move container from fire area, if possible. Avoid breathing vapors or dusts. Keep upwind. Use full firefighting gear (bunker gear). Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive pressure mode in combination with a separate escape air supply. Use any self contained breathing apparatus with a full face piece.

Alert fire brigade and indicate hazard location. Wear breathing apparatus plus protective clothing. Cool fire exposed containers with water spray from a protected location. Do not approach containers suspected to be hot. If safe to do so, remove containers from path of fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Use appropriate personal protection. (See section 8.)

Environmental precautions: For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

Methods for material containment and cleaning up: Observe precautions from other sections. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible. Clean up residue with an appropriate solvent. Seal the container.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with skin, inhalation of mist, or ingestion. See section 8 for personal protection equipment. Practice good personal hygiene to



SAFETY DATA SHEET

POLYSI® Lubricants PST-1220

Issued 2/14/18

Revision 0 2/14/18

prevent accidental ingestion after handling. Properly dispose of clothing that cannot be decontaminated.

Conditions for safe storage, including any incompatibilities: Store away from oxidizing materials. Store product in a closed container located in a dry area. Do not store in open, inadequate, or mislabeled packaging. Check that containers are clearly labeled. Use metal cans, metal drums, plastic, or lined fiber containers. Keep away from heat and flame.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters: Recommended occupational exposure limit values are 5 mg/m³ for mineral oil and triethanolamine.

Engineering Controls: Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Processing may form hazardous compounds (see Section 10).

Personal Protective Equipment (PPE):

Eyes: Safety goggles recommended.

Skin: Impermeable gloves should be worn. Product is compatible with most elastomers.

Inhalation: No respiratory protection required under most conditions. If workplace concentrations are excessive, approved respiratory equipment must be used.

9. CHEMICAL AND PHYSICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Mild
Odor Threshold:	Not available
pH Value:	< 11.5
Melting Point:	Not determined
Freezing Point:	0°C
Initial Boiling Point:	Not determined
Flash Point:	> 150°C COC
Evaporation rate:	Not available
Flammability (solid, gas):	Not applicable
Explosion limits:	Not available
Vapor pressure:	Not determined
Vapor density:	Not available
Solubility:	Soluble
Specific Gravity:	0.95 – 0.97
Auto-ignition temperature:	Not available
Decomposition temperature:	Not determined

10. STABILITY AND REACTIVITY

Chemical stability: Stable under normal ambient temperatures and pressures

Possibility of hazardous reactions: None under normal conditions.

Conditions to avoid: Avoid heat and contamination.

Materials to avoid: No data is available

Hazardous decomposition products: Thermal decomposition and combustion may liberate carbon dioxide and other toxic vapors and gases.

11. TOXICOLOGICAL INFORMATION





SAFETY DATA SHEET

POLYSI® Lubricants

PST-1220

Issued 2/14/18

Revision 0 2/14/18

- (a) **acute toxicity** Estimate: calculated oral > 5,000 mg/kg; dermal > 2,000 mg/kg
(b) **skin corrosion/irritation** Can cause skin irritation
(c) **serious eye damage/irritation** Severely irritating to the eyes.
(d) **respiratory or skin sensitization** Biocides can cause skin sensitization
(e) **germ-cell mutagenicity** Not a germ cell mutagen.
(f) **carcinogenicity** Not a carcinogen.
(g) **reproductive toxicity** Reproductive toxicant. May cause harm to breast fed children.
(h) **aspiration hazard** Not applicable (not an aerosol/mist).

12. ECOLOGICAL INFORMATION

Toxicity:

The ecological effects are not established for this mixture. Highly recommended that material be prevented from entering waterways and soil. Medium Chain Chlorinated Alkanes are very toxic to aquatic life with long lasting effects. Bioaccumulation potential in aquatic organisms.

13. DISPOSAL PROCEDURES

Waste treatment methods: Waste (substance and container material) shall be recycled/recovered or disposed of as applicable and in accordance with community (EU) and local legislation. Recycle wherever possible. Consult state land waste management authority for disposal. Bury at an approved site. Recycle containers if possible, or dispose of in an authorized landfill.

According to the European Waste Catalogue, Waste Codes are not product specific but application specific. Waste Codes should be assigned by the user based on the application in which the product is used.

For USA Disposal: Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

14. TRANSPORT INFORMATION

Class or Type: US DOT, IMO, ADR, RID, ADN, IMDG, and IATA: Not a dangerous good

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the mixture:

Other Information:

U. S. Regulatory information

TSCA Inventory Status:	All ingredients listed or exempt
TSCA 12 (b) Export Notification:	Not listed
CERCLA Section 103 (40 CFR 302.4):	N
SARA Section 302 (40 CFR 355.30):	N
SARA Section 304 (40 CFR 355.40):	N
SARA Section 313 (40 CFR 372.65):	N
OSHA Process Safety (29 CFR 1910.119):	N
SARA Hazard Categories, SARA Sections 311/312 (40 CFR 370.21) -	
Acute Hazard:	Y
Chronic Hazard:	Y
Fire Hazard:	N
Reactivity Hazard:	N
Sudden Release Hazard:	N

State Regulations:





SAFETY DATA SHEET

POLYSI® Lubricants

Issued 2/14/18

PST-1220

Revision 0 2/14/18

California Proposition 65: Warning! This product does not contain any chemical known in the state of California to cause cancer.

Chemical Inventories:

DSL (Canada)

All ingredients listed or exempt

EINECS (European Union)

All ingredients listed or exempt

ENCS/ISHL (Japan)

All ingredients listed or exempt

IECSC (Peoples Republic of China)

All ingredients listed or exempt

TSCA (United States of America)

All ingredients listed or exempt

16. OTHER INFORMATION

NFPA Hazard Classification:

Health: 1

Flammability: 1

Reactivity: 0

Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency personnel to address the hazards that are presented by short-term, acute exposure to material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification:

Health: 1

Flammability: 1

Reactivity: 0

Protection: B (See PPE section)

Hazardous Material Identification System (HMIS) hazard ratings are designed to inform employees of chemical hazards in the workplace. The ratings are based on inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations.

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.