

SAFETY DATA SHEET

1. Identification

Product name	RENOFORM SVX 3617
Other means of identification	No data available.
Recommended use:	Metalworking fluid
Restrictions on use:	Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
	Harvey, Illinois 60426
Telephone:	708-333-8900
Fax:	708-333-9180
Contact Person:	EHS Department
E-mail:	sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Physical	Hazards	

Flammable liquids	Category 3
Health Hazards	
Skin Corrosion/Irritation	Category 2
Specific Target Organ Toxicity - Single Exposure	Category 3
Aspiration Hazard	Category 1

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTRE/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. In case of fire: Use to extinguish.
Storage:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.
Unknown toxicity - Health	
Acute toxicity, oral	0 %

Acute toxicity, orai	0%
Acute toxicity, dermal	0 %
Acute toxicity, inhalation, vapor	97.95 %
Acute toxicity, inhalation, dust	5.59 %
or mist	



3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Mineral oil	Confidential	60 - 100%
2-6-di-tert-butyl-p-cresol	128-37-0	0.1 - 1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures		
Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.	
Inhalation:	Move to fresh air. Call a POISON CENTRE/doctor if you feel unwell.	
Skin Contact:	Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Most important symptoms/effec	ts, acute and delayed	
Symptoms:	No data available.	
Indication of immediate medical a	attention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
5. Fire-fighting measures		
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.	
Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.	



Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.		
Special protective equipment and	d precautions for firefighters		
Special fire fighting procedures:	No data available.		
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.		
6. Accidental release measures	S		
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep unauthorized personnel away. Ensure adequate ventilation. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.		
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. In case of leakage, eliminate all ignition sources. Dike far ahead of larger spill for later recovery and disposal. Use non-sparking tools.		
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.		
7. Handling and storage			
Precautions for safe handling:	End-users should follow industry best practices for handling and using this product.		
	Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.		
Conditions for safe storage, including any incompatibilities:	Store locked up. Store in a well-ventilated place. Store in a cool place. Flammable liquid storage.		



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
2-6-di-tert-butyl-p-cresol - Inhalable fraction and vapor.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (03 2012)

Protective Measures:Use explosion-proof ventilation equipment. Good general ventilation (typically
10 air changes per hour) should be used. Ventilation rates should be matched
to conditions. If applicable, use process enclosures, local exhaust ventilation,
or other engineering controls to maintain airborne levels below recommended
exposure limits. If exposure limits have not been established, maintain
airborne levels to an acceptable level. Provide easy access to water supply and
eye wash facilities.Respiratory Protection:In case of inadequate ventilation use suitable respirator. Seek advice from
supervisor on the company's respiratory protection standards.

Eye Protection:	Wear safety glasses with side shields (or goggles).
Eye Protection:	Wear safety glasses with side shields (or goggles).

- **Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- **Hygiene measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties

Appearance	
Physical state:	Liquid
Form:	No data available.
Color:	Colorless
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	40.56 °C (105.01 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	

5/9



Flammability limit - upper (%): Flammability limit - lower (%): Explosive limit - upper (%): Explosive limit - lower (%): Vapor pressure: Vapor density: Relative density: Solubility(ies) Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: VOC: No data available. 0.77

Insoluble No data available. No data available. No data available. No data available. 1 mm2/s (40 °C) 95.48 % (Method 24)

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	Harmful if swallowed.
Inhalation:	May cause irritation to the respiratory system. Harmful if inhaled.
Skin Contact:	Causes skin irritation.
Eye contact:	Causes eye irritation.
Symptoms related to the physical, chemical and toxicological characteristics Ingestion: No data available.	
Inhalation:	No data available.



Skin Contact:	No data available.	
Eye contact:	No data available.	
Information on toxicological effects		
Acute toxicity (list all possible routes of exposure)		
Oral Product:	ATEmix (): > 5000 mg/kg	
Dermal Product:	ATEmix (): 2000 - 5000 mg/kg	
Inhalation Product:	Not classified for acute toxicity based on available data.	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Serious Eye Damage/Eye Irritation Product:	on No data available.	
Respiratory or Skin SensitizationProduct:No data available.		
Carcinogenicity Product:	No data available.	
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified		
US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified		
Germ Cell Mutagenicity		
In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity		



Product:	No data available.	
Specific Target Organ Toxicity - Single Exposure Product: No data available.		
Specific Target Organ Toxicity · Product:	- Repeated Exposure No data available.	
Aspiration Hazard Product:	May be fatal if swallowed and enters airways.	
Other effects:	No data available.	
12. Ecological information		
General information:	This product has not been evaluated for ecological toxicity or other environmental effects.	
13. Disposal considerations		
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.	
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.	
14. Transport information		
DOT UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): Packing Group: Marine Pollutant: Special precautions for user:	NA 1993 Combustible liquid, n.o.s.(Petroleum distillates) CBL NONE III No	



IMDG

UN Number:	UN 1993
UN Proper Shipping Name:	FLAMMABLE LIQUID, N.O.S.(Petroleum distillates)
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
Packing Group:	III
Marine Pollutant:	Not regulated.
Special precautions for user:	-
Cargo aircraft only:	Allowed.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

16.Other information, including date of preparation or last revision		
Issue Date:	21.11.2017	
Revision Date:	16.01.2017	
Version #:	1.2	
Further Information:	No data available.	
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.	