

SAFETY DATA SHEET

1. Identification

Product name

RENOLIT GRS PT YELLOW BB

Other means of identification

Recommended use:

Paint

Restrictions on use:

Industrial use only

No data available.

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
- · ·	Harvey, Illinois 60426
Telephone:	708-333-8900
Fax:	708-333-9180
Contact Person: E-mail:	EHS Department sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Physical H	lazards
------------	---------

Flammable liquids	Category 3
Health Hazards	
Skin Corrosion/Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B

Label Elements

Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapor. Causes skin irritation. May cause genetic defects. May cause cancer.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see in product SDS). Take off contaminated clothing. In case of fire: Use water mist, dry chemical extinguisher, or foam to extinguish.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Other hazards which do not result in GHS classification:	None.

3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Limestone	1317-65-3	30 - 40%
Mineral spirits	Confidential	10 - 20%
Solvent naphtha (petroleum), light arom.	64742-95-6	1 - 5%
Mineral oil	Confidential	2%
Petrolatum	8009-03-8	2%
Benzene, (1-methylethyl)-	98-82-8	0.2%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.



4. First-aid measures	
4. First-aid measures	
Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
Most important symptoms/effect	s, acute and delayed
Symptoms:	No data available.
Indication of immediate medical a	ttention and special treatment needed
Treatment:	Symptoms may be delayed.
5. Fire-fighting measures	
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
Suitable (and unsuitable) exting	uishing media
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.
Special protective equipment an	d precautions for firefighters
Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.



Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep unauthorized personnel away. Ensure adequate ventilation. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. In case of leakage, eliminate all ignition sources. Dike far ahead of larger spill for later recovery and disposal. Use non-sparking tools.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use.
	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.



8. Exposure controls/personal protection

Exposure Limits

Chemical name	Туре	Exposure Limit Valu	ues	Source
Limestone - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Limestone - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral spirits	TWA	100 ppm		US. ACGIH Threshold Limit Values (03 2012)
Mineral spirits	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral oil - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Petrolatum - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Petrolatum - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Benzene, (1-methylethyl)-	TWA	50 ppm		US. ACGIH Threshold Limit Values (03 2012)
Benzene, (1-methylethyl)-	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Protective Measures:	Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Observe good industrial hygiene practices.

9. Physical and chemical properties



Appearance

Physical state: Form: Color: Odor: Odor threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash Point: **Evaporation rate:** Flammability (solid, gas): Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): Flammability limit - lower (%): Explosive limit - upper (%): **Explosive limit - lower (%):** Vapor pressure: Vapor density: **Relative density:** Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water): Auto-ignition temperature: **Decomposition temperature:** Viscosity:

liquid No data available. Yellow Solvent odor No data available. No data available. No data available. A3 °C (109 °F) No data available. No data available. No data available.

1.0 %(V) No data available. No data available. No data available. No data available. 1.31

Insoluble No data available. No data available. No data available. No data available. No data available.

Other information VOC:

222.22 g/l

10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	No data available.



Hazardous Decomposition	Thermal decomposition or combustion may liberate carbon oxides and
Products:	other toxic gases or vapors.

11. Toxicological information

Information on likely routes of ex Ingestion:	p osure Harmful if swallowed.
Inhalation:	Harmful if inhaled.
Skin Contact:	Causes skin irritation.
Eye contact:	Eye contact is possible and should be avoided.
Symptoms related to the physica Ingestion:	I, chemical and toxicological characteristics No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Information on toxicological effe	cts
Acute toxicity (list all possible	routes of exposure)
Oral Product:	Not classified for acute toxicity based on available data.
Dermal Product:	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritatio Product:	on No data available.
Respiratory or Skin Sensitization Product:	n No data available.
Carcinogenicity Product:	May cause cancer.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified		
Cumene	Overall evaluation: 2B. Possibly carcinogenic to humans.	
US. National Toxicolog No carcinogenic compor	y Program (NTP) Report on Carcinogens: nents identified	
US. OSHA Specifically No carcinogenic compor	Regulated Substances (29 CFR 1910.1001-1050): nents identified	
Germ Cell Mutagenicity		
In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Toxici Product:	i ty - Single Exposure No data available.	
Specific Target Organ Toxici Product:	i ty - Repeated Exposure No data available.	
Aspiration Hazard Product:	No data available.	
Other effects:	Components may cause a risk to the following : Skin irritation Central Nervous System impairment Eye irritation Upper Respiratory Tract irritation Kidneys	
12. Ecological information		
General information:	This product has not been evaluated for ecological toxicity or other environmental effects.	
13. Disposal considerations	\$	
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.	



Contaminated Packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	
UN Number:	UN 1263
UN Proper Shipping Name:	Paint
Transport Hazard Class(es)	
Class:	3
Label(s):	3
Packing Group:	III
Marine Pollutant:	No
Special precautions for user:	_
IMDG	
UN Number:	UN 1263
UN Proper Shipping Name:	PAINT
Transport Hazard Class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
Packing Group:	
Marine Pollutant:	Not regulated.
Special precautions for user:	-
ΙΑΤΑ	
UN Number:	UN 1263
Proper Shipping Name:	Paint
Transport Hazard Class(es):	
Class:	3
Label(s):	3
Packing Group:	
Environmental Hazards	Not regulated.
Special precautions for user:	_
Other information	
Passenger and cargo aircraft:	Allowed.
Cargo aircraft only:	Allowed.
<u> </u>	

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.



Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable (gases, aerosols, liquids, or solids) Skin Corrosion or Irritation Germ Cell Mutagenicity Carcinogenicity

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



This product can expose you to chemicals includingCumenewhich is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision		
Issue Date:	23.10.2018	
Revision Date:	23.10.2018	
Version #:	1.1	
Further Information:	No data available.	
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.	