

1. Identification	
Product name	RENOLIT KT 245
Other means of identificatio	n No data available.
Recommended use:	Lubricating grease
Restrictions on use:	Industrial use only
Manufacturer/Importer/Supp	lier/Distributor Information
Manufacturer Company Name: Address: Telephone: Fax: Contact Person: E-mail: Emergency telephone number	Fuchs Lubricants Co. 17050 Lathrop Avenue Harvey, Illinois 60426 708-333-8900 708-333-9180 EHS Department msds@fuchs.com er: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)
2. Hazard(s) identification	
Hazard Classification	Not classified as hazardous under 29CFR 1910.1200 (HazCom 2012)
Label Elements	
Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement:	Not applicable
Precautionary Statement	Not applicable
Other hazards which do not result in GHS classification:	None.
3. Composition/information	on ingredients



Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Mineral oil	Confidential	3 - 7%
Barium compound	Confidential	1 - 5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures	
Ingestion:	Rinse mouth thoroughly. Call a Poison Center or doctor if you feel unwell. Do NOT induce vomiting.
Inhalation:	Move to fresh air. Call a Poison Center or doctor if you feel unwell.
Skin Contact:	Remove contaminated/saturated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.
Most important symptoms/effec	ts, acute and delayed
Symptoms:	No data available.
Indication of immediate medical a	attention and special treatment needed
Treatment:	Get medical attention as appropriate or if symptoms persist.
5. Fire-fighting measures	
General Fire Hazards:	No unusual fire or explosion hazards noted.
Suitable (and unsuitable) exting	uishing media
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	Heat may cause the containers to pressurize and possibly rupture. During fire, gases hazardous to health may be formed.
Special protective equipment ar	nd precautions for firefighters
Special fire fighting procedures:	No data available.



Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment appropriate for industrial fires.
6. Accidental release measure	s
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not handle damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.
Methods and material for containment and cleaning up:	Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.
Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so and protect against releases into the environment. Remediate as appropriate.
7. Handling and storage	
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.

8. Exposure controls/personal protection

Exposure Limits

Chemical name	type	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral oil	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium compound - as Ba	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Barium compound - as Ba	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Protective Measures:

Use personal protective equipment as required.

Respiratory Protection:

In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.

Eye Protection: MSDS_US - R00000450641 Wear safety glasses with side shields (or goggles).



Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. Discard contaminated footwear that cannot be cleaned. Avoid contact with skin, eyes, and clothing.

9. Physical and chemical properties

Appearance

Solid
Semi-solid
Black
Mild petroleum
No data available.
246.11 °C (475.00 °F)
No data available.
No data available.
No data available.
0.934
No data available.
> 22 mm2/s (40 °C)



10. Stability and reactivity	
Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of Hazardous Reactions:	None under normal conditions.
Conditions to Avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.			
Inhalation:	Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.		
Skin Contact:	Prolonged skin contact may cause redness and irritation.		
Eye contact:	Eye contact is possible and should be avoided.		
Symptoms related to the physical, chemical and toxicological characteristics Ingestion: No data available.			
Inhalation:	No data available.		
Skin Contact:	No data available.		
Eye contact:	No data available.		
Information on toxicological effects			
Acute toxicity (list all possible routes of exposure)			
Oral Product:	ATEmix (): > 5000 mg/kg		
Dermal Product:	ATEmix (): 1000 - 2000 mg/kg		

Inhalation



Product:	Not classified for acute toxicity based on available data.
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irritati Product:	on No data available.
Respiratory or Skin Sensitizatio Product:	n No data available.
Carcinogenicity Product:	No data available.
IARC Monographs on the No carcinogenic component	Evaluation of Carcinogenic Risks to Humans: s identified
US. National Toxicology P No carcinogenic component	rogram (NTP) Report on Carcinogens: s identified
US. OSHA Specifically Reg No carcinogenic component	gulated Substances (29 CFR 1910.1001-1050): s identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity - Product:	•
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.



12. Ecological information	
General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
13. Disposal considerations	;
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.

This material is not subject to transport regulations.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories None

SARA 313 (TRI Reporting)

Chemical Identity	
Barium compound	

Reporting threshold for other users 10000 lbs Reporting threshold for manufacturing and processing 25000 lbs.

US State Regulations

US. California Proposition 65

No component is regulated by CA Prop 65.

16.Other information, including date of preparation or last revision



Revision Date:	30.05.2015
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty . The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.