

SAFETY DATA SHEET

1. Identification

Product name	RENOLIT S2 TX
Other means of identification	No data available.
Recommended use:	Lubricating grease
Restrictions on use:	Industrial use only

Manufacturer/Importer/Supplier/Distributor Information

Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
	Harvey, Illinois 60426
Telephone:	708-333-8900
Fax:	708-333-9180
Contact Person:	EHS Department
E-mail:	sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

2. Hazard(s) identification

Hazard Classification

Not classified as hazardous

Label Elements

Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement:	Not applicable
Precautionary Statements	Not applicable

None.



3. Composition/information on ingredients

Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Paraffin oils	Confidential	50 - <100%
Polyisobutylene	Confidential	5 - <10%
Mineral oil	Confidential	1 - <5%
Boric acid, potassium salt	Confidential	1 - <5%
Antimony compound	Confidential	1 - <5%
Zinc compound	Confidential	0.1 - <1%
Molybdenum compound (insoluble)	Confidential	0.1 - <1%
Benzene, dimethyl-	1330-20-7	0.1 - <1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

4. First-aid measures		
Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.	
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.	
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.	
Most important symptoms/effects, acute and delayed		
Symptoms:	No data available.	
Indication of immediate medical	attention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) exting	guishing media	
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	



Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment and	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures	S	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.	
Methods and material for containment and cleaning up:	Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.	
Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.	
7. Handling and storage		
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.	
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.	



8. Exposure controls/personal protection

Exposure Limits	1		
Chemical name	Туре	Exposure Limit Values	Source
Paraffin oils - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Paraffin oils - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Paraffin oils - Mist.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Antimony compound - as Sb	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Antimony compound - as Sb	PEL	0.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Molybdenum compound (insoluble) - Respirable fraction as Mo	TWA	0.5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Molybdenum compound (insoluble) - as Mo	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Benzene, dimethyl-	TWA	100 ppm	US. ACGIH Threshold Limit Values (03 2012)
Benzene, dimethyl-	STEL	150 ppm	US. ACGIH Threshold Limit Values (03 2012)
Benzene, dimethyl-	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Protective Measures:	Use personal protective equipment as required.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

9. Physical and chemical properties



Appearance **Physical state:** Form: Color: Odor: Odor threshold: pH: Melting point/freezing point: Initial boiling point and boiling range: Flash Point: **Evaporation rate:** Flammability (solid, gas): Upper/lower limit on flammability or explosive limits Flammability limit - upper (%): Flammability limit - lower (%): Explosive limit - upper (%): **Explosive limit - lower (%):** Vapor pressure: Vapor density: **Relative density:** Solubility(ies) Solubility in water: Solubility (other): Partition coefficient (n-octanol/water): Auto-ignition temperature:

solid Grease Dark blue Mild petroleum/solvent No data available. No data available. No data available. No data available. 218.33 °C (424.99 °F) No data available. 0.91 Insoluble No data available. No data available. No data available. No data available. > 22 mm2/s (40 °C, estimated)

10. Stability and reactivity

Viscosity:

Decomposition temperature:

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.



11. Toxicological informati	on
Information on likely routes Ingestion:	of exposure May be ingested by accident. Ingestion may cause irritation and malaise.
Inhalation:	Inhalation is the primary route of exposure. In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Prolonged skin contact may cause redness and irritation.
Eye contact:	Eye contact is possible and should be avoided.
Symptoms related to the phy Ingestion:	vsical, chemical and toxicological characteristics No data available.
Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Information on toxicological	effects
Acute toxicity (list all pos	sible routes of exposure)
Oral Product:	ATEmix (): > 5000 mg/kg
Dermal Product:	Not classified for acute toxicity based on available data.
Inhalation Product:	ATEmix (, 4 h): > 5 mg/l Dusts, mists and fumes
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Serious Eye Damage/Eye Irr Product:	itation No data available.
Respiratory or Skin Sensitiz Product:	ation No data available.
Carcinogenicity Product:	No data available.



IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicity - Product:	Single Exposure No data available.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

12. Ecological information

General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
13. Disposal considerations	
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.



14. Transport information

DOT

Not regulated.

IMDG Not regulated.

ΙΑΤΑ

Not regulated.

15. Regulatory information

US Federal Regulations

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Not classified as hazardous

SARA 313 (TRI Reporting)

Chemical Identity
Antimony compound

Reporting threshold for other users 10000 lbs

Reporting threshold for manufacturing and processing 25000 lbs.

US State Regulations

US. California Proposition 65



WARNING: This product can expose you to chemicals including, Ethylbenzene, which is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

16.Other information, including date of preparation or last revision

Issue Date:	07.09.2018
Revision Date:	20.08.2018
Version #:	1.2
Further Information:	No data available.



Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.