

# SAFETY DATA SHEET

## 1. Identification

Product name	STABYL EAL LG 2
Other means of identification	No data available.
Recommended use:	Grease
Restrictions on use:	Industrial use only

#### Manufacturer/Importer/Supplier/Distributor Information

#### Manufacturer

Company Name:	Fuchs Lubricants Co.
Address:	17050 Lathrop Avenue
	Harvey, Illinois 60426
Telephone:	708-333-8900
Fax:	708-333-9180
Contact Person:	EHS Department
E-mail:	sds@fuchsus.com

Emergency telephone number: 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

#### **Hazard Classification**

Not classified as hazardous

#### Label Elements

Hazard Symbol:	No symbol
Signal Word:	No signal word.
Hazard Statement:	Not applicable
Precautionary Statements	Not applicable



## 3. Composition/information on ingredients

#### Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Mineral oil	Confidential	10 - <20%
Calcium carbonate	471-34-1	1 - <5%
Magnesium silicate	14807-96-6	1 - <5%
Mineral oil	Confidential	1 - <5%
Inorganic stearate	Confidential	1 - <5%
Calcium hydroxide	1305-62-0	0.1 - <1%
Sodium nitrite	7632-00-0	0.1 - <1%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.

# 4. First-aid measures

Ingestion:	Rinse mouth thoroughly. Call a POISON CENTER/doctor if you feel unwell. Do NOT induce vomiting.	
Inhalation:	Move to fresh air. Call a POISON CENTER/doctor if you feel unwell.	
Skin Contact:	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.	
Eye contact:	Flush thoroughly with water. If irritation occurs, get medical assistance. Continue to rinse for at least 15 minutes.	
Most important symptoms/effects, acute and delayed		
Symptoms:	No data available.	
Indication of immediate medical attention and special treatment needed		
Treatment:	Get medical attention if symptoms occur.	
5. Fire-fighting measures		
General Fire Hazards:	No unusual fire or explosion hazards noted.	
Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media:	Water spray, fog, CO2, dry chemical, or regular foam. Use fire- extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.	



Specific hazards arising from the chemical:	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.	
Special protective equipment and	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures	3	
Personal precautions, protective equipment and emergency procedures:	See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away. Ensure adequate ventilation.	
Methods and material for containment and cleaning up:	Absorb with sand or other inert absorbent. Stop the flow of material, if this is without risk.	
Environmental Precautions:	Avoid release to the environment. Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.	
7. Handling and storage		
Precautions for safe handling:	Observe good industrial hygiene practices. Wear appropriate personal protective equipment. Do not expose to intense heat as product may expand and pressurize container.	
Conditions for safe storage, including any incompatibilities:	Store in original tightly closed container. Avoid contact with oxidizing agents. Store away from incompatible materials.	



# 8. Exposure controls/personal protection

#### **Exposure Limits**

Chemical name	Туре	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesium silicate - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Magnesium silicate	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Magnesium silicate - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Magnesium silicate - Respirable.	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Inorganic stearate - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Inorganic stearate - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (03 2017)
Calcium hydroxide	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2012)
Calcium hydroxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium hydroxide - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Protective Measures:	Use personal protective equipment as required.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
Eye Protection:	Wear safety glasses with side shields (or goggles).
Skin and Body Protection:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.



# 9. Physical and chemical properties

Appearance	
Physical state:	solid
Form:	Grease
Color:	Off-white
Odor:	Mild
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	> 260 °C (500 °F)
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	No data available.
Relative density:	1.1
Solubility(ies)	
Solubility in water:	Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

# 10. Stability and reactivity

Reactivity:	Not reactive during normal use.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	None under normal conditions.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.



Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological informatio	n	
Information on likely routes o Ingestion:	f exposure May be ingested by accident. Ingestion may cause irritation and malaise.	
Inhalation:	None under normal conditions.	
Skin Contact:	Prolonged skin contact may cause redness and irritation.	
Eye contact:	Eye contact is possible and should be avoided.	
Symptoms related to the physe Ingestion:	sical, chemical and toxicological characteristics No data available.	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Information on toxicological e	effects	
Acute toxicity (list all possi	ible routes of exposure)	
Oral Product:	ATEmix (): > 5000 mg/kg	
Dermal Product:	Not classified for acute toxicity based on available data.	
Inhalation Product:	ATEmix (, 4 h): > 5 mg/l Dusts, mists and fumes	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	
Serious Eye Damage/Eye Irrit Product:	tation No data available.	
Respiratory or Skin Sensitiza Product:	ntion No data available.	
Carcinogenicity Product:	No data available.	



#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified

#### US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

#### **Germ Cell Mutagenicity**

In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	No data available.
Specific Target Organ Toxicit Product:	y - Single Exposure No data available.
Specific Target Organ Toxicit Product:	y - Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

# 12. Ecological information

General information:	This product has not been evaluated for ecological toxicity or other environmental effects.
13. Disposal considerations	
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.
Contaminated Packaging:	Empty containers should be taken to an approved waste handling site for recycling or disposal.



## 14. Transport information

#### DOT

Not regulated.

IMDG Not regulated.

#### ΙΑΤΑ

Not regulated.

### 15. Regulatory information

#### **US Federal Regulations**

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Crystalline silica kidney effects

kidney effects lung effects immune system effects Cancer

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Not classified as hazardous

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### **US State Regulations**

## US. California Proposition 65



WARNING: This product can expose you to chemicals including, Crystalline silica, which is [are] known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

## 16.Other information, including date of preparation or last revision

Issue Date:	24.08.2018
Revision Date:	24.08.2018
Version #:	1.0
Further Information: SDS_US	No data available.



#### Disclaimer:

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.