



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 1. Identification

**Product name** TUF DRAW 1919 A

**Other means of identification** No data available.

**Recommended use:** Metalworking fluid

**Restrictions on use:** Industrial use only

### Manufacturer/Importer/Supplier/Distributor Information

#### Manufacturer

Company Name: Fuchs Lubricants Co.  
Address: 17050 Lathrop Avenue  
Harvey, Illinois 60426  
Telephone: 708-333-8900  
Fax: 708-333-9180

Contact Person: EHS Department  
E-mail: sds@fuchsus.com

**Emergency telephone number:** 708-333-8900 (Bus. hrs) 800-255-3924 (24 hrs)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Acute toxicity (Inhalation - vapor)	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 1
Toxic to reproduction	Effects on or via lactation

### Label Elements

#### Hazard Symbol:



**Signal Word:** Danger



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Hazard Statement:** Harmful if inhaled.  
Causes skin irritation.  
Causes serious eye damage.  
May cause harm to breast-fed children.

## Precautionary Statements

**Prevention:** Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not breathe dust or mists. Avoid contact during pregnancy/while nursing. Do not eat, drink or smoke when using this product.

**Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Immediately call a POISON CENTER/doctor. Specific treatment (see this label). Take off contaminated clothing.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Other hazards which do not result in GHS classification:** None.

## Unknown toxicity - Health

Acute toxicity, oral	14.2 %
Acute toxicity, dermal	55.15 %
Acute toxicity, inhalation, vapor	95.48 %
Acute toxicity, inhalation, dust or mist	72.9 %

## 3. Composition/information on ingredients

### Hazardous Component(s):

Chemical name	CAS-No.	Concentration
Chlorinated paraffin	Confidential	25 - 50%
Mineral oil	Confidential	20 - 50%
Sulfonate	Confidential	10 - 20%
Rosin oil	8002-16-2	5 - 10%
Nonylphenol ethoxylate	Confidential	3 - 5%
Triethanolamine	102-71-6	1 - 5%

Specific chemical identities and/or exact percentages have been withheld as trade secrets.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 4. First-aid measures

<b>Ingestion:</b>	Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.
<b>Inhalation:</b>	Call a POISON CENTER/doctor/.../if you feel unwell. Move to fresh air.
<b>Skin Contact:</b>	Remove contaminated clothing and shoes. Wash contact areas with soap and water. If skin irritation occurs: Get medical advice/attention.
<b>Eye contact:</b>	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Call a physician or poison control center immediately.

### Most important symptoms/effects, acute and delayed

<b>Symptoms:</b>	No data available.
------------------	--------------------

### Indication of immediate medical attention and special treatment needed

<b>Treatment:</b>	Symptoms may be delayed.
-------------------	--------------------------

## 5. Fire-fighting measures

<b>General Fire Hazards:</b>	No unusual fire or explosion hazards noted.
------------------------------	---

### Suitable (and unsuitable) extinguishing media

<b>Suitable extinguishing media:</b>	Water spray, fog, CO <sub>2</sub> , dry chemical, or regular foam. Use fire-extinguishing media appropriate for surrounding materials.
<b>Unsuitable extinguishing media:</b>	Do not use water jet as an extinguisher, as this will spread the fire.

<b>Specific hazards arising from the chemical:</b>	Heat may cause the containers to explode. During fire, gases hazardous to health may be formed.
--	---

### Special protective equipment and precautions for firefighters

<b>Special fire fighting procedures:</b>	No data available.
<b>Special protective equipment for fire-fighters:</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

## 6. Accidental release measures



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Personal precautions, protective equipment and emergency procedures:**

Ventilate closed spaces before entering them. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Methods and material for containment and cleaning up:**

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.

**Environmental Precautions:**

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.

## 7. Handling and storage

**Precautions for safe handling:**

End-users should follow industry best practices for handling and using this product.

Guidance may be found using the current version of ASTM Standard E1497-05: Standard Practice for Selection and Safe Use of Water-Miscible and Straight Oil Metal Removal Fluids Contains amines. Do not add sodium nitrite or other nitrosating agents which may form cancer causing nitrosamines. Do not get in eyes. Wash hands thoroughly after handling. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy/while nursing. Obtain special instructions before use. Avoid contact with skin.

**Conditions for safe storage, including any incompatibilities:**

Keep container tightly closed. Store locked up. Store in a well-ventilated place.

## 8. Exposure controls/personal protection

**Exposure Limits**

Chemical name	type	Exposure Limit Values	Source
Mineral oil - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Mineral oil - Mist.	STEL	10 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Triethanolamine	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2012)

**Protective Measures:**

Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

<b>Respiratory Protection:</b>	In case of inadequate ventilation use suitable respirator. Seek advice from supervisor on the company's respiratory protection standards.
<b>Eye Protection:</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and Body Protection:</b>	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
<b>Hygiene measures:</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

## 9. Physical and chemical properties

### Appearance

<b>Physical state:</b>	liquid
<b>Form:</b>	No data available.
<b>Color:</b>	Dark brown
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	No data available.
<b>pH:</b>	No data available.
<b>Melting point/freezing point:</b>	No data available.
<b>Initial boiling point and boiling range:</b>	No data available.
<b>Flash Point:</b>	151.67 °C (305.01 °F)
<b>Evaporation rate:</b>	No data available.
<b>Flammability (solid, gas):</b>	No data available.
<b>Upper/lower limit on flammability or explosive limits</b>	
<b>Flammability limit - upper (%):</b>	No data available.
<b>Flammability limit - lower (%):</b>	No data available.
<b>Explosive limit - upper (%):</b>	No data available.
<b>Explosive limit - lower (%):</b>	No data available.
<b>Vapor pressure:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Relative density:</b>	1.069
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Emulsifiable in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Viscosity:** 400 mm<sup>2</sup>/s (40 °C)

**Other information**

**VOC:** 43.2 g/l (ASTM E 1868-10)

## 10. Stability and reactivity

**Reactivity:** Not reactive during normal use.

**Chemical Stability:** Material is stable under normal conditions.

**Possibility of hazardous reactions:** None under normal conditions.

**Conditions to avoid:** Avoid heat or contamination.

**Incompatible Materials:** No data available.

**Hazardous Decomposition Products:** Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

**Ingestion:** Harmful if swallowed.

**Inhalation:** Harmful if inhaled.

**Skin Contact:** Causes skin irritation.

**Eye contact:** Causes serious eye damage.

### Symptoms related to the physical, chemical and toxicological characteristics

**Ingestion:** No data available.

**Inhalation:** No data available.

**Skin Contact:** No data available.

**Eye contact:** No data available.

### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

**Oral**  
**Product:** ATEmix (): > 5000 mg/kg

**Dermal**



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

**Product:** ATEmix (): 2000 - 5000 mg/kg

**Inhalation Product:** ATEmix (, 4 h): 10 - 20 mg/l Vapour

**Repeated dose toxicity Product:** No data available.

**Skin Corrosion/Irritation Product:** No data available.

**Serious Eye Damage/Eye Irritation Product:** No data available.

**Respiratory or Skin Sensitization Product:** No data available.

**Carcinogenicity Product:** No data available.

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**  
No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:**  
No carcinogenic components identified

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**  
No carcinogenic components identified

## Germ Cell Mutagenicity

**In vitro Product:** No data available.

**In vivo Product:** No data available.

**Reproductive toxicity Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure Product:** No data available.

**Aspiration Hazard Product:** No data available.

**Other effects:** No data available.



LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## 12. Ecological information

**General information:** This product has not been evaluated for ecological toxicity or other environmental effects.

## 13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local laws. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. It is the responsibility of the product user or owner to determine at the time of disposal, which waste regulations must be applied.

**Contaminated Packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

**DOT**  
Not regulated.

**IMDG**  
Not regulated.

**IATA**  
Not regulated.

## 15. Regulatory information

### US Federal Regulations

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**  
None present or none present in regulated quantities.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories**  
Immediate (Acute) Health Hazards  
Delayed (Chronic) Health Hazard

### SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Nonylphenol ethoxylate	10000 lbs	25000 lbs.





LUBRICANTS.  
TECHNOLOGY.  
PEOPLE.

# SAFETY DATA SHEET

## US State Regulations

### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

## 16. Other information, including date of preparation or last revision

**Issue Date:** 12.01.2017

**Revision Date:** 12.01.2017

**Version #:** 1.2

**Further Information:** No data available.

**Disclaimer:** This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.