

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: GEARMASTER LXG 00

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating grease

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

FUCHS LUBRICANTS GERMANY GmbH
Friesenheimer Str. 19
68169 Mannheim

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

Contact for request of safety data sheets

E-mail:

Automotive lubricants

CS.Services-FLG@fuchs.com

Industrial lubricants

Telephone:

+49 621 3701-0 (ZENTRALE)

Informing department for safety data sheets

E-mail:

produktsicherheit-FLG@fuchs.com

1.4 US contact telephone :

708-333-8900

Emergency telephone:

800-255-3924

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

|| The product has been classified and labelled as hazardous according to the legislation in force.

Health Hazards

||

Toxic to reproduction

Category 2

Hazard summary

Physical Hazards:

No data available.

Product name: GEARMASTER LXG 00

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H361: Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention: P201: Obtain special instructions before use.

Response: P308+P313: IF exposed or concerned: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

General information: Lubricating grease: Thickener system and additives in synthetic base oil.

Chemical name	Identifier	Concentration *	Notes
Dialkyl dithiophosphate ester	268567-32-4	0.10 - <1.00%	
Amine aromatic , alkylated	68411-46-1	0.10 - <1.00%	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
Dialkyl dithiophosphate ester	268567-32-4	Eye Dam. 1;H318, Skin Sens. 1B;H317, Aquatic Chronic 3;H412
Amine aromatic , alkylated	68411-46-1	Repr. 2;H361f, Aquatic Chronic 3;H412

Product name: GEARMASTER LXG 00

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur. Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: In case of spills, beware of slippery floors and surfaces. Not required.

Product name: GEARMASTER LXG 00

- 6.2 Environmental Precautions:** Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
- 6.3 Methods and material for containment and cleaning up:** Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
- 6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.
- 7.2 Conditions for safe storage, including any incompatibilities:** Store in original tightly closed container. Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store away from incompatible materials. No special precautions necessary if used correctly. Use only containers specifically permitted for this substance/product. Protect from contamination
- 7.3 Specific end use(s):** No data available.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Exposure Limits

None of the components have assigned exposure limits.

8.2.Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Product name: GEARMASTER LXG 00

Skin protection**Hand Protection:**

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: ≥ 480 min
Recommended thickness of the material: ≥ 0.38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Not relevant, due to the form of the product.

Thermal hazards:

No data available.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls:

No data available.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	solid
Form:	Paste
Color:	Yellow
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water)
Drop Point:	Not applicable for mixtures
Boiling Point:	Value not relevant for classification
Flash Point:	Not applicable
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)—:	Not applicable for mixtures
Flammability Limit - Lower (%)—:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0.90 g/cm ³ (20 °C)
Solubility(ies)	
Solubility in Water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures

Product name: GEARMASTER LXG 00

Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
NLGI:	00
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11 TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Acute toxicity**Oral****Product:****Specified substance(s)**Amine aromatic ,
alkylated

Not classified for acute toxicity based on available data.

LD 50 (Rat): > 5,000 mg/kg (OECD 401)

Dermal**Product:**

Not classified for acute toxicity based on available data.

Product name: GEARMASTER LXG 00

Inhalation**Product:**

Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:**Product:**

Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation:**Product:**

Based on available data, the classification criteria are not met.

Specified substance(s)

Amine aromatic ,
alkylated

OECD 405 (Rabbit): Not irritant.

Respiratory or Skin Sensitization:**Product:**

Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Dialkyl dithiophosphate
ester

, OECD 406-1 (Guinea Pig)sensitizing

Amine aromatic ,
alkylated

No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity**Product:**

Based on available data, the classification criteria are not met.

Carcinogenicity**Product:**

Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity**Product:**

Based on available data, the classification criteria are met.

Specific Target Organ Toxicity - Single Exposure**Product:**

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure**Product:**

Based on available data, the classification criteria are not met.

Product name: GEARMASTER LXG 00

Aspiration Hazard**Product:**

Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

12.1 Toxicity**Acute toxicity****Product:**

Based on available data, the classification criteria are not met.

Fish**Specified substance(s)**Dialkyl dithiophosphate
ester

LC 50 (Fish, 96 h): 38 mg/l (OECD 203)

Amine aromatic ,
alkylated

LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)

Aquatic Invertebrates**Specified substance(s)**Dialkyl dithiophosphate
ester

EC 50 (Water Flea, 48 h): 53 mg/l (OECD 202)

Amine aromatic ,
alkylated

EC 50 (Daphnia magna): 51 mg/l (OECD 202)

Chronic ToxicityProduct:

Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants**Specified substance(s)**Dialkyl dithiophosphate
ester

EC 50 (Alga, 72 h): 79 mg/l (OECD 201)

Amine aromatic ,
alkylated

EC 50 (72 h): > 100 mg/l (OECD 201)

12.2 Persistence and Degradability**Biodegradation****Product:**

Not applicable for mixtures

Specified substance(s)Dialkyl dithiophosphate
ester

< 10 % (OECD 301B) Not readily degradable.

Amine aromatic ,
alkylated

Not readily degradable.

12.3 Bioaccumulative potential**Product:**

Not applicable for mixtures

Product name: GEARMASTER LXG 00

Specified substance(s)Dialkyl dithiophosphate
ester

Bioconcentration Factor (BCF): < 10 (OECD 305)

12.4 Mobility in soil:**Product:**

Not applicable for mixtures

**12.5 Results of PBT and vPvB
assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

13 Disposal considerations**13.1 Waste treatment methods****General information:**

Dispose in accordance with all applicable regulations.

Disposal methods:

Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

14 TRANSPORT INFORMATION**DOT**

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.

IATA

Not regulated.

15 REGULATORY INFORMATION**US Federal Regulations****US State Regulations****Inventory Status**

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

16 OTHER INFORMATION**Revision Information:**

Vertical lines in the margin indicate an amendment.

Product name: GEARMASTER LXG 00

Wording of the H-statements in section 2 and 3

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H412	Harmful to aquatic life with long lasting effects.

Revision Date: 18.01.2023

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.