

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: RENOLIT LX-NHU 2 OEM

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricating grease

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

FUCHS LUBRICANTS GERMANY GmbH
Friesenheimer Str. 19
68169 Mannheim

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

US Distributor

Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Contact for request of safety data sheets

E-mail:

Automotive lubricants
Industrial lubricants

CS.Services-FLG@fuchs.com

Telephone:

+49 621 3701-0 (ZENTRALE)

Informing department for safety data sheets

E-mail:

produktsicherheit-FLG@fuchs.com

1.4 US contact telephone :

708-333-8900

Emergency telephone:

800-255-3924

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Health Hazards

Toxic to reproduction

Category 2

Hazard summary

Physical Hazards:

No data available.

Product name: RENOLIT LX-NHU 2 OEM

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H361: Suspected of damaging fertility or the unborn child.

Precautionary Statements

Prevention: P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P281: Use personal protective equipment as required.

Response: P308+P313: IF exposed or concerned: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

General information: Lubricating grease: Thickener system and additives in solvent refined mineral oil.

Chemical name	Identifier	Concentration *	Notes
dilithium sebacate	68815-49-6	1.00 - <5.00%	
Amine aromatic , alkylated	68411-46-1	1.00 - <3.00%	
Zn compound	12001-85-3	0.10 - <1.00%	
Thickener compound for lithium greases	12007-60-2	0.10 - <1.00%	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Product name: RENOLIT LX-NHU 2 OEM

Classification

Chemical name	Identifier	Classification
dilithium sebacate	68815-49-6	Acute Tox. 4;H302
Amine aromatic , alkylated	68411-46-1	Repr. 2;H361f, Aquatic Chronic 3;H412
Zn compound	12001-85-3	Aquatic Chronic 2;H411, Skin Sens. 1B;H317, Eye Irrit. 2;H319
Thickener compound for lithium greases	12007-60-2	Acute Tox. 4;H302, Eye Dam. 1;H318, Repr. 2;H361d

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Product name: RENOLIT LX-NHU 2 OEM

Special fire-fighting procedures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Not required.
6.2 Environmental Precautions:	Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
6.3 Methods and material for containment and cleaning up:	Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
6.4 Reference to other sections:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.
7.2 Conditions for safe storage, including any incompatibilities:	Local regulations concerning handling and storage of waterpolluting products have to be followed.
7.3 Specific end use(s):	No data available.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Exposure Limits

None of the components have assigned exposure limits.
None of the components have assigned exposure limits.

8.2.Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Product name: RENOLIT LX-NHU 2 OEM

Individual protection measures, such as personal protective equipment

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
Eye/face protection:	Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.
Skin protection	
Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: ≥ 480 min Recommended thickness of the material: ≥ 0.38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Not relevant, due to the form of the product.
Thermal hazards:	No data available.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	solid
Form:	Paste
Color:	Light brown
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water)
Drop Point:	250 °C (IP 396)
Boiling Point:	Not applicable
Flash Point:	Not applicable
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)—:	Not applicable for mixtures

Product name: RENOLIT LX-NHU 2 OEM

Flammability Limit - Lower (%)—:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0.90 g/ml (25.00 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
NLGI:	1
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Acute toxicity

Oral

Product:	ATEmix: 52,880.67 mg/kg
-----------------	-------------------------

Product name: RENOLIT LX-NHU 2 OEM

Specified substance(s)

dilithium sebacate	LD 50 (Rat): 2,000 mg/kg (OECD 420)
Amine aromatic , alkylated	LD 50 (Rat): > 5,000 mg/kg (OECD 401)
Zn compound	LC 50 (Rat): 4,920 mg/kg
Thickener compound for lithium greases	LD 50 (Rat): 500 mg/kg (OECD 423)

Dermal**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s)Thickener compound for
lithium greases

Based on available data, the classification criteria are not met.

Inhalation**Product:**

Not classified for acute toxicity based on available data.

Specified substance(s)

dilithium sebacate

No data available.

Zn compound

LC 0 (Rat, 4 h): > 11.6 mg/l

Thickener compound for
lithium greases

No data available.

Skin Corrosion/Irritation:**Product:**

Based on available data, the classification criteria are not met.

Specified substance(s)

dilithium sebacate

OECD 431 Based on available data, the classification criteria are not met.
OECD 439 Based on available data, the classification criteria are not met.Thickener compound for
lithium greasesOECD 431 Based on available data, the classification criteria are not met.
OECD 439 Based on available data, the classification criteria are not met.

Product name: RENOLIT LX-NHU 2 OEM

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

dilithium sebacate OECD 405 (Rabbit): Based on available data, the classification criteria are not met.

Amine aromatic ,
alkylated OECD 405 (Rabbit): Not irritant.

Thickener compound for
lithium greases OECD 437 Not applicable
OECD 405 Corrosive.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

dilithium sebacate , OECD 429 (Mouse)Based on available data, the classification criteria are not met.

Amine aromatic ,
alkylated No sensitizing effect (guinea pig); OECD 406

Thickener compound for
lithium greases Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

In vitro**Specified substance(s)**

dilithium sebacate (OECD 471)
Based on available data, the classification criteria are not met.

Thickener compound for
lithium greases (OECD 473)
Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHA: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product name: RENOLIT LX-NHU 2 OEM

Product: Based on available data, the classification criteria are met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

dilithium sebacate LC 50 (Fish, 96 h): 100 mg/l (OECD 203)

Amine aromatic , LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)
alkylated

Zn compound LC 50 (Fish, 96 h): > 100 mg/l

Thickener compound for LC 50 (Fish, 96 h): 100 mg/l (OECD 203)
lithium greases

Aquatic Invertebrates

Specified substance(s)

dilithium sebacate EC 50 (Water Flea, 48 h): 100 mg/l (OECD 202)

Amine aromatic , EC 50 (Daphnia magna): 51 mg/l (OECD 202)
alkylated

Zn compound EC 50 (Water Flea, 48 h): 35 mg/l

Thickener compound for EC 50 (Water Flea, 48 h): 100 mg/l (OECD 202)
lithium greases

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants

Specified substance(s)

dilithium sebacate EC 50 (Alga, 72 h): 100 mg/l (OECD 201)

Amine aromatic , EC 50 (72 h): > 100 mg/l (OECD 201)
alkylated

Zn compound EC 50 (Alga, 72 h): 4 mg/l

Thickener compound for EC 50 (Alga, 72 h): 100 mg/l (OECD 201)

Product name: RENOLIT LX-NHU 2 OEM

lithium greases

12.2 Persistence and Degradability**Biodegradation**

Product:	Not applicable for mixtures
Specified substance(s) dilithium sebacate	(OECD 301D) Inherently biodegradable
Amine aromatic , alkylated	Not readily degradable.
Thickener compound for lithium greases	Study technically not feasible

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

No data available.

13 Disposal considerations

13.1 Waste treatment methods

General information:	Dispose in accordance with all applicable regulations.
Disposal methods:	Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

14 TRANSPORT INFORMATION

DOT

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.

IATA

Not regulated.

15 REGULATORY INFORMATION

US Federal Regulations**US State Regulations**

Product name: RENOLIT LX-NHU 2 OEM

Inventory Status

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision Date: 25.01.2023

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.