

SAFETY DATA SHEET

Classified in accordance with Health Canada Hazardous Products Regulations (SOR/2015-17)

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: STABYL LT 50

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Recommended use and restriction on use

Recommended use: Lubricating grease

Restrictions on use: No uses advised against identified.

US Distributor

Fuchs Lubricants Co.

17050 Lathrop Avenue

Harvey, IL 60426

(708) 333-8900

(800) 255-3924 24 hrs

Emergency

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier

FUCHS LUBRICANTS GERMANY GmbH

Friesenheimer Str. 19

68169 Mannheim

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

1.4 Emergency telephone number: +49 621 3701-0 (Mo - Fr 08:00 am - 04:00 pm, GMT + 1)

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Health Hazards

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2

Reproductive toxicity Category 2

Specific Target Organ Toxicity - Repeated Exposure Category 2

Environmental Hazards

Chronic hazards to the aquatic environment Category 3

Product name: STABYL LT 50

2.2 Label Elements



Signal Words: Warning

Hazard Statement(s): H315: Causes skin irritation.
H319: Causes serious eye irritation.
H361f: Suspected of damaging fertility.
H373: May cause damage to organs through prolonged or repeated exposure.
H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: P201: Obtain special instructions before use.
P260: Do not breathe dust/fume/gas/mist/vapors/spray.
P264: Wash face, hands and any exposed skin thoroughly after handling.
P273: Avoid release to the environment.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: P332+P313: If skin irritation occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P337+P313: If eye irritation persists: Get medical advice/attention.
P308+P313: IF exposed or concerned: Get medical advice/attention.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

General information: Lubricating grease: Thickener system and additives in synthetic base oil.

Product name: STABYL LT 50

Chemical name	Identifier	Concentration (%w/w)	Notes
Heterocyclic N-compound	95-38-5	1.00 - 5.00	
Amine aromatic , alkylated	68411-46-1	0.10 - 1.00	
phenolic antioxidant	128-37-0	0.10 - 1.00	

A specific chemical identity and/or percentage of composition has been withheld as a trade secret.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
Heterocyclic N-compound	95-38-5	Skin Corr. 1C;H314, Eye Dam. 1;H318, STOT RE 2;H373, Aquatic Acute 1;H400, Aquatic Chronic 1;H410, Acute Tox. 4;H302; M-Factor (aquatic acute): 10; M-Factor (aquatic chronic): 1
Amine aromatic , alkylated	68411-46-1	Repr. 2;H361f, Aquatic Chronic 3;H412
phenolic antioxidant	128-37-0	Aquatic Acute 1;H400, Aquatic Chronic 1;H410; M-Factor (aquatic acute): 1; M-Factor (aquatic chronic): 1

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Skin Contact: Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.

Ingestion: Rinse mouth. Call a POISON CENTER or doctor/ physician if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed: Causes serious eye irritation. Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

Product name: STABYL LT 50

5.1 Extinguishing media

Suitable extinguishing media:

CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media:

Water with a full water jet.

5.2 Special hazards arising from the substance or mixture:

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

6.2 Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up:

Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Avoid contact with eyes. Wash hands thoroughly after handling. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with skin.

7.2 Conditions for safe storage, including any incompatibilities:

Local regulations concerning handling and storage of waterpolluting products have to be followed.

Product name: STABYL LT 50

7.3 Specific end use(s): Not applicable

8 EXPOSURE CONTROLS / PERSONAL PROTECTION
--

8.1.Exposure Limits

None of the components have assigned exposure limits.

8.2.Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Safety glasses (EN 166) recommended during refilling. Avoid contact with eyes. Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile butyl rubber (NBR).
Min. Breakthrough time: ≥ 480 min
Recommended thickness of the material: ≥ 0.38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Not relevant, due to the form of the product.

Thermal hazards:

No data available.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls:

No data available.

Product name: STABYL LT 50

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties**Appearance**

Physical state:	solid
Form:	Paste
Color:	Light brown
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water)
Drop Point:	180 °C (IP 396)
Boiling Point:	Not applicable
Flash Point:	Not applicable
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Explosion Limit - Upper (%):	Not applicable for mixtures
Explosion Limit - Lower (%):	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Relative density:	0.84 g/ml (25 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Auto-ignition temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
NLGI:	2
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification

9.2 Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Product name: STABYL LT 50

11	TOXICOLOGICAL INFORMATION
----	---------------------------

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	Causes skin irritation.
Eye contact:	Causes eye irritation.

Acute toxicity**Oral**

Product:	ATEmix: 63,250 mg/kg
Specified substance(s)	
Heterocyclic N-compound	LD 50 (Rat): 1,265 mg/kg (OECD 401)
Amine aromatic , alkylated	LD 50 (Rat): > 5,000 mg/kg (OECD 401)
phenolic antioxidant	LD 50 (Rat): > 2,930 mg/kg (OECD 401)

Dermal

Product:	Not classified for acute toxicity based on available data.
Specified substance(s)	
phenolic antioxidant	LD 50 (Rat): > 5,000 mg/kg (OECD 402)

Inhalation

Product:	Not classified for acute toxicity based on available data.
----------	--

Skin Corrosion/Irritation:

Product:	Based on available data, the classification criteria are met.
Specified substance(s)	
Heterocyclic N-compound	OECD 404 (Rabbit): Corrosive.

Serious Eye Damage/Eye Irritation:

Product:	Based on available data, the classification criteria are met.
Specified substance(s)	
Heterocyclic N-compound	OECD 405 (Rabbit): Corrosive.
Amine aromatic , alkylated	OECD 405 (Rabbit): Not irritant.

Product name: STABYL LT 50

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

Heterocyclic N-compound No sensitizing effect (guinea pig); OECD 406

Amine aromatic ,
alkylated No sensitizing effect (guinea pig); OECD 406

phenolic antioxidant No sensitizing effect (guinea pig); OECD 406

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

ACGIH: US.ACGIH Threshold Limit Values:

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

General information: Not applicable

12.1 Toxicity**Acute toxicity**

Product: Based on available data, the classification criteria are not met.

Fish**Specified substance(s)**

Heterocyclic N-compound LC 50 (Fish, 96 h): 0.3 mg/l (OECD 203)

Product name: STABYL LT 50

Amine aromatic ,
alkylated LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)

Aquatic Invertebrates**Specified substance(s)**

Heterocyclic N-compound EC 50 (Water Flea, 48 h): 0.136 mg/l (OECD 202)

Amine aromatic ,
alkylated EC 50 (Daphnia magna): 51 mg/l (OECD 202)

phenolic antioxidant EC 50 (Water Flea, 48 h): 0.61 mg/l (OECD 202)

Chronic Toxicity**Product:**

Based on available data, the classification criteria are met.

Aquatic Invertebrates**Specified substance(s)**

phenolic antioxidant NOEC (Water Flea, 21 d): > 0.39 mg/l

Toxicity to Aquatic Plants**Specified substance(s)**

Heterocyclic N-compound EC 50 (Alga, 72 h): 0.03 mg/l (OECD 201)
NOEC (Alga, 72 h): 0.11 mg/l

Amine aromatic ,
alkylated EC 50 (72 h): > 100 mg/l (OECD 201)

12.2 Persistence and Degradability**Biodegradation****Product:**

Not applicable for mixtures

Specified substance(s)

Heterocyclic N-compound (OECD 301B) The product is not biodegradable.

Amine aromatic ,
alkylated Not readily degradable.

phenolic antioxidant 30 % (OECD 302C) Not readily degradable.

12.3 Bioaccumulative potential**Product:**

Not applicable for mixtures

Specified substance(s)

phenolic antioxidant May be accumulated in organism

12.4 Mobility in soil:**Product:**

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

Product name: STABYL LT 50

13 Disposal considerations**13.1 Waste treatment methods**

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

14 TRANSPORT INFORMATION**TDG**

Not Regulated.

IMDG - International Maritime Dangerous Goods Code

Not Regulated.

IATA

Not Regulated.

Transport in bulk according to Annex II of MARPOL and the IBC Code: Not applicable.

15 REGULATORY INFORMATION**Inventory Status**

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision Date: 07.02.2024

Product name: STABYL LT 50

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.