

US Distributor

# SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

## PRODUCT AND COMPANY IDENTIFICATION

### **1.1 Product identifier**

1

Product name: TITAN SUPERGEAR MC 80W-140

Other means of identification: For further information, please refer to section 9 of the SDS.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against Identified uses: Lubricant Uses advised against: No uses advised against identified.

# 1.3 Details of the supplier of the safety data sheet

.3 Details of the supplier of the safety data sheet		Fuchs Lubricants Co.
Manufacturer / Supplier	FUCHS LUBRICANTS GERMANY GmbH Friesenheimer Str. 19 68169 Mannheim	17050 Lathrop Avenue Harvey, IL 60426 (708) 333-8900
Telephone: Fax:	+49 621 3701-0 (ZENTRALE) +49 621 3701-570	(800) 255-3924 24 hrs Emergency

### Contact for request of safety data sheets

E-mail:	Automotive lubricants Industrial lubricants	CS.Services-FLG@fuchs.com
Telephone:	+49 621 3701-0 (ZENTRALE)	

### Informing department for safety data sheets

E-mail:	produktsicherheit-FLG@fuchs.com
1.4 US contact telephone :	708-333-8900
Emergency telephone:	800-255-3924

#### 2 **HAZARDS IDENTIFICATION**

### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous and does not need to be labelled according to the legislation in force.

Hazard summary	
Physical Hazards:	No data available.

#### 2.2 Label Elements Not applicable





## Product name: TITAN SUPERGEAR MC 80W-140

2.3 Other hazards:	By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.
Unknown toxicity:	Due to information available product does not contain any ingredients of unknown toxicity.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

## 3.2 Mixtures

Chemical name	Identifier	Concentration *	Notes
organic Polysulphide	68937-96-2	1.00 - <5.00%	
dithiophosphoric acid derivative	71888-91-0	1.00 - <2.50%	
Magnesium metaborate	13703-82-7	0.10 - <1.00%	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

### Classification

Chemical name	Identifier	Classification
organic Polysulphide	68937-96-2	Skin Sens. 1B;H317, Aquatic Chronic 3;H412
dithiophosphoric acid derivative		Acute Tox. 4;H302, Skin Sens. 1B;H317, Eye Irrit. 2;H319, Aquatic Chronic 2;H411
Magnesium metaborate	13703-82-7	Skin Sens. 1B;H317

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

# 4 FIRST AID MEASURES

General:	Instantly remove any clothing soiled by the product.
4.1 Description of first aid measu Inhalation:	res Supply fresh air; consult doctor in case of symptoms.
Eye contact:	Promptly wash eyes with plenty of water while lifting the eye lids.
Skin Contact:	Wash with soap and water.
Ingestion:	Rinse mouth thoroughly.
4.2 Most important symptoms and effects, both acute and delayed:	May cause skin and eye irritation.



# Product name: TITAN SUPERGEAR MC 80W-140

4.3 Indication of any immediate	Get medical attention if symptoms occur.
medical attention and special	
treatment needed	

## SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media:	CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added
Unsuitable extinguishing media:	Water with a full water jet.
5.2 Special hazards arising from the substance or mixture:	During fire, gases hazardous to health may be formed.
5.3 Advice for firefighters Special fire fighting procedures:	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
Special protective equipment for fire-fighters:	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
SECTION 6: Accidental release m	easures
6.1 Personal precautions, protective equipment and emergency procedures:	In case of spills, beware of slippery floors and surfaces.
6.2 Environmental Precautions:	Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.
6.3 Methods and material for containment and cleaning up:	Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
6.4 Reference to other sections:	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

[



# Product name: TITAN SUPERGEAR MC 80W-140

# SECTION 7: Handling and storage:

7.1 Precautions for safe handling:	Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
7.2 Conditions for safe storage, including any incompatibilities:	Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.
7.3 Specific end use(s):	No data available.

# 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1.Exposure Limits

Chemical name	Туре	Exposure Limit Values	Source
Unalloyed mineral oil - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2014)
Unalloyed mineral oil	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Unalloyed mineral oil - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Unalloyed mineral oil	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Unalloyed mineral oil - Mist.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)

## 8.2.Exposure controls

Appropriate engineering controls:	Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measu	res, such as personal protective equipment

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166) recommended during refilling.



# Product name: TITAN SUPERGEAR MC 80W-140

Skin protection Hand Protection:	Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0.38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.
Thermal hazards:	No data available.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

# 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and cher	nical propertiesAppearance
Physical state:	liquid
Form:	liquid
Color:	Dark yellow
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	substance/mixture is non-soluble (in water)
Freezing point:	Not applicable for mixtures
Boiling Point:	Value not relevant for classification
Flash Point:	220 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)–:	Not applicable for mixtures
Flammability Limit - Lower (%)–:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Relative vapor density:	Not applicable for mixtures
Density:	0.87 g/ml (15.00 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures



# Product name: TITAN SUPERGEAR MC 80W-140

Autoignition Temperature: Decomposition Temperature: Kinematic viscosity: Explosive properties: Oxidizing properties: 9.2 Other information Value not relevant for classification Value not relevant for classification 269 mm2/s (40.00 °C) Value not relevant for classification Value not relevant for classification No data available.

# SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

# 11 TOXICOLOGICAL INFORMATION

Information on likely routes of Inhalation:	of exposure No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Acute toxicity	
Oral Product: Specified substance(s) organic Polysulphide	ATEmix: 30,959 mg/kg LD 50 (Rat): 6,500 mg/kg
Dermal Product:	Not classified for acute toxicity based on available data.
Inhalation Product:	Not classified for acute toxicity based on available data.



#### Product name: TITAN SUPERGEAR MC 80W-140 m/l==! -. . . . .

	Skin Corrosion/Irritation: Product:	Based on available data, the classification criteria are not met.
	Serious Eye Damage/Eye Irri Product:	itation: Based on available data, the classification criteria are not met.
	Respiratory or Skin Sensitiza Product:	ation: Experimental data has shown that the concentration of potentially sensitizing components present in this product does not induce skin sensitization.
	Germ Cell Mutagenicity Product:	Based on available data, the classification criteria are not met.
	Carcinogenicity Product:	Based on available data, the classification criteria are not met.
	IARC: IARC Monographs o	n the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified
	NTP: US. National Toxicolo	ogy Program (NTP) Report on Carcinogens: No carcinogenic components identified
	OSHASP: US. OSHA Speci	fically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified
	Reproductive toxicity Product:	Based on available data, the classification criteria are not met.
	Specific Target Organ Toxici Product:	ity - Single Exposure Based on available data, the classification criteria are not met.
	Specific Target Organ Toxici Product:	ity - Repeated Exposure Based on available data, the classification criteria are not met.
	Aspiration Hazard Product:	Based on available data, the classification criteria are not met.
12	ECOLOGICAL INFORMATIO	N
12.1	Toxicity	
	Acute toxicity Product:	Based on available data, the classification criteria are not met.
	Fish Specified substance(s)	

LC 50 (Fish, 96 h): 8.5 mg/l

12



# Product name: TITAN SUPERGEAR MC 80W-140

Aquatic Invertebrates Specified substance(s) organic Polysulphide	EC 50 (Water Flea, 48 h): 63 mg/l (OECD 202)
dithiophosphoric acid derivative	EC 50 (Water Flea, 48 h): 91.4 mg/l
Chronic ToxicityProduct:	Based on available data, the classification criteria are not met.
Toxicity to Aquatic Plants Specified substance(s) organic Polysulphide	EC 50 (Alga, 72 h): > 101 mg/l (OECD 201)
dithiophosphoric acid derivative	NOEC (Alga, 96 h): 1.7 mg/l
12.2 Persistence and Degradabili	ty
Biodegradation Product: Specified substance(s)	Not applicable for mixtures
organic Polysulphide	13 % (28 d, OECD 301B) Not readily degradable.
dithiophosphoric acid derivative	7.4 % (28 d, OECD 301B) Not easily biodegradable
12.3 Bioaccumulative potential Product:	Not applicable for mixtures

12.4 Mobility in soil: Product:	Not applicable for mixtures
12.5 Results of PBT and vPvB assessment:	The product does not contain any substances fulfilling the PBT/vPvB criteria.

No data available.

# 13 Disposal considerations

12.6 Other adverse effects:

# 13.1 Waste treatment methods

General information:	Dispose in accordance with all applicable regulations.
Disposal methods:	Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

# 14 TRANSPORT INFORMATION

# DOT

Not regulated.



## Product name: TITAN SUPERGEAR MC 80W-140

#### IMDG - International Maritime Dangerous Goods Code Not regulated.

#### ΙΑΤΑ

Not regulated.

### 15 REGULATORY INFORMATION

### **US Federal Regulations**

### **US State Regulations**

#### **Inventory Status**

TSCA	On or in compliance with the inventory
DSL	Q (quantity restricted)

### 16 OTHER INFORMATION

### **Revision Information:**

Vertical lines in the margin indicate an amendment.

### Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision Date:** 12.01.2022 **Disclaimer:** The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.