

## SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifier

**Product name:** GEARMaster PGP 150

**Other means of identification:** For further information, please refer to section 9 of the SDS.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricant

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer

FUCHS LUBRITECH GmbH  
Werner-Heisenberg-Straße 1  
67661 Kaiserslautern/Germany

Telephone: +49 (0) 6301 3206-0  
Fax: +49 (0) 6301 3206-940

##### Contact Person:

FUCHS LUBRITECH GmbH - Product Safety Management  
Telephone: +49 (0) 6301 3206-0  
Fax: +49 (0) 6301 3206-940  
E-mail: INFO@FUCHS-LUBRITECH.DE

**1.4 US contact telephone :** 708-333-8900  
**Emergency telephone:** 800-255-3924

### 2 HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous and does not need to be labelled according to the legislation in force.

##### Hazard summary

**Physical Hazards:** No data available.

#### 2.2 Label Elements

Not applicable

#### 2.3 Other hazards:

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

**Unknown toxicity:** Due to information available product does not contain any ingredients of unknown toxicity.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

**Product name:** GEARMASTER PGP 150

**General information:** Mixture based on polyglycole. Mixture of synthetic base oils with additives.

Chemical name	Identifier	Concentration *	Notes
Amine aromatic , alkylated	68411-46-1	1.00 - <5.00%	
Phenol derivative	35074-77-2	1.00 - <5.00%	
Oleic acid derivative	110-25-8	0.10 - <1.00%	
Diphenylamine	122-39-4	0.00 - <0.10%	
Xylene	1330-20-7	0.00 - <0.10%	
Benzene derivative	100-41-4	0.00 - <0.10%	
Toluene	108-88-3	0.00 - <0.10%	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

### Classification

Chemical name	Identifier	Classification
Amine aromatic , alkylated	68411-46-1	Aquatic Chronic 3;H412
Phenol derivative	35074-77-2	Aquatic Chronic 4;H413
Oleic acid derivative	110-25-8	Eye Dam. 1;H318, Aquatic Acute 1;H400, Acute Tox. 4;H332, Skin Irrit. 2;H315
Diphenylamine	122-39-4	Acute Tox. 3;H301, Acute Tox. 3;H311, Acute Tox. 3;H331, STOT RE 2;H373, Aquatic Acute 1;H400, Aquatic Chronic 1;H410
Xylene	1330-20-7	Flam. Liq. 3;H226, Acute Tox. 4;H312, Acute Tox. 4;H332, Skin Irrit. 2;H315
Benzene derivative	100-41-4	Flam. Liq. 2;H225, Acute Tox. 4;H332
Toluene	108-88-3	Flam. Liq. 2;H225, Asp. Tox. 1;H304, Repr. 2;H361d, STOT RE 2;H373, Skin Irrit. 2;H315, STOT SE 3;H336

## 4 FIRST AID MEASURES

**General:** Instantly remove any clothing soiled by the product.

### 4.1 Description of first aid measures

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause skin and eye irritation.

**4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

Product name: GEARMASTER PGP 150

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:** Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture:** During fire, gases hazardous to health may be formed.

### 5.3 Advice for firefighters

**Special fire fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures:** In case of spills, beware of slippery floors and surfaces.

**6.2 Environmental Precautions:** Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

**6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

## SECTION 7: Handling and storage:

**7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

---

**Product name:** GEARMASTER PGP 150

---

**7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed.

**7.3 Specific end use(s):** No data available.

<b>8 EXPOSURE CONTROLS / PERSONAL PROTECTION</b>
--

**8.1.Exposure Limits**

None of the components have assigned exposure limits.

**8.2.Exposure controls**

**Appropriate engineering controls:**

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information:**

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

**Eye/face protection:**

Safety glasses (EN 166) recommended during refilling.

**Skin protection**

**Hand Protection:**

Material: Nitrile-butadiene rubber (NBR).  
Min. Breakthrough time:  $\geq 480$  min  
Recommended thickness of the material:  $\geq 0.38$  mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Other:**

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

**Respiratory Protection:**

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

**Thermal hazards:**

No data available.

**Hygiene measures:**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

**Product name:** GEARMASTER PGP 150

**Environmental Controls:** No data available.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

<b>Physical state:</b>	liquid
<b>Form:</b>	liquid
<b>Color:</b>	Yellow
<b>Odor:</b>	Characteristic
<b>Odor Threshold:</b>	Not applicable for mixtures
<b>pH:</b>	not applicable
<b>Freezing point:</b>	Not applicable for mixtures
<b>Boiling Point:</b>	Value not relevant for classification
<b>Flash Point:</b>	240 °C (DIN EN ISO 2592)
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	Value not relevant for classification
<b>Flammability Limit - Upper (%)–:</b>	Not applicable for mixtures
<b>Flammability Limit - Lower (%)–:</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Vapor density (air=1):</b>	Not applicable for mixtures
<b>Density:</b>	1.05 g/ml (15.00 °C) (DIN 51757)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Soluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Autoignition Temperature:</b>	Value not relevant for classification
<b>Decomposition Temperature:</b>	Value not relevant for classification
<b>Kinematic viscosity:</b>	150 mm <sup>2</sup> /s (40 °C, DIN 51562)
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification

**9.2 Other information** No data available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

---

**Product name:** GEARMASTER PGP 150

---

<b>11 TOXICOLOGICAL INFORMATION</b>
-------------------------------------

**Information on likely routes of exposure**

<b>Inhalation:</b>	No data available.
<b>Ingestion:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.

**Acute toxicity**

**Oral**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

Phenol derivative	LD 50 (Rat): > 5,000 mg/kg
Oleic acid derivative	LD 50 (Rat): 9,200 mg/kg
Xylene	LD 50 (Rat): 8,700 mg/kg
Benzene derivative	LD 50 (Rat): 3,500 mg/kg

**Dermal**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

Xylene	LD 50 (Rabbit): 2,000 mg/kg
Benzene derivative	LD 50 (Rabbit): 17,800 mg/kg
Toluene	LD 50 (Rabbit): 12,124 mg/kg

**Inhalation**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

Oleic acid derivative	LC 50 (Rat, 4 h): 1.37 mg/l Dusts, mists and fumes
Xylene	LC 50 (Rat, 4 h): 6,350 mg/l Vapour

---

**Product name:** GEARMASTER PGP 150

---

**Skin Corrosion/Irritation:**

**Product:** Based on available data, the classification criteria are not met.

**Specified substance(s)**

Amine aromatic ,  
alkylated                      OECD 404 (Rabbit): Not irritant.

Oleic acid derivative                      OECD 404 (Rabbit): Irritating.

**Serious Eye Damage/Eye Irritation:**

**Product:** Based on available data, the classification criteria are not met.

**Specified substance(s)**

Amine aromatic ,  
alkylated                      OECD 405 (Rabbit): Not irritant.

**Respiratory or Skin Sensitization:**

**Product:** Skin sensitizer: Based on available data, the classification criteria are not met.  
Respiratory sensitizer: Based on available data, the classification criteria are not met.

**Specified substance(s)**

Amine aromatic ,  
alkylated                      No sensitizing effect (guinea pig); OECD 406

Phenol derivative                      (Guinea Pig)Not a skin sensitizer.

Oleic acid derivative                      No sensitizing effect (guinea pig); OECD 406

**Germ Cell Mutagenicity**

**Product:** Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:** Based on available data, the classification criteria are not met.

**IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**NTP: US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Reproductive toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Product name:** GEARMASTER PGP 150

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Aspiration Hazard**

**Product:** Based on available data, the classification criteria are not met.

**12 ECOLOGICAL INFORMATION**

**12.1 Toxicity**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Fish**

**Specified substance(s)**

Phenol derivative LC 50 (Fish, 96 h): > 101 mg/l (OECD 203)

Oleic acid derivative LC 50 (Fish, 96 h): 3.2 - 4.6 mg/l

**Aquatic Invertebrates**

**Specified substance(s)**

Amine aromatic ,  
alkylated EC 50 (Water Flea, 48 h): 51 mg/l

Phenol derivative EC 50 (Water Flea, 24 h): > 101 mg/l (OECD 202)

Oleic acid derivative EC 50 (Water Flea, 48 h): 0.53 mg/l

Diphenylamine EC 50 (Water Flea, 48 h): 0.31 mg/l

**Chronic ToxicityProduct:** Based on available data, the classification criteria are not met.

**Toxicity to Aquatic Plants**

**Specified substance(s)**

Phenol derivative EC 50 (Alga, 72 h): > 101 mg/l (OECD 201)

Oleic acid derivative EC 50 (Alga, 72 h): 5.1 mg/l

Diphenylamine EC 50 (Alga, 72 h): 1.51 mg/l

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures

**Specified substance(s)**

Phenol derivative The product is slightly biodegradable.

Oleic acid derivative 85 % (28 d, OECD 301B)

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

---

**Product name:** GEARMASTER PGP 150

---

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Other adverse effects:**

No data available.

<b>13 Disposal considerations</b>
-----------------------------------

**13.1 Waste treatment methods**

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

<b>14 TRANSPORT INFORMATION</b>
---------------------------------

**DOT**

Not regulated.

**IMDG - International Maritime Dangerous Goods Code**

Not regulated.

**IATA**

Not regulated.

<b>15 REGULATORY INFORMATION</b>
----------------------------------

**US Federal Regulations**

**US State Regulations**

**Inventory Status**

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

<b>16 OTHER INFORMATION</b>
-----------------------------

**Revision Information:**

Vertical lines in the margin indicate an amendment.

---

**Product name:** GEARMASTER PGP 150

---

**Wording of the H-statements in section 2 and 3**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Revision Date:**

16.04.2018

**Disclaimer:**

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.