

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: GLEITMO 805

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer

FUCHS LUBRITECH GmbH
Werner-Heisenberg-Straße 1
67661 Kaiserslautern/Germany

US Distributor

Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Telephone:

+49 (0) 6301 3206-0

Fax:

+49 (0) 6301 3206-940

Contact Person:

FUCHS LUBRITECH GmbH - Product Safety Management

Telephone:

+49 (0) 6301 3206-0

Fax:

+49 (0) 6301 3206-940

E-mail:

INFO@FUCHS-LUBRITECH.DE

1.4 US contact telephone :

708-333-8900

Emergency telephone:

800-255-3924

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Environmental Hazards

Chronic hazards to the aquatic environment Category 3

Hazard summary

Physical Hazards:

No data available.

2.2 Label Elements

Hazard Statement(s): H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P273: Avoid release to the environment.

Product name: GLEITMO 805

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

General information: Mixture of the substances listed below with harmless additions.

Chemical name	Identifier	Concentration *	Notes
base oil ,VHVI	72623-87-1	20.00 - <50.00%	
Lime hydrate	1305-62-0	10.00 - <25.00%	
inorganic Zink salt	7446-26-6	2.50 - <5.00%	
Zn compound	1314-13-2	0.10 - <0.25%	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Identifier	Classification
base oil ,VHVI	72623-87-1	Asp. Tox. 1;H304
Lime hydrate	1305-62-0	Eye Dam. 1;H318, STOT SE 3;H335, Skin Irrit. 2;H315
inorganic Zink salt	7446-26-6	Aquatic Chronic 2;H411
Zn compound	1314-13-2	Aquatic Acute 1;H400, Aquatic Chronic 1;H410

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Get medical attention if any discomfort continues. Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: No data available.

Product name: GLEITMO 805

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up: Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections: See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.

Product name: GLEITMO 805

7.2 Conditions for safe storage, including any incompatibilities: Local regulations concerning handling and storage of waterpolluting products have to be followed.

7.3 Specific end use(s): Not applicable

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Exposure Limits

Chemical name	Type	Exposure Limit Values		Source
base oil ,VHVI - Inhalable fraction.	TWA		5 mg/m ³	US. ACGIH Threshold Limit Values (03 2014)
base oil ,VHVI	PEL	500 ppm	2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
base oil ,VHVI - Mist.	PEL		5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
base oil ,VHVI	TWA	400 ppm	1,600 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
base oil ,VHVI - Mist.	TWA		5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Residual oils (petroleum), solvent-refined - Inhalable fraction.	TWA		5 mg/m ³	US. ACGIH Threshold Limit Values (03 2014)
Residual oils (petroleum), solvent-refined	PEL	500 ppm	2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Residual oils (petroleum), solvent-refined - Mist.	PEL		5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Residual oils (petroleum), solvent-refined	TWA	400 ppm	1,600 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Residual oils (petroleum), solvent-refined - Mist.	TWA		5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates (petroleum), solvent-refined heavy paraffinic	PEL	500 ppm	2,000 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Distillates (petroleum), solvent-refined heavy paraffinic - Mist.	PEL		5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Distillates (petroleum), solvent-refined heavy paraffinic	TWA	400 ppm	1,600 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates (petroleum), solvent-refined heavy paraffinic - Mist.	TWA		5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Distillates (petroleum), solvent-refined heavy paraffinic - Inhalable fraction.	TWA		5 mg/m ³	US. ACGIH Threshold Limit Values (02 2012)

8.2.Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Product name: GLEITMO 805

Individual protection measures, such as personal protective equipment

General information:	Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
Eye/face protection:	Safety glasses (EN 166) recommended during refilling.
Skin protection	
Hand Protection:	Avoid long-term and repeated skin contact. Protective gloves, where permitted in acc. to safety directions.
Other:	Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.
Respiratory Protection:	Not relevant, due to the form of the product.
Thermal hazards:	No data available.
Hygiene measures:	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.
Environmental Controls:	No data available.

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	solid
Form:	Paste
Color:	Light brown
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	Not applicable
Melting Point:	Not applicable for mixtures
Boiling Point:	Not applicable
Flash Point:	Not applicable
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%)—:	Not applicable for mixtures
Flammability Limit - Lower (%)—:	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	1.10 g/cm ³ (15 °C)
Solubility(ies)	

Product name: GLEITMO 805

Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Flow time:	Value not relevant for classification
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s) base oil ,VHVI

LD 50 (Rat): > 5,000 mg/kg

Product name: GLEITMO 805

Dermal

Product:

Not classified for acute toxicity based on available data.

Inhalation

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

base oil ,VHVI

LC 50 (Rat, 4 h): > 5.53 mg/l

Zn compound

LC 50 (Rat, 4 h): 5.7 mg/l

Skin Corrosion/Irritation:

Product:

Not irritant. Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation:

Product:

No irritant effect at the eyes of rabbits (OECD 405).

Respiratory or Skin Sensitization:

Product:

Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product:

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product:

Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product:

Based on available data, the classification criteria are not met.

Product name: GLEITMO 805

Aspiration Hazard

Product:

Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Acute toxicity

Product:

Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Lime hydrate

LC 50 (Fish, 96 h): 50.6 mg/l

Aquatic Invertebrates

Specified substance(s)

Lime hydrate

EC 50 (Water Flea, 48 h): 49.1 mg/l

inorganic Zink salt

EC 50 (Water Flea, 48 h): 26 mg/l

Zn compound

EC 50 (Water Flea, 48 h): 2.2 mg/l

Chronic ToxicityProduct:

Based on available data, the classification criteria are met.

Toxicity to Aquatic Plants

Specified substance(s)

Lime hydrate

EC 50 (Alga, 72 h): 184.57 mg/l

Zn compound

EC 50 (Alga, 72 h): 0.17 mg/l

12.2 Persistence and Degradability

Biodegradation

Product:

Not applicable for mixtures

12.3 Bioaccumulative potential

Product:

Not applicable for mixtures

12.4 Mobility in soil:

Product:

Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

13 Disposal considerations

13.1 Waste treatment methods

General information:

Dispose in accordance with all applicable regulations.

Product name: GLEITMO 805

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

14 TRANSPORT INFORMATION

DOT

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.

IATA

Not regulated.

15 REGULATORY INFORMATION

US Federal Regulations

US State Regulations

Inventory Status

DSL	On or in compliance with the inventory
NDSL	Not in compliance with the inventory.
TSCA	On or in compliance with the inventory

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision Date: 23.05.2018

Product name: GLEITMO 805

Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.