



SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: gleitmo 980 SPRAY

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

| Manufacturer / Supplier | FUCHS LUBRITECH GmbH Werner-Heisenberg-Straße 1 67661 Kaiserslautern/Germany |
|-------------------------|------------------------------------------------------------------------------------|
| Telephone: | +49 (0) 6301 3206-0 |
| Fax: | +49 (0) 6301 3206-940 |
| Contact Person: | FUCHS LUBRITECH GmbH - Product Safety Management |
| Telephone: | +49 (0) 6301 3206-0 |
| Fax: | +49 (0) 6301 3206-940 |
| E-mail: | reach@fuchs-lubritech.de |

1.4 Emergency telephone number: +49 (0) 6301 3206-0

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

| Physical Hazards | | |
|-------------------|------------|-----------------------------------------------------------------------------------------|
| Flammable aerosol | Category 1 | H222: Extremely flammable aerosol. H229: Pressurized container: May burst if heated. |
| Hererd cummers | | |

| Hazard summary | |
|-------------------|--------------------|
| Physical Hazards: | Flammable aerosol. |

2.2 Label Elements





| Signal Words: | Danger | |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Hazard Statement(s): | H222: Extremely flammable aerosol. H229: Pressurized container: May burst if heated. | |
| Precautionary Statement | | |
| Prevention: | P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. | |
| Storage: | P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. | |
| 2.3 Other hazards: | The product may not be released into the environment without control. By handling of chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. | |

SECTION 3: Composition/information on ingredients

3.2 Mixtures

General information:

Mixture of components with propellant in aerosol can.

| Chemical name | Identifier | Concentration * | REACH Registration No. | Notes |
|-----------------------------|-------------------|-----------------|------------------------|-------|
| Butane | EINECS: 203-448-7 | 0,00 - <100,00% | 01-2119474691-32 | |
| Propane | EINECS: 200-827-9 | 0,00 - <100,00% | 01-2119486944-21 | |
| Hydrocarbons, low viscosity | EINECS: 265-150-3 | 0,00 - <5,00% | 01-2119457273-39 | |
| Hydrocarbons, low viscosity | EC: 927-241-2 | 0,00 - <5,00% | 01-2119471843-32 | |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.





Classification

| Chemical name | Identifier | Classifi | cation |
|-----------------------------|-------------------|----------|--------------------------------------------------------------------------------|
| Butane | EINECS: 203-448-7 | CLP: F | Flam. Gas 1;H220, Press. Gas H280 |
| Propane | EINECS: 200-827-9 | CLP: F | Flam. Gas 1;H220, Press. Gas H280 |
| Hydrocarbons, low viscosity | EINECS: 265-150-3 | | Asp. Tox. 1;H304, Flam. Liq. 3;H226, Aquatic Chronic 3;H412 |
| Hydrocarbons, low viscosity | EC: 927-241-2 | | Flam. Liq. 3;H226, Asp. Tox. 1;H304, STOT SE 3;H336, Aquatic Chronic 3;H412 |

CLP: Regulation No. 1272/2008.

For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

| General: | Instantly remove any clothing soiled by the product. |
|--------------------------------------------------------------------------------------|-------------------------------------------------------------------------|
| 4.1 Description of first aid measu Inhalation: | Ires Supply fresh air; consult doctor in case of symptoms. |
| Eye contact: | Promptly wash eyes with plenty of water while lifting the eye lids. |
| Skin Contact: | Wash with soap and water. |
| Ingestion: | Rinse mouth thoroughly. |
| 4.2 Most important symptoms and effects, both acute and delayed: | Dizziness Freeze burns |
| 4.3 Indication of any immediate medical attention and special treatment needed | Get medical attention if symptoms occur. |
| SECTION 5: Firefighting measures | S |
| General Fire Hazards: | Use water spray to keep fire-exposed containers cool. Fight fire from a |

| General Fire Hazards: | Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk. |
|------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5.1 Extinguishing media | |
| Suitable extinguishing media: | CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added |
| Unsuitable extinguishing media: | Water with a full water jet. |
| 5.2 Special hazards arising from the substance or mixture: | Danger of explosion with aerosol cans. |

5.3 Advice for firefighters





| FIGULE Hame. gleiting 300 SFIAT | |
|--------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Special fire fighting procedures: | Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains. |
| Special protective equipment for fire-fighters: | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| SECTION 6: Accidental release m | easures |
| 6.1 Personal precautions, protective equipment and emergency procedures: | Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep away from sources of ignition - No smoking. |
| 6.2 Environmental Precautions: | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. |
| 6.3 Methods and material for containment and cleaning up: | Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations. |
| 6.4 Reference to other sections: | See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal. |
| SECTION 7: Handling and storage | e: |
| 7.1 Precautions for safe handling: | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas. |
| 7.2 Conditions for safe storage, including any incompatibilities: | Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces No smoking. |
| 7.3 Specific end use(s): | not applicable |

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

8.2 Exposure controls





| Appropriate engineering controls: | Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Individual protection measure | es, such as personal protective equipment |
| General information: | Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products. |
| Eye/face protection: | Safety glasses (EN 166) recommended during refilling. |
| Skin protection Hand Protection: | Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: >= 480 min Recommended thickness of the material: >= 0,38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to |
| | safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. |
| Other: | Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing. |
| Respiratory Protection: | Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol. |
| Thermal hazards: | Not known. |
| Hygiene measures: | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. |
| Environmental Controls: | No data available. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Appearance | |
|-----------------|-----------------------------|
| Physical state: | Aerosols |
| Form: | Aerosols |
| Color: | Colorless |
| Odor: | Characteristic |
| Odor Threshold: | Not applicable for mixtures |
| pH: | not applicable |
| Freezing point: | Not applicable for mixtures |
| | |

LUBRITECH Special Application Lubricants



Product name: gleitmo 980 SPRAY

| Boiling Point: | Value not relevant for classification |
|------------------------------------------|---------------------------------------|
| Flash Point: | < 0 °C |
| Evaporation Rate: | Not applicable for mixtures |
| Flammability (solid, gas): | Value not relevant for classification |
| Flammability Limit - Upper (%)–: | Not applicable for mixtures |
| Flammability Limit - Lower (%)–: | Not applicable for mixtures |
| Vapor pressure: | Not applicable for mixtures |
| Vapor density (air=1): | Not applicable for mixtures |
| Density: | 0,60 g/cm3 |
| Solubility(ies) | |
| Solubility in Water: | No data available. |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | Not applicable for mixtures |
| Autoignition Temperature: | Value not relevant for classification |
| Decomposition Temperature: | Value not relevant for classification |
| Flow time | Value not relevant for classification |
| Explosive properties: | Value not relevant for classification |
| Oxidizing properties: | Value not relevant for classification |
| 9.2 Other information | No data available. |

SECTION 10: Stability and reactivity

| 10.1 Reactivity: | Stable under normal use conditions. |
|-------------------------------------------|-------------------------------------------------------------------------------------------------|
| 10.2 Chemical Stability: | Stable under normal use conditions. |
| 10.3 Possibility of hazardous reactions: | Stable under normal use conditions. |
| 10.4 Conditions to avoid: | Stable under normal use conditions. |
| 10.5 Incompatible Materials: | Strong oxidizing substances. Strong acids. Strong bases. |
| 10.6 Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Oral Product:

Not classified for acute toxicity based on available data.





| adde name: giolano oco el taxi | |
|-----------------------------------------------------------------|-------------------------------------------------------------------------------------------|
| Specified substance(s) Hydrocarbons, low viscosity | LD 50 (Rat): > 15.000 mg/kg |
| Hydrocarbons, low viscosity | LD 50 (Rat): > 5.001 mg/kg (OECD 401) |
| Dermal Product: | Net cleasified for equite towicity becaute on evoluble date |
| | Not classified for acute toxicity based on available data. |
| Specified substance(s) Hydrocarbons, low viscosity | LD 50 (Rabbit): > 3.160 mg/kg |
| Hydrocarbons, low viscosity | LD 50 (Rabbit): > 5.001 mg/kg (OECD 402) |
| Inhalation | |
| Product: | |
| Troduct. | Not classified for acute toxicity based on available data. |
| Specified substance(s) | |
| Butane | LC 50 (Rat, 4 h): 658 mg/l Gas |
| Skin Corrosion/Irritation: | |
| Product: | Based on available data, the classification criteria are not met. |
| Specified substance(s) | |
| Hydrocarbons, low | OECD 404 |
| viscosity | Prolonged or repeated contact: Slightly irritating. |
| Serious Eye Damage/Eye Irr | itation. |
| Product: | Based on available data, the classification criteria are not met. |
| Respiratory or Skin Sensitiz | |
| Product: | Skin sensitizer: Based on available data, the classification criteria are not |
| | met. |
| | Respiratory sensitizer: Based on available data, the classification criteria are not met. |
| | |
| Germ Cell Mutagenicity | |
| Product: | Based on available data, the classification criteria are not met. |
| | |
| Carcinogenicity | |
| Product: | Based on available data, the classification criteria are not met. |
| Reproductive toxicity | |
| Product: | Based on available data, the classification criteria are not met. |
| Specific Target Organ Toxicity - Single Exposure | |
| Product: | Based on available data, the classification criteria are not met. |
| | |





| Specific Target Organ Toxici | tv - Reneated Exposure |
|----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Product: | Based on available data, the classification criteria are not met. |
| Aspiration Hazard Product: | Based on available data, the classification criteria are not met. |
| Other Adverse Effects: | No data available. |
| ECTION 12: Ecological information | on |
| 2.1 Toxicity | |
| Acute toxicity Product: | Based on available data, the classification criteria are not met. |
| Fish Specified substance(s) Hydrocarbons, low viscosity | LC 50 (Fish, 96 h): > 1.000 mg/l |
| Hydrocarbons, low viscosity | LC 50 (Fish, 96 h): 10 - 30 mg/l |
| Aquatic Invertebrates Specified substance(s) Hydrocarbons, low viscosity | EC 50 (Water Flea, 48 h): > 1.000 mg/l |
| Hydrocarbons, low viscosity | EC 50 (Water Flea, 48 h): 22 - 46 mg/l |
| Chronic ToxicityProduct: | Based on available data, the classification criteria are not met. |
| Toxicity to Aquatic Plants Specified substance(s) Hydrocarbons, low viscosity | EC 50 (Alga): > 1.000 mg/l |
| Hydrocarbons, low viscosity | EC 50 (Alga, 72 h): > 1.000 mg/l |
| 2.2 Persistence and Degradabili | ty |
| Biodegradation Product: Specified substance(s) Hydrocarbons, low viscosity | Not applicable for mixtures 89 % (28 d) The product is easily biodegradable. |
| 2.3 Bioaccumulative Potential Product: | Not applicable for mixtures |
| 2.4 Mobility in Soil: Product: | Not applicable for mixtures |





- **12.5 Results of PBT and vPvB** The product does not contain any substances fulfilling the PBT/vPvB criteria. assessment:
- **12.6 Other Adverse Effects:** No data available.

| SECTION 13: Disposal considerations | | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| 13.1 Waste treatment methods | | |
| General information: | Dispose in accordance with all applicable regulations. | |
| Disposal methods: | Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed. | |
| European Waste Codes | | |
| | 16 05 04*: Gases in pressure containers (including halons) containing dangerous substances. | |

SECTION 14: Transport information

ADR/RID

| ABIGICIB | |
|---------------------------------------------------------------------------------------------------------|----------------------|
| 14.1 UN Number: 14.2 UN Proper Shipping Name: | UN 1950 AEROSOLS |
| 14.3 Transport Hazard Class(es) Class: Label(s): Hazard No. (ADR): Tunnel restriction code: | 2 2.1 - (D) |
| 14.4 Packing Group: | _ |
| 14.5 Environmental hazards: | _ |
| 14.6 Special precautions for user: | - |
| ADN 14.6 Special precautions for user: | - |
| IMDG | |
| 14.1 UN Number: | UN 1950 |
| 14.2 UN Proper Shipping Name: 14.3 Transport Hazard Class(es) | AEROSOLS |
| Class: | 2.1 |
| Label(s): | 2.1 |
| EmS No.: | F-D, S-U |
| 14.3 Packing Group: | _ |
| 14.5 Environmental hazards: | _ |
| 14.6 Special precautions for user: | _ |
| | |





| IATA 14.1 UN Number: 14.2 Proper Shipping Name: 14.3 Transport Hazard Class(es): | UN 1950 Aerosols, flammable |
|-------------------------------------------------------------------------------------------|--------------------------------|
| Class: | 2.1 |
| Label(s): | 2.1 |
| 14.4 Packing Group: | - |
| 14.5 Environmental hazards: | - |
| 14.6 Special precautions for user: | - |

14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: not applicable.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

Regulation (EC) No. 2037/2000 Substances that deplete the ozone layer: none

Regulation (EC) No. 850/2004 on persistent organic pollutants: none

15.2 Chemical safety No Chemical Safety Assessment has been carried out. **assessment:**

SECTION 16: Other information

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

| worung or the h-state | |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| H220 | Extremely flammable gas. |
| H222 | Extremely flammable aerosol. |
| H226 | Flammable liquid and vapor. |
| H229 | Pressurized container: May burst if heated. |
| H280 | Contains gas under pressure; may explode if heated. |
| H304 | May be fatal if swallowed and enters airways. |
| H336 | May cause drowsiness or dizziness. |
| H412 | Harmful to aquatic life with long lasting effects. |
| Other information: | The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies. The classification results from the Conventional Method mentioned in regulation EU 1272/2008 (CLP). |
| Revision Date: | 05.10.2016 |





Disclaimer:

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.