



SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: GLEITMO WSP 5040 SPRAY

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer FUCHS LUBRITECH GmbH

Werner-Heisenberg-Straße 1

67661 Kaiserslautern/Germany

Telephone: +49 (0) 6301 3206-0

Fax: +49 (0) 6301 3206-940

US Distributor

Fuchs Lubricants Co. 17050 Lathrop Avenue Harvey, IL 60426

(708) 333-8900

(800) 255-3924 24 hrs Emergency

Contact Person: FUCHS LUBRITECH GmbH - Product Safety Management

Telephone: +49 (0) 6301 3206-0 Fax: +49 (0) 6301 3206-940

E-mail: INFO@FUCHS-LUBRITECH.DE

1.4 US contact telephone : 708-333-8900 **Emergency telephone : 800-255-3924**

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Aspiration Hazard Category 1

Hazard summary

Physical Hazards: Flammable aerosol.

Health Hazards

Ingestion: If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0





2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Precautionary Statements

Prevention: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

Storage: P410: Protect from sunlight.

P412: Do not expose to temperatures exceeding 50 oC/122oF.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular

hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the

environment without control.

Unknown toxicity:Due to information available product does not contain any ingredients of

unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

General information: Mixture of components with propellant in aerosol can.

Chemical name	Identifier	Concentration *	Notes
Butane	106-97-8	25.00 - <50.00%	
Propane	74-98-6	10.00 - <20.00%	
Hydrocarbons, low viscosity	64742-48-9	10.00 - <20.00%	
Lime hydrate	1305-62-0	5.00 - <10.00%	
Calcium Sulfonate	68584-23-6	1.00 - <5.00%	
inorganic Zink salt	7446-26-6	1.00 - <2.50%	
Calcium Sulfonate	61789-86-4	0.10 - <1.00%	
Ca Sulfonate	70024-69-0	0.10 - <1.00%	

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.





Classification

Chemical name	Identifier	Classification
Butane	106-97-8	Flam. Gas 1;H220, Press. Gas H280
Propane	74-98-6	Flam. Gas 1;H220, Press. Gas H280
Hydrocarbons, low viscosity	64742-48-9	Asp. Tox. 1;H304, Flam. Liq. 3;H226, Aquatic Chronic 3;H412
Lime hydrate	1305-62-0	Eye Dam. 1;H318, STOT SE 3;H335, Skin Irrit. 2;H315
Calcium Sulfonate	68584-23-6	Skin Sens. 1B;H317
inorganic Zink salt	7446-26-6	Aquatic Chronic 2;H411
Calcium Sulfonate	61789-86-4	Skin Sens. 1B;H317
Ca Sulfonate	70024-69-0	Skin Sens. 1B;H317

FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed:

If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special

treatment needed

Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

5.1 Extinguishing media

Suitable extinguishing

media:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger

fires with alcohol resistant foam or spray water with suitable surfactant

added

Unsuitable extinguishing

media:

Water with a full water jet.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 00000000601081101

Version: 1.0





5.2 Special hazards arising from the substance or mixture:

Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe

to do so.

6.3 Methods and material for containment and cleaning up:

g r

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.

7.2 Conditions for safe storage, including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and handling of aerosol cans and flammable liquids have to be kept. Keep away from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): Not applicable

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS_US - 000000000601081101

Version: 1.0





EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. Exposure Limits

Chemical name	Туре	Exposure Limit Valu	ues	Source
Propane	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Propane	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Mineral base oil - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Mineral base oil	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral base oil - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Mineral base oil	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Mineral base oil - Mist.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Base oil - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Base oil	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Base oil - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Base oil	TWA	400 ppm	1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Base oil - Mist.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
phenolic antioxidant	TWA		10 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
phenolic antioxidant - Inhalable fraction and vapor.	TWA		2 mg/m3	US. ACGIH Threshold Limit Values (02 2012)

8.2. Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective

equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS_US - 000000000601081101





Eye/face protection: Safety glasses (EN 166) recommended during refilling.

Skin protection

Hand Protection: Material: Nitrile-butadiene rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0.38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the

manufacturer of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser

pockets. Wear suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the workplace. Avoid breathing

vapour/ aerosol.

Thermal hazards: No data available.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

Environmental Controls: No data available.

PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Appearance

Physical state:AerosolsForm:AerosolsColor:Beige

Odor: Characteristic

Odor Threshold: Not applicable for mixtures

pH: Not applicable

Freezing point: Not applicable for mixtures

Boiling Point: Value not relevant for classification

Flash Point: < 0 °C

Evaporation Rate:Not applicable for mixtures

Flammability (solid, gas): Value not relevant for classification

Flammability Limit - Upper (%)—:

Flammability Limit - Lower (%)—:

Vapor pressure:

Vapor density (air=1):

Not applicable for mixtures

Solubility(ies)

9

Solubility in Water: The product is insoluble in water.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0





Solubility (other):No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Autoignition Temperature:

Decomposition Temperature:

Value not relevant for classification

9.2 Other information No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.

10.6 Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: No data available.

Ingestion: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Hydrocarbons, low

viscosity

LD 50 (Rat): > 15,000 mg/kg

CP1000600

Calcium Sulfonate LD 50 (Rat): > 16,000 mg/kg

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0

7/11





Dermal

Product:

Not classified for acute toxicity based on available data.

Inhalation Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Butane LC 50 (Rat, 4 h): 658 mg/l

Gas

Skin Corrosion/Irritation:

Product: OECD 404 (Rabbit): Not irritant.

Specified substance(s)

Calcium Sulfonate OECD 404 (Rabbit): Not irritant.

Serious Eye Damage/Eye Irritation:

Product: OECD 405 (Rabbit): Not irritant.

Specified substance(s)

Calcium Sulfonate OECD 405 (Rabbit): Not irritant.

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not

met.

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHASP: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Issue Date: 04.10.2016
Revision Date: 08.05.2018
Supersedes Date: 13.05.2018
SDS_US - 000000000601081101

Version: 1.0





Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Hydrocarbons, low

viscosity

LC 50 (Fish, 96 h): > 1,000 mg/l

Lime hydrate LC 50 (Fish, 96 h): 50.6 mg/l

Calcium Sulfonate LC 50 (Fish, 96 h): > 10,000 mg/l (OECD 203)

Ca Sulfonate LC 50 (Fish, 96 h): > 1,001 mg/l

Aquatic Invertebrates Specified substance(s)

Hydrocarbons, low

viscosity

EC 50 (Water Flea, 48 h): > 1,000 mg/l

Lime hydrate EC 50 (Water Flea, 48 h): 49.1 mg/l

inorganic Zink salt EC 50 (Water Flea, 48 h): 26 mg/l

Calcium Sulfonate EC 50 (Water flea (Simocephalus vetulus), 48 h): > 100 mg/l (OECD 202)

Ca Sulfonate EC 50 (Water Flea, 48 h): > 1,001 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants Specified substance(s)

Hydrocarbons, low

viscosity

EC 50 (Alga): > 1,000 mg/l

Lime hydrate EC 50 (Alga, 72 h): 184.57 mg/l

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Specified substance(s)

Calcium Sulfonate 8.6 % (28 d) Not easily biodegradable

12.3 Bioaccumulative potential

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0

9/11





Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects: No data available.

13 Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local

laws.

14 TRANSPORT INFORMATION

DOT

14.1 UN Number: UN 1950

14.2 Proper Shipping Name: Aerosols, flammable, n.o.s.

14.3 Transport Hazard Class(es): 2.1 14.4 Subsidiary risk label: – 14.5 Packing Group: – 14.6 Label(s): 2.1

IMDG - International Maritime Dangerous Goods Code

14.1 UN Number: UN 1950
14.2 UN Proper Shipping Name: AEROSOLS

14.3 Transport Hazard Class(es): 2.1
14.4 Subsidiary risk label: –
14.5 Packing Group: –

14.5 Packing Group: –
14.6 Label(s): 2.1
14.7 Marine Pollutant: –

14.8 EmS No.: F-D; S-U

IATA

14.1 UN Number: UN 1950

14.2 Proper Shipping Name: Aerosols, flammable

14.3 Transport Hazard Class(es): 2.1
14.4 Subsidiary risk label: 14.5 Packing Group: 14.6 Label(s): 2.1

15 REGULATORY INFORMATION

US Federal Regulations

US State Regulations

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0





Inventory Status

	DSL	On or in compliance with the inventory		
NDSL		Not in compliance with the inventory.		
	TSCA	On or in compliance with the inventory		

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapour.
H229	Pressurised container: May bu

urst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage. May cause respiratory irritation. H335

Toxic to aquatic life with long lasting effects. H411 H412 Harmful to aquatic life with long lasting effects.

Revision Date: 08.05.2018

Disclaimer: The data contained in this safety data sheet are based on our current

knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no

signature.

Issue Date: 04.10.2016 Revision Date: 08.05.2018 Supersedes Date: 13.05.2018 SDS US - 000000000601081101

Version: 1.0