

## SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

### 1 PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifier

**Product name:** STABYL LX 460 SYN

**Other means of identification:** For further information, please refer to section 9 of the SDS.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricating grease

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer**

FUCHS LUBRITECH GmbH  
Werner-Heisenberg-Straße 1  
67661 Kaiserslautern/Germany

US Distributor  
Fuchs Lubricants Co.  
17050 Lathrop Avenue  
Harvey, IL 60426

Telephone: +49 (0) 6301 3206-0  
Fax: +49 (0) 6301 3206-940

**Contact Person:**

Telephone: +49 (0) 6301 3206-0  
Fax: +49 (0) 6301 3206-940  
E-mail: INFO@FUCHS-LUBRITECH.DE

**1.4 US contact telephone :** 708-333-8900

**Emergency telephone:** 800-255-3924

### 2 HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous and does not need to be labelled according to the legislation in force.

**Hazard summary**

**Physical Hazards:** No data available.

**2.2 Label Elements** not applicable

**Product name:** STABYL LX 460 SYN

**2.3 Other hazards:** By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

**Unknown toxicity:** Due to information available product does not contain any ingredients of unknown toxicity.

### 3 COMPOSITION / INFORMATION ON INGREDIENTS

**General information:** Lubricating grease: Thickener system and additives in synthetic base oil.

Chemical name	Identifier	Concentration *	Notes
dilithium sebacate	19370-86-6	1.00 - <5.00%	
Ca sulfonate	939-603-7	1.00 - <5.00%	
Na sulphonate	85117-47-1	0.10 - <1.00%	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

#### Classification

Chemical name	Classification	
dilithium sebacate	19370-86-6	Acute Tox. 4;H302
Ca sulfonate	939-603-7	Skin Sens. 1B;H317
Na sulphonate	85117-47-1	Skin Sens. 1B;H317

### 4 FIRST AID MEASURES

**General:** Instantly remove any clothing soiled by the product.

#### 4.1 Description of first aid measures

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause skin and eye irritation.

---

**Product name:** STABYL LX 460 SYN

---

**4.3 Indication of any immediate medical attention and special treatment needed**      Get medical attention if symptoms occur.

<b>SECTION 5: Firefighting measures</b>
---

**5.1 Extinguishing media**

**Suitable extinguishing media:**      CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:**      Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture:**      During fire, gases hazardous to health may be formed.

**5.3 Advice for firefighters**

**Special fire fighting procedures:**      Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:**      Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

<b>SECTION 6: Accidental release measures</b>
---

**6.1 Personal precautions, protective equipment and emergency procedures:**      Not required.

**6.2 Environmental Precautions:**      Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

**6.3 Methods and material for containment and cleaning up:**      Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

**6.4 Reference to other sections:**      See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

Product name: STABYL LX 460 SYN

## SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.
- 7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed.
- 7.3 Specific end use(s):** No data available.

## 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1.Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
calciumcarbonate - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calciumcarbonate - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calciumcarbonate - Total dust.	TWA	15 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calciumcarbonate - Respirable fraction.	TWA	5 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

### 8.2.Exposure controls

- Appropriate engineering controls:** Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

#### Individual protection measures, such as personal protective equipment

- General information:** Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.
- Eye/face protection:** Safety glasses (EN 166) recommended during refilling.

**Product name:** STABYL LX 460 SYN

**Skin protection**

**Hand Protection:**

Material: Nitrile butyl rubber (NBR).  
Min. Breakthrough time:  $\geq 480$  min  
Recommended thickness of the material:  $\geq 0.38$  mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Other:**

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

**Respiratory Protection:**

Not relevant, due to the form of the product.

**Thermal hazards:**

No data available.

**Hygiene measures:**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

**Environmental Controls:**

No data available.

**9 PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties**

<b>Physical state:</b>	solid
<b>Form:</b>	Paste
<b>Color:</b>	Light brown
<b>Odor:</b>	Characteristic
<b>Odor Threshold:</b>	Not applicable for mixtures
<b>pH:</b>	not applicable
<b>Melting Point:</b>	Not applicable for mixtures
<b>Boiling Point:</b>	not applicable
<b>Flash Point:</b>	not applicable
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	Value not relevant for classification
<b>Flammability Limit - Upper (%)—:</b>	Not applicable for mixtures
<b>Flammability Limit - Lower (%)—:</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Vapor density (air=1):</b>	Not applicable for mixtures

---

**Product name:** STABYL LX 460 SYN

---

<b>Density:</b>	0.90 g/cm <sup>3</sup> (25 °C)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Autoignition Temperature:</b>	Value not relevant for classification
<b>Decomposition Temperature:</b>	Value not relevant for classification
<b>NLGI:</b>	1-2
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification
<b>9.2 Other information</b>	No data available.

#### SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

#### 11 TOXICOLOGICAL INFORMATION

##### Information on likely routes of exposure

<b>Inhalation:</b>	No data available.
<b>Ingestion:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.

---

**Product name:** STABYL LX 460 SYN

---

**Acute toxicity**

**Oral**

**Product:**

ATEmix: 10,018.23 mg/kg

**Specified substance(s)**

dilithium sebacate

LD 50 (Rat): (OECD 420)

**Dermal**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

dilithium sebacate

> 2,000 mg/kg

Read-across from supporting substance (structural analogue or surrogate),  
Key study

**Inhalation**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

dilithium sebacate

No data available.

**Skin Corrosion/Irritation:**

**Product:**

Based on available data, the classification criteria are not met.

**Specified substance(s)**

dilithium sebacate

OECD 431 Based on available data, the classification criteria are not met.  
OECD 439 Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation:**

**Product:**

Based on available data, the classification criteria are not met.

**Specified substance(s)**

dilithium sebacate

OECD 405 (Rabbit): Based on available data, the classification criteria are not met.

**Respiratory or Skin Sensitization:**

**Product:**

Experimental data has shown that the concentration of potentially sensitizing components present in this product does not induce skin sensitization.

**Specified substance(s)**

dilithium sebacate

, OECD 429 (Mouse)Based on available data, the classification criteria are not met.

---

**Product name:** STABYL LX 460 SYN

---

**Germ Cell Mutagenicity**

**Product:** Based on available data, the classification criteria are not met.

**In vitro**

**Specified substance(s)**

dilithium sebacate (OECD 471)

Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:** Based on available data, the classification criteria are not met.

**IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**NTP: US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Reproductive toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** Based on available data, the classification criteria are not met.

**Aspiration Hazard**

**Product:** Based on available data, the classification criteria are not met.

---

**12 ECOLOGICAL INFORMATION**

---

**12.1 Toxicity**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Fish**

**Specified substance(s)**

dilithium sebacate LC 50 (Fish, 96 h): 100 mg/l (OECD 203)

Ca sulfonate LC 50 (Fish, 96 h): > 101 mg/l



---

**Product name:** STABYL LX 460 SYN

---

**Aquatic Invertebrates**

**Specified substance(s)**

dilithium sebacate EC 50 (Water Flea, 48 h): 100 mg/l (OECD 202)

Ca sulfonate EC 50 (Water Flea, 48 h): > 1,001 mg/l

**Chronic ToxicityProduct:** Based on available data, the classification criteria are not met.

**Toxicity to Aquatic Plants**

**Specified substance(s)**

dilithium sebacate EC 50 (Alga, 72 h): 100 mg/l (OECD 201)

Ca sulfonate EC 50 (Alga, 72 h): > 101 mg/l

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures

**Specified substance(s)**

dilithium sebacate  
(OECD 301B) Inherently biodegradable  
(OECD 301D) Inherently biodegradable  
(OECD 301D) Inherently biodegradable  
(OECD 301E) Inherently biodegradable  
(OECD 302B) Inherently biodegradable

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Other adverse effects:** No data available.

---

**13 Disposal considerations**

---

**13.1 Waste treatment methods**

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

Product name: STABYL LX 460 SYN

## 14 TRANSPORT INFORMATION

### DOT

Not regulated.

### IMDG - International Maritime Dangerous Goods Code

Not regulated.

### IATA

Not regulated.

## 15 REGULATORY INFORMATION

### US Federal Regulations

### US State Regulations

### Inventory Status

TSCA

On or in compliance with the inventory

## 16 OTHER INFORMATION

**Revision Information:** Vertical lines in the margin indicate an amendment.

### Wording of the R-phrases and H-statements in section 2 and 3

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.

**Revision Date:** 10.10.2017

**Disclaimer:** The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.