

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: ANTICORIT CPX 3373 (SPRAYDOSE)

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Anticorrosion product

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer Fuchs Schmierstoffe GmbH <u>US Distributor</u>

Friesenheimer Str. 19
68169 Mannheim
Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Telephone: +49 621 3701-0 (ZENTRALE)

Fax: +49 621 3701-570

Contact Person: Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telephone: +49 621 3701-1333 Fax: +49 621 3701-7303

E-mail: PRODUKTSICHERHEIT@FUCHS-SCHMIERSTOFFE.DE

1.4 US contact telephone : 708-333-8900 **Emergency telephone: 800-255-3924**

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Aspiration Hazard Category 1

Hazard summary

Physical Hazards: Flammable aerosol.

Health Hazards

Issue Date: 30.10.2013 Revision Date: 20.04.2017 Supersedes Date: 19.02.2019 SDS US - 000000000601357190

Version: 1.1



Ingestion: If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately.

2.2 Label Elements



Signal Words: Danger

Hazard Statement(s): H222: Extremely flammable aerosol.

H229: Pressurized container: May burst if heated.

Precautionary Statements

Prevention: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

Storage: P410+P412: Protect from sunlight. Do not expose to temperatures

exceeding 50°C/122°F.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular

hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the

environment without control.

Unknown toxicity:Due to information available product does not contain any ingredients of

unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

General information: Mixture of active ingredients with propellant

Chemical name	Identifier	Concentration *	Notes
Isobutane (<0,1% 1,3-butadiene)	75-28-5	0.00 - 100.00%	
base oil, low viscous	72623-87-1	10.00 - 30.00%	
Calcium Sulfonate	61789-86-4	1.00 - 5.00%	

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Classification

Chemical name	Classification	
Isobutane (<0,1% 1,3-butadiene)	75-28-5	Flam. Gas 1;H220, Press. Gas Liq. Gas;H280
base oil, low viscous	72623-87-1	Asp. Tox. 1;H304
Calcium Sulfonate	61789-86-4	Skin Sens. 1B;H317

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Call a physician or poison control center immediately. Rinse mouth. Never

give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and

delayed:

If ingested, material may be aspirated into the lungs and cause chemical

pneumonitis. Treat appropriately. Dizziness Freeze burns

4.3 Indication of any immediate medical attention and special

treatment needed

Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

5.1 Extinguishing media

Suitable extinguishing

media:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger

fires with alcohol resistant foam or spray water with suitable surfactant

added

Unsuitable extinguishing

media:

Water with a full water jet.



5.2 Special hazards arising from the substance or mixture:

Danger of explosion with aerosol cans.

5.3 Advice for firefighters

Special fire fighting procedures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. Keep away from sources of ignition - No smoking.

6.2 Environmental Precautions:

Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Scrape up spillage or absorb with absorbing material. Stop the flow of material, if this is without risk. Dispose of the material collected according to regulations.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Avoid contact with flame and heat source, prevent contact with direct sunlight Use only in well-ventilated areas.



7.2 Conditions for safe storage, including any

incompatibilities:

Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Local regulations concerning handling and storage of waterpolluting products have to be followed. Local regulations for the storage and

handling of aerosol cans and flammable liquids have to be kept. Keep away

from heat/sparks/hot surfaces. - No smoking.

7.3 Specific end use(s): not applicable

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Exposure Limits

8

Chemical name	Туре	Exposure Limit Values	Source
Isobutane (<0,1% 1,3-butadiene)	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (02 2013)
base oil, low viscous - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
base oil, low viscous	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
base oil, low viscous - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
base oil, low viscous	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
base oil, low viscous - Mist.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calcium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calcium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calcium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calcium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calcium sulfate - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (02 2012)

8.2. Exposure controls



Appropriate engineering

controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation,

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information: Wash hands before breaks and after work. Use personal protective

equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to inhandling the chemicals or the mineral oil products.

Eye/face protection: Safety glasses (EN 166) recommended during refilling.

Skin protection

Hand Protection: Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0.38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the

manufacturer of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser

pockets. Wear suitable protective clothing.

Respiratory Protection: Ensure good ventilation/exhaustion at the workplace. Avoid breathing

vapour/ aerosol.

Thermal hazards: No data available.

Hygiene measures: Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing to remove contaminants. Discard contaminated

footwear that cannot be cleaned.

Environmental Controls: No data available.

PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties Appearance

Issue Date: 30.10.2013 Revision Date: 20.04.2017 Supersedes Date: 19.02.2019 SDS US - 000000000601357190

9



Physical state: Aerosols
Form: Aerosols
Color: Light brown
Odor: Characteristic

Odor Threshold: Not applicable for mixtures

pH: not applicable

Freezing point: Not applicable for mixtures

Boiling Point: Value not relevant for classification

Flash Point: < 0 °C

Evaporation Rate: Not applicable for mixtures

Flammability (solid, gas): Value not relevant for classification

Flammability Limit - Upper (%)—: Not applicable for mixtures
Flammability Limit - Lower (%)—: Not applicable for mixtures
Vapor pressure: Not applicable for mixtures
Vapor density (air=1): Not applicable for mixtures

Density: 1.05 g/cm3 (15 °C)

Solubility(ies)

Solubility in Water:Insoluble in waterSolubility (other):No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Autoignition Temperature:Value not relevant for classificationDecomposition Temperature:Value not relevant for classificationFlow time:Value not relevant for classificationExplosive properties:Value not relevant for classificationOxidizing properties:Value not relevant for classification

9.2 Other informationNo data available.

SECTION 10: Stability and reactivity

10.1 Reactivity: Stable under normal use conditions.

10.2 Chemical Stability: Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

10.4 Conditions to avoid: Stable under normal use conditions.

10.5 Incompatible Materials: Strong oxidizing substances. Strong acids. Strong bases.



10.6 Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation: No data available.

Ingestion: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

base oil, low viscous LD 50 (Rat): > 5,001 mg/kg (OECD 401)

Calcium Sulfonate LD 50 (Rat): > 16,000 mg/kg

Dermal

Product:

ATEmix: 17,703.01 mg/kg

Specified substance(s)

base oil, low viscous LD 50 (Rabbit): > 2,001 mg/kg (OECD 402)

Calcium Sulfonate LD 50 (Rat): > 4,000 mg/kg

Inhalation

Product:

Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product: Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.



Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not

met.

Respiratory sensitizer: Based on available data, the classification criteria

are not met.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHASP: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: May be fatal if swallowed and enters airways.

12 ECOLOGICAL INFORMATION



12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.Based on

available data, the classification criteria are not met.

Fish

Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

LC 50 (Fish, 96 h): 28 mg/l

base oil, low viscous LC 50 (Fish, 96 h): > 100 mg/l (OECD 203)

Aquatic Invertebrates Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Water Flea, 48 h): 16.3 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

base oil, low viscous NOEC (Fish, 14 d): > 1,000 mg/l

Aquatic Invertebrates Specified substance(s)

base oil, low viscous NOEC (Water Flea, 21 d): 10 mg/l (OECD 211)

Toxicity to Aquatic Plants Specified substance(s)

Isobutane (<0,1% 1,3-

butadiene)

EC 50 (Alga, 72 h): 8.6 mg/l

base oil, low viscous NOEC (Alga, 72 h): > 100 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

12.3 Bioaccumulative potential

Product: Not applicable for mixtures



12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects: No data available.

13 **Disposal considerations**

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local

14 TRANSPORT INFORMATION

DOT

14.1 UN Number: UN 1950

14.2 Proper Shipping Name: Aerosols, flammable, n.o.s.

14.3 Transport Hazard Class(es): 2.1 14.4 Subsidiary risk label: 14.5 Packing Group: 14.6 Label(s): 2.1

IMDG - International Maritime Dangerous Goods Code

14.1 UN Number: UN 1950 **AEROSOLS**

14.2 UN Proper Shipping Name:

14.3 Transport Hazard Class(es): 2.1 14.4 Subsidiary risk label: 14.5 Packing Group: 14.6 Label(s): 2.1 14.7 Marine Pollutant:

14.8 EmS No.: F-D; S-U

IATA

UN 1950 14.1 UN Number:

14.2 Proper Shipping Name: Aerosols, flammable

14.3 Transport Hazard Class(es): 2.1 14.4 Subsidiary risk label: 14.5 Packing Group: 14.6 Label(s): 2.1



15 REGULATORY INFORMATION

US Federal Regulations

US State Regulations

Inventory Status

TSCA	On or in compliance with the inventory

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the R-phrases and H-statements in section 2 and 3

H220 Extremely flammable gas.H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

Revision Date: 20.04.2017

Disclaimer: The data contained in this safety data sheet are based on our current

knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no

signature.