

# SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

## 1 PRODUCT AND COMPANY IDENTIFICATION

### 1.1 Product identifier

**Product name:** RENOLIT CX-TOM 15

**Other means of identification:** For further information, please refer to section 9 of the SDS.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricating grease

**Uses advised against:** No uses advised against identified.

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer

Fuchs Schmierstoffe GmbH  
Friesenheimer Str. 19  
68169 Mannheim

#### US Distributor

Fuchs Lubricants Co.  
17050 Lathrop Avenue  
Harvey, IL 60426

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

#### Contact Person:

Telephone:

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-mail:

PRODUKTSICHERHEIT@FUCHS-SCHMIERSTOFFE.DE

### 1.4 US contact telephone :

708-333-8900

#### Emergency telephone:

**800-255-3924**

## 2 HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

#### Health Hazards

Serious Eye Damage/Eye Irritation

Category 1

#### Environmental Hazards

Chronic hazards to the aquatic environment

Category 3

#### Hazard summary

##### Physical Hazards:

No data available.

**Product name:** RENOLIT CX-TOM 15

## 2.2 Label Elements



**Signal Words:** Danger

**Hazard Statement(s):** H318: Causes serious eye damage.  
H412: Harmful to aquatic life with long lasting effects.

### Precautionary Statements

**Prevention:** P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.

**Response:** P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor.

**2.3 Other hazards:** By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

**Unknown toxicity:** Due to information available product does not contain any ingredients of unknown toxicity.

## 3 COMPOSITION / INFORMATION ON INGREDIENTS

**General information:** Lubricating grease: Thickener system and additives in synthetic base oil.

Chemical name	Identifier	Concentration *	Notes
Calcium Sulfonate	68584-23-6	5.00 - <10.00%	
Ca-sulfonate	84989-14-0	3.00 - <5.00%	
Calcium Sulfonate	61789-86-4	1.00 - <5.00%	
Ca Sulfonate	70024-69-0	1.00 - <5.00%	
phenolic antioxidant	128-37-0	0.25 - <1.00%	
aromatic phosphoric acid ester derivative	115-86-6	0.25 - <1.00%	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.  
PBT: persistent, bioaccumulative and toxic substance.  
vPvB: very persistent and very bioaccumulative substance.

**Product name:** RENOLIT CX-TOM 15

### Classification

Chemical name	Identifier	Classification
Calcium Sulfonate	68584-23-6	Skin Sens. 1B;H317
Ca-sulfonate	84989-14-0	Eye Dam. 1;H318, Skin Irrit. 2;H315
Calcium Sulfonate	61789-86-4	Skin Sens. 1B;H317
Ca Sulfonate	70024-69-0	Skin Sens. 1B;H317
phenolic antioxidant	128-37-0	Aquatic Acute 1;H400, Aquatic Chronic 1;H410
aromatic phosphoric acid ester derivative	115-86-6	Aquatic Acute 1;H400, Aquatic Chronic 1;H410

## 4 FIRST AID MEASURES

**General:** Instantly remove any clothing soiled by the product.

### 4.1 Description of first aid measures

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** Risk of serious damage to eyes.

**4.3 Indication of any immediate medical attention and special treatment needed** Get medical attention if symptoms occur.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Unsuitable extinguishing media:** Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture:** During fire, gases hazardous to health may be formed.

### 5.3 Advice for firefighters

**Product name:** RENOLIT CX-TOM 15

<b>Special fire fighting procedures:</b>	Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.
<b>Special protective equipment for fire-fighters:</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

#### SECTION 6: Accidental release measures

<b>6.1 Personal precautions, protective equipment and emergency procedures:</b>	Not required.
<b>6.2 Environmental Precautions:</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so.
<b>6.3 Methods and material for containment and cleaning up:</b>	Scrape up spillage or absorb with absorbing material. Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
<b>6.4 Reference to other sections:</b>	See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.
	Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

#### SECTION 7: Handling and storage:

<b>7.1 Precautions for safe handling:</b>	Provide adequate ventilation. Observe good industrial hygiene practices. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products.
<b>7.2 Conditions for safe storage, including any incompatibilities:</b>	Local regulations concerning handling and storage of waterpolluting products have to be followed.
<b>7.3 Specific end use(s):</b>	not applicable

#### 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

**Product name:** RENOLIT CX-TOM 15

### 8.1. Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Base oil - Inhalable fraction.	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Base oil	PEL	500 ppm    2,000 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Base oil - Mist.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Base oil	TWA	400 ppm    1,600 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Base oil - Mist.	TWA	5 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calciumcarbonate - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calciumcarbonate - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
calciumcarbonate - Total dust.	TWA	15 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
calciumcarbonate - Respirable fraction.	TWA	5 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
phenolic antioxidant	TWA	10 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
phenolic antioxidant - Inhalable fraction and vapor.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (02 2012)
aromatic phosphoric acid ester derivative	PEL	3 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
aromatic phosphoric acid ester derivative	TWA	3 mg/m <sup>3</sup>	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
aromatic phosphoric acid ester derivative	TWA	3 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (02 2012)

### 8.2. Exposure controls

**Appropriate engineering controls:**

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information:**

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

**Eye/face protection:**

Safety glasses (EN 166) recommended during refilling. Avoid contact with eyes. Wear closed protection glasses.

**Product name:** RENOLIT CX-TOM 15

**Skin protection**

**Hand Protection:**

Material: Nitrile butyl rubber (NBR).  
 Min. Breakthrough time:  $\geq 480$  min  
 Recommended thickness of the material:  $\geq 0.38$  mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Other:**

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

**Respiratory Protection:**

Not relevant, due to the form of the product.

**Thermal hazards:**

No data available.

**Hygiene measures:**

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

**Environmental Controls:**

No data available.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

<b>Physical state:</b>	solid
<b>Form:</b>	Paste
<b>Color:</b>	Light brown
<b>Odor:</b>	Characteristic
<b>Odor Threshold:</b>	Not applicable for mixtures
<b>pH:</b>	not applicable
<b>Melting Point:</b>	Not applicable for mixtures
<b>Boiling Point:</b>	Value not relevant for classification
<b>Flash Point:</b>	not applicable
<b>Evaporation Rate:</b>	Not applicable for mixtures
<b>Flammability (solid, gas):</b>	Value not relevant for classification
<b>Flammability Limit - Upper (%)–:</b>	Not applicable for mixtures
<b>Flammability Limit - Lower (%)–:</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Vapor density (air=1):</b>	Not applicable for mixtures
<b>Density:</b>	0.95 g/ml (25.00 °C)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures

**Product name:** RENOLIT CX-TOM 15

<b>Autoignition Temperature:</b>	Value not relevant for classification
<b>Decomposition Temperature:</b>	Value not relevant for classification
<b>NLGI:</b>	1
<b>Explosive properties:</b>	Value not relevant for classification
<b>Oxidizing properties:</b>	Value not relevant for classification
<b>9.2 Other information</b>	No data available.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11 TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Inhalation:</b>	No data available.
<b>Ingestion:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	Causes serious eye damage.

### Acute toxicity

#### Oral

##### Product:

<b>Specified substance(s)</b>	Not classified for acute toxicity based on available data.
Calcium Sulfonate	LD 50 (Rat): > 16,000 mg/kg
phenolic antioxidant	LD 50 (Rat): 2,930 mg/kg (OECD 401)

**Product name:** RENOLIT CX-TOM 15

---

**Dermal**

**Product:**

Not classified for acute toxicity based on available data.

**Specified substance(s)**

phenolic antioxidant

LD 50 (Rat): > 5,000 mg/kg (OECD 402)

**Inhalation**

**Product:**

Not classified for acute toxicity based on available data.

**Skin Corrosion/Irritation:**

**Product:**

Based on available data, the classification criteria are not met.

**Serious Eye Damage/Eye Irritation:**

**Product:**

Based on available data, the classification criteria are met.

**Respiratory or Skin Sensitization:**

**Product:**

Experimental data has shown that the concentration of potentially sensitizing components present in this product does not induce skin sensitization.

**Specified substance(s)**

phenolic antioxidant

No sensitizing effect (guinea pig); OECD 406

**Germ Cell Mutagenicity**

**Product:**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:**

Based on available data, the classification criteria are not met.

**IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

No carcinogenic components identified

**NTP: US. National Toxicology Program (NTP) Report on Carcinogens:**

No carcinogenic components identified

**OSHASp: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Reproductive toxicity**

**Product:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:**

Based on available data, the classification criteria are not met.

**Aspiration Hazard**

**Product:**

Based on available data, the classification criteria are not met.



Product name: RENOLIT CX-TOM 15

## 12 ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Acute toxicity

**Product:** Based on available data, the classification criteria are not met.

#### Fish

##### Specified substance(s)

Ca Sulfonate LC 50 (Fish, 96 h): > 1,001 mg/l

aromatic phosphoric acid  
ester derivative LC 50 (Fish, 96 h): 0.8 mg/l

#### Aquatic Invertebrates

##### Specified substance(s)

Ca Sulfonate EC 50 (Water Flea, 48 h): > 1,001 mg/l

aromatic phosphoric acid  
ester derivative EC 50 (Water Flea, 48 h): 0.202 mg/l

**Chronic ToxicityProduct:** Based on available data, the classification criteria are met.

#### Aquatic Invertebrates

##### Specified substance(s)

phenolic antioxidant NOEC (Water Flea, 21 d): > 0.39 mg/l

### 12.2 Persistence and Degradability

#### Biodegradation

**Product:** Not applicable for mixtures

##### Specified substance(s)

Calcium Sulfonate 8.6 % Not easily biodegradable

phenolic antioxidant 30 % (OECD 302C)

### 12.3 Bioaccumulative potential

**Product:** Not applicable for mixtures

##### Specified substance(s)

phenolic antioxidant May be accumulated in organism

### 12.4 Mobility in soil:

**Product:** Not applicable for mixtures

### 12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

### 12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

**Product name:** RENOLIT CX-TOM 15

## 13 Disposal considerations

### 13.1 Waste treatment methods

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Discharge, treatment, or disposal may be subject to national, state, or local laws.

## 14 TRANSPORT INFORMATION

### DOT

Not regulated.

### IMDG - International Maritime Dangerous Goods Code

Not regulated.

### IATA

Not regulated.

## 15 REGULATORY INFORMATION

### US Federal Regulations

### US State Regulations

### Inventory Status

DSL	On or in compliance with the inventory
TSCA	On or in compliance with the inventory

## 16 OTHER INFORMATION

**Revision Information:** Vertical lines in the margin indicate an amendment.

### Wording of the H-statements in section 2 and 3

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Revision Date:** 24.11.2017

---

**Product name:** RENOLIT CX-TOM 15

---

**Disclaimer:**

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.