

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: TITAN ATF 6400

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Fuchs Schmierstoffe GmbH
Friesenheimer Str. 19
68169 Mannheim

US Distributor

Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Telephone:

+49 621 3701-0 (ZENTRALE)

(708) 333-8900

Fax:

+49 621 3701-570

(800) 255-3924 24 hrs Emergency

Contact Person:

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telephone:

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-mail:

produktsicherheit-FS@fuchs.com

1.4 US contact telephone :

708-333-8900

Emergency telephone:

800-255-3924

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to the legislation in force.

Environmental Hazards

Chronic hazards to the aquatic environment Category 3

Hazard summary

Physical Hazards:

No data available.

Product name: TITAN ATF 6400

2.2 Label Elements

Hazard Statement(s): H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention: P273: Avoid release to the environment.

Disposal: P501: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

General information: Mixture containing severely refined base oils and additives.

Chemical name	Identifier	Concentration *	Notes
Base oil, low viscous	64742-55-8	20.00 - <50.00%	
Alkoxysulfolane	398141-87-2	1.00 - <2.50%	
Heterocyclic N-compound	95-38-5	0.01 - <1.00%	
substituted hydrocarbyl sulphide	67124-09-8	0.25 - <1.00%	
Alkyl amine derivative	471-920-1	0.10 - <1.00%	
Alkyl amine derivative	897393-64-5	0.10 - <1.00%	
olefin derivative	Polymer	0.10 - <1.00%	
Ca Sulfonate	70024-69-0	0.10 - <1.00%	
ethoxylated amine	1218787-32-6	0.01 - <1.00%	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Product name: TITAN ATF 6400

Classification

Chemical name	Identifier	Classification
Base oil, low viscous	64742-55-8	Asp. Tox. 1;H304
Alkoxysulfolane	398141-87-2	Aquatic Chronic 2;H411
Heterocyclic N-compound	95-38-5	Skin Corr. 1C;H314, STOT RE 2;H373, Aquatic Acute 1;H400, Aquatic Chronic 1;H410, Acute Tox. 4;H302; M-Factor (aquatic acute): 10; M-Factor (aquatic chronic): 1
substituted hydrocarbyl sulphide	67124-09-8	Aquatic Acute 1;H400, Aquatic Chronic 1;H410, Skin Sens. 1;H317
Alkyl amine derivative	471-920-1	Skin Sens. 1B;H317
Alkyl amine derivative	897393-64-5	Aquatic Chronic 3;H412, Skin Sens. 1B;H317
olefin derivative	Polymer	Skin Sens. 1B;H317
Ca Sulfonate	70024-69-0	Skin Sens. 1B;H317
ethoxylated amine	1218787-32-6	Skin Corr. 1C;H314, Aquatic Acute 1;H400, Aquatic Chronic 2;H411, Acute Tox. 4;H302, Eye Dam. 1;H318; M-Factor (aquatic acute): 10; M-Factor (aquatic chronic): 1

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Note L of Annex VI of Regulation EC 1272/2008."

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Product name: TITAN ATF 6400

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions: Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

6.4 Reference to other sections: See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

7.1 Precautions for safe handling: Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibilities: Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

7.3 Specific end use(s): Not applicable

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Product name: TITAN ATF 6400

8.1.Exposure Limits

Chemical name	Type	Exposure Limit Values	Source
Base oil, low viscous - Mist.	PEL	5 mg/m ³	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Base oil, low viscous - Mist.	TWA	5 mg/m ³	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Base oil, low viscous - Inhalable fraction.	TWA	5 mg/m ³	US. ACGIH Threshold Limit Values (03 2014)

8.2.Exposure controls

Appropriate engineering controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information:

Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Eye/face protection:

Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

Skin protection

Hand Protection:

Material: Nitrile-butadiene rubber (NBR).
 Min. Breakthrough time: ≥ 480 min
 Recommended thickness of the material: ≥ 0.38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Other:

Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

Respiratory Protection:

Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

Thermal hazards:

No data available.

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

Environmental Controls:

No data available.

Product name: TITAN ATF 6400

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state:	liquid
Form:	liquid
Color:	Red
Odor:	Characteristic
Odor Threshold:	Not applicable for mixtures
pH:	Not applicable
Freezing point:	Not applicable for mixtures
Boiling Point:	Value not relevant for classification
Flash Point:	210 °C
Evaporation Rate:	Not applicable for mixtures
Flammability (solid, gas):	Value not relevant for classification
Flammability Limit - Upper (%):	Not applicable for mixtures
Flammability Limit - Lower (%):	Not applicable for mixtures
Vapor pressure:	Not applicable for mixtures
Vapor density (air=1):	Not applicable for mixtures
Density:	0.84 g/cm ³ (15 °C)
Solubility(ies)	
Solubility in Water:	Insoluble in water
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	Not applicable for mixtures
Autoignition Temperature:	Value not relevant for classification
Decomposition Temperature:	Value not relevant for classification
Kinematic viscosity:	26 mm ² /s (40 °C)
Explosive properties:	Value not relevant for classification
Oxidizing properties:	Value not relevant for classification
9.2 Other information	No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity:	Stable under normal use conditions.
10.2 Chemical Stability:	Stable under normal use conditions.
10.3 Possibility of hazardous reactions:	Stable under normal use conditions.
10.4 Conditions to avoid:	Stable under normal use conditions.
10.5 Incompatible Materials:	Strong oxidizing substances. Strong acids. Strong bases.
10.6 Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

Product name: TITAN ATF 6400

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation:	No data available.
Ingestion:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.

Acute toxicity

Oral

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Heterocyclic N-compound LD 50 (Rat): 1,265 mg/kg (OECD 401)

substituted hydrocarbyl sulphide LD 50 (Rat): > 5,000 mg/kg

Ca Sulfonate LD 50 (Rat): > 5,000 mg/kg (OECD 401)

Dermal

Product:

Not classified for acute toxicity based on available data.

Specified substance(s)

Ca Sulfonate LD 50 (Rabbit): > 5,000 mg/kg (OECD 402)

Inhalation

Product:

Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Heterocyclic N-compound OECD 404 (Rabbit): Corrosive.

Serious Eye Damage/Eye Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

Heterocyclic N-compound OECD 405 (Rabbit): Corrosive.

Product name: TITAN ATF 6400

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.
Respiratory sensitizer: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

Alkoxysulfolane	LC 50 (Fish, 96 h): 2.4 mg/l
Heterocyclic N-compound	LC 50 (Fish, 96 h): 0.3 mg/l (OECD 203)
olefin derivative	LC 50 (Fish, 96 h): > 101 mg/l
Ca Sulfonate	LC 50 (Fish, 96 h): > 1,001 mg/l
ethoxylated amine	LC 50 (Fish, 96 h): 0.1 mg/l

Product name: TITAN ATF 6400

Aquatic Invertebrates

Specified substance(s)

Alkoxysulfolane	EC 50 (Water Flea, 48 h): 4.6 mg/l
Heterocyclic N-compound	EC 50 (Water Flea, 48 h): 0.136 mg/l (OECD 202)
substituted hydrocarbyl sulphide	EC 50 (Water Flea, 48 h): 0.58 mg/l
Alkyl amine derivative	EC 50 (Water Flea, 48 h): 180 mg/l
olefin derivative	EC 50 (Water Flea, 48 h): > 101 mg/l
Ca Sulfonate	EC 50 (Water Flea, 48 h): > 1,001 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are met.

Fish

Specified substance(s)

Alkoxysulfolane	NOEC (Fish, 96 d): 1 mg/l
-----------------	---------------------------

Aquatic Invertebrates

Specified substance(s)

Alkoxysulfolane	NOEC (Water Flea, 48 d): 0.63 mg/l
substituted hydrocarbyl sulphide	EC 50 (Water Flea, 21 d): 0.75 mg/l
Alkyl amine derivative	NOEC (Water Flea, 21 d): 56 mg/l
olefin derivative	NOEC (Water Flea, 21 d): 10 mg/l
ethoxylated amine	EC 10 (Water Flea, 21 d): 0.0107 mg/l

Toxicity to Aquatic Plants

Specified substance(s)

Alkoxysulfolane	NOEC (Alga, 72 h): 0.313 mg/l
Heterocyclic N-compound	EC 50 (Alga, 72 h): 0.03 mg/l (OECD 201) NOEC (Alga, 72 h): 0.11 mg/l
substituted hydrocarbyl sulphide	NOEC (Alga, 96 h): 100 mg/l
olefin derivative	EC 50 (Alga, 72 h): > 101 mg/l
Ca Sulfonate	EC 50 (Alga, 72 h): > 1,000 mg/l
ethoxylated amine	NOEC (Alga, 72 h): 0.0156 mg/l

12.2 Persistence and Degradability

Biodegradation

Product name: TITAN ATF 6400

Product: Not applicable for mixtures
Specified substance(s)
 Heterocyclic N-compound (OECD 301B) The product is not biodegradable.
 ethoxylated amine 63 % (28 d, OECD 301D)

12.3 Bioaccumulative potential

Product: Not applicable for mixtures

12.4 Mobility in soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other adverse effects:

Harmful to aquatic life with long lasting effects.

13 Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Discharge, treatment, or disposal may be subject to national, state, or local laws.

14 TRANSPORT INFORMATION

DOT

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.

IATA

Not regulated.

15 REGULATORY INFORMATION

US Federal Regulations

US State Regulations

Inventory Status

DSL	Q (quantity restricted)
TSCA	On or in compliance with the inventory

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Product name: TITAN ATF 6400

Wording of the H-statements in section 2 and 3

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision Date: 27.05.2019

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.