

SAFETY DATA SHEET

acc.to ISO/DIS 11014 for USA

1 PRODUCT AND COMPANY IDENTIFICATION

1.1 Product identifier

Product name: TITAN CARGO MAXX 10W-40

Other means of identification: For further information, please refer to section 9 of the SDS.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

Uses advised against: No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer

Fuchs Schmierstoffe GmbH
Friesenheimer Str. 19
68169 Mannheim

US Distributor

Fuchs Lubricants Co.
17050 Lathrop Avenue
Harvey, IL 60426

Telephone:

+49 621 3701-0 (ZENTRALE)

Fax:

+49 621 3701-570

Contact Person:

Fuchs Schmierstoffe GmbH Abteilung Produktsicherheit

Telephone:

+49 621 3701-1333

Fax:

+49 621 3701-7303

E-mail:

PRODUKTSICHERHEIT@FUCHS-SCHMIERSTOFFE.DE

1.4 US contact telephone :

708-333-8900

Emergency telephone:

800-255-3924

2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

The product has not been classified as hazardous and does not need to be labelled according to the legislation in force.

Hazard summary

Physical Hazards:

No data available.

2.2 Label Elements

not applicable

Product name: TITAN CARGO MAXX 10W-40

2.3 Other hazards: By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

Unknown toxicity: Due to information available product does not contain any ingredients of unknown toxicity.

3 COMPOSITION / INFORMATION ON INGREDIENTS

General information: Mixture containing severely refined base oils and additives.

| Chemical name | Identifier | Concentration * | Notes |
|---------------------------|--------------|-----------------|-------|
| baseoil, low viscous | 72623-87-1 | 15.00 - 40.00% | |
| alkylphenol | 125643-61-0 | 1.00 - 5.00% | |
| alkarylamine, longchained | 36878-20-3 | 1.00 - 5.00% | |
| zinc dithiophosphate | 93819-94-4 | 1.00 - 5.00% | |
| Alkyl phenol, long chain | 1190625-94-5 | 0.10 - 1.00% | |

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

Classification

| Chemical name | Classification | |
|---------------------------|----------------|---|
| baseoil, low viscous | 72623-87-1 | Asp. Tox. 1;H304 |
| alkylphenol | 125643-61-0 | Aquatic Chronic 4;H413 |
| alkarylamine, longchained | 36878-20-3 | Aquatic Chronic 4;H413 |
| zinc dithiophosphate | 93819-94-4 | Skin Irrit. 2;H315, Eye Dam. 1;H318, Aquatic Chronic 2;H411 |
| Alkyl phenol, long chain | 1190625-94-5 | Skin Sens. 1B;H317, STOT RE 2;H373 |

4 FIRST AID MEASURES

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

Eye contact: Promptly wash eyes with plenty of water while lifting the eye lids.

Skin Contact: Wash with soap and water.

Product name: TITAN CARGO MAXX 10W-40

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed: May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed Get medical attention if symptoms occur.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: CO₂, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

Unsuitable extinguishing media: Water with a full water jet.

5.2 Special hazards arising from the substance or mixture: During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire fighting procedures: Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures: In case of spills, beware of slippery floors and surfaces.

6.2 Environmental Precautions: Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

Product name: TITAN CARGO MAXX 10W-40

- 6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.
- 6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

SECTION 7: Handling and storage:

- 7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.
- 7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.
- 7.3 Specific end use(s):** No data available.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1.Exposure Limits

| Chemical name | type | Exposure Limit Values | Source |
|------------------------------|------|-----------------------|--|
| base oil, paraffinic | TWA | 400 ppm 1,600 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |
| base oil, paraffinic - Mist. | TWA | 5 mg/m3 | US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989) |

8.2.Exposure controls

- Appropriate engineering controls:** Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

- General information:** Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

Product name: TITAN CARGO MAXX 10W-40

| | |
|--------------------------------|---|
| Eye/face protection: | Safety glasses (EN 166) recommended during refilling. |
| Skin protection | |
| Hand Protection: | Material: Nitrile butyl rubber (NBR). Min. Breakthrough time: ≥ 480 min Recommended thickness of the material: ≥ 0.38 mm Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. |
| Other: | Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing. |
| Respiratory Protection: | Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol. |
| Thermal hazards: | No data available. |
| Hygiene measures: | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. |
| Environmental Controls: | No data available. |

9 PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | |
|---------------------------------------|---------------------------------------|
| Physical state: | liquid |
| Form: | liquid |
| Color: | Amber |
| Odor: | Characteristic |
| Odor Threshold: | Not applicable for mixtures |
| pH: | not applicable |
| Freezing point: | Not applicable for mixtures |
| Boiling Point: | Value not relevant for classification |
| Flash Point: | 238 °C |
| Evaporation Rate: | Not applicable for mixtures |
| Flammability (solid, gas): | Value not relevant for classification |
| Flammability Limit - Upper (%) | Not applicable for mixtures |

Product name: TITAN CARGO MAXX 10W-40

| | |
|---|---------------------------------------|
| Flammability Limit - Lower (%)—: | Not applicable for mixtures |
| Vapor pressure: | Not applicable for mixtures |
| Vapor density (air=1): | Not applicable for mixtures |
| Density: | 0.86 g/ml (15.00 °C) |
| Solubility(ies) | |
| Solubility in Water: | Insoluble in water |
| Solubility (other): | No data available. |
| Partition coefficient (n-octanol/water): | Not applicable for mixtures |
| Autoignition Temperature: | Value not relevant for classification |
| Decomposition Temperature: | Value not relevant for classification |
| Kinematic viscosity: | 97.37 mm ² /s (40.00 °C) |
| Explosive properties: | Value not relevant for classification |
| Oxidizing properties: | Value not relevant for classification |
| 9.2 Other information | No data available. |

SECTION 10: Stability and reactivity

| | |
|---|---|
| 10.1 Reactivity: | Stable under normal use conditions. |
| 10.2 Chemical Stability: | Stable under normal use conditions. |
| 10.3 Possibility of hazardous reactions: | Stable under normal use conditions. |
| 10.4 Conditions to avoid: | Stable under normal use conditions. |
| 10.5 Incompatible Materials: | Strong oxidizing substances. Strong acids. Strong bases. |
| 10.6 Hazardous Decomposition Products: | Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors. |

11 TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| | |
|----------------------|--------------------|
| Inhalation: | No data available. |
| Ingestion: | No data available. |
| Skin Contact: | No data available. |
| Eye contact: | No data available. |

Product name: TITAN CARGO MAXX 10W-40

Acute toxicity

Oral

Product:

ATEmix: 2,731.72 mg/kg

Specified substance(s)

baseoil, low viscous

LD 50 (Rat): > 2,001 mg/kg

alkylphenol

LD 50 (Rat): > 2,001 mg/kg (OECD 401)

alkarylamine,
longchained

LD 50 (Rat): > 5,001 mg/kg (OECD 423)

zinc dithiophosphate

LD 50 (Rat): 2,600 mg/kg

Dermal

Product:

ATEmix: 2,659.98 mg/kg

Specified substance(s)

baseoil, low viscous

LD 50 (Rabbit): > 2,001 mg/kg

alkylphenol

LD 50 (Rat): > 2,001 mg/kg (OECD 402)

alkarylamine,
longchained

LD 50 (Rat): > 2,001 mg/kg (OECD 402)

zinc dithiophosphate

LD 50 (Rabbit): > 3,160 mg/kg

Inhalation

Product:

Not classified for acute toxicity based on available data.

Skin Corrosion/Irritation:

Product:

Based on available data, the classification criteria are not met.

Specified substance(s)

alkylphenol

OECD 404 (Rabbit): Not irritant.

alkarylamine,
longchained

OECD 404 (Rabbit): Not irritant.

Product name: TITAN CARGO MAXX 10W-40

Serious Eye Damage/Eye Irritation:

Product: Based on available data, the classification criteria are not met.

Specified substance(s)

alkylphenol OECD 405 (Rabbit): Not irritant.

alkarylamine, OECD 405 (Rabbit): Not irritant.
longchained

Respiratory or Skin Sensitization:

Product: Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

Specified substance(s)

alkylphenol No sensitizing effect (guinea pig); OECD 406

alkarylamine, No sensitizing effect (guinea pig); OECD 406
longchained

Germ Cell Mutagenicity

Product: Based on available data, the classification criteria are not met.

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

IARC: IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

NTP: US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

OSHAS: US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product name: TITAN CARGO MAXX 10W-40

Product: Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

12.1 Toxicity

Acute toxicity

Product: Based on available data, the classification criteria are not met.

Fish

Specified substance(s)

alkylphenol LC 50 (Fish, 96 h): > 74 mg/l (OECD 203)

alkarylamine,
longchained LC 50 (Fish, 96 h): > 101 mg/l (OECD 203)

zinc dithiophosphate LC 50 (Fish, 96 h): 4.5 mg/l (OECD 203)

Aquatic Invertebrates

Specified substance(s)

alkylphenol EC 50 (Water Flea, 24 h): > 101 mg/l (OECD 202)

alkarylamine,
longchained EC 50 (Water Flea, 48 h): > 101 mg/l (OECD 202)

zinc dithiophosphate EC 50 (Water Flea, 48 h): 5.4 mg/l (OECD 202)

Chronic ToxicityProduct: Based on available data, the classification criteria are not met.

Toxicity to Aquatic Plants

Specified substance(s)

alkylphenol EC 50 (Alga, 72 h): > 3 mg/l (OECD 201)

alkarylamine,
longchained EC 50 (Alga, 72 h): > 101 mg/l (OECD 201)

12.2 Persistence and Degradability

Biodegradation

Product: Not applicable for mixtures

Product name: TITAN CARGO MAXX 10W-40

Specified substance(s)

| | |
|------------------------------|--|
| alkylphenol | (OECD 301B) The product is not biodegradable. |
| alkarylamine, longchained | 1 % (28 d, OECD 301B) The product is slightly biodegradable. |
| zinc dithiophosphate | 1.5 % (28 d, OECD 301B) The product is slightly biodegradable. |

12.3 Bioaccumulative Potential

Product: Not applicable for mixtures

Specified substance(s)

| | |
|------------------------------|---|
| alkylphenol | Oncorhynchus mykiss, Bioconcentration Factor (BCF): 260 (OECD 305) May be accumulated in organism |
| alkarylamine, longchained | Bioconcentration Factor (BCF): 1,584 |
| zinc dithiophosphate | Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected. |

12.4 Mobility in Soil:

Product: Not applicable for mixtures

12.5 Results of PBT and vPvB assessment:

The product does not contain any substances fulfilling the PBT/vPvB criteria.

12.6 Other Adverse Effects:

No data available.

13 Disposal considerations

13.1 Waste treatment methods

General information: Dispose in accordance with all applicable regulations.

Disposal methods: Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

14 TRANSPORT INFORMATION

DOT

Not regulated.

IMDG - International Maritime Dangerous Goods Code

Not regulated.

Product name: TITAN CARGO MAXX 10W-40

IATA

Not regulated.

15 REGULATORY INFORMATION

US Federal Regulations

Inventory Status

| | |
|------|--|
| TSCA | On or in compliance with the inventory |
|------|--|

16 OTHER INFORMATION

Revision Information: Vertical lines in the margin indicate an amendment.

Wording of the R-phrases and H-statements in section 2 and 3

| | |
|------|--|
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H411 | Toxic to aquatic life with long lasting effects. |
| H413 | May cause long lasting harmful effects to aquatic life. |

Revision Date: 09.09.2016

Disclaimer: The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.